

MATERIAL SAFETY DATA SHEET

132

DATE OF PREPARATION
OCT 08 1986

AGL-3

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor "Essentially Similar" to Form OSHA-20)

-72

Section I

American Art Clay Co., Inc.
Reward Ceramic Color Mfrs., Co.
4717 W. Sixteenth Street
Indianapolis, IN 46222

EMERGENCY TELEPHONE NO.:
(317) 244-6871, (800) 428-3239, (800) 358-8252,
or contact your local poison control center.
TELEX 272145 AMACO IND

PRODUCT CLASS: Liquid & Dry Ceramic Glaze TRADE NAME: AMACO

MANUFACTURERS CODE IDENTIFICATION: LG 10, 20, 21, 25, 30, 32, 34, 36, 45, 50, 51, 53
54, 55, 56, 60, 62, 65, 66
LF 952, 953, 960, 965
CTL 35, 36, 50, 54, 65
SP 57, 58, 62, 63, 66, 67 - SP 10

Packaging: 1 Lb. Dry, 1 Pint Liquid
1 Gallon Liquid

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/M3		
NO ACUTE HAZARDOUS INGREDIENTS Lead Borosilicate Bears the CL Seal - Conforms to ASTM D-4236 See Section V	ave 10/25	N/A	.15 as Pb.	N/A	N/A

Section III - SPECIAL LABELING INSTRUCTIONS

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with the following seal:



"Products bearing the CL Certified Label Conformance Statement of The Art and Craft Materials Institute, Inc. are certified to be properly labeled in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board."

Section III - PHYSICAL DATA

BOILING RANGE: NOT APPLICABLE

VAPOR DENSITY: NOT APPLICABLE, HEAVIER, LIGHTER, THAN AIR

EVAPORATION RATE: NOT APPLICABLE,
 FASTER, SLOWER, THAN ETHER

PERCENT VOLATILE BY VOLUME: None

SPECIFIC GRAVITY: Sp Gr 2

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: N/A

FLASH POINT: NOT APPLICABLE

LEL: N/A

EXTINGUISHING MEDIA: NOT APPLICABLE - no fire or explosion hazard

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

SPECIAL FIRE FIGHTING PROCEDURES: NONE

004030

2 #132
Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE. TLV not established for the whole product.

CL - Seal - Labeling conforms to ASTM D4236

EFFECTS OF OVEREXPOSURE

None

EMERGENCY AND FIRST AID PROCEDURES Not applicable. No acute hazard.

Section VI - REACTIVITY DATA

STABILITY UNSTABLE STABLE CONDITIONS TO AVOID.

INCOMPATIBILITY (materials to avoid): None

HAZARDOUS DECOMPOSITION PRODUCTS None.

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID. Keep liquid glaze covered, uncovered glazes will dry out.

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Clean with paper towel and wet sponge.

WASTE DISPOSAL METHOD Dispose of paper towel in trash and rinse wet sponge.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION 1) Not needed for normal application of liquid glaze. When using one pound bags of dry glaze, care should be taken when mixing water not to create a dust.

2) For spray application and when mixing large quantities of dry glaze, use NIOSH Certified Mask.

VENTILATION: 1) Not needed for normal application of liquid glaze.

2) Locally exhausting hood appropriate for the operation, for spray application and when mixing large quantities of dry glaze.

PROTECTIVE GLOVES N/A

EYE PROTECTION: N/A

OTHER PROTECTIVE EQUIPMENT N/A

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: None

OTHER PRECAUTIONS

When using do not eat, drink or smoke. Wear a work apron and wash hands immediately after use. Not for unsupervised children.