

# MATERIAL SAFETY DATA SHEET

545  
NPCA 1-72  
~~000012~~

FOR COATINGS, RESINS AND RELATED MATERIALS  
(Approved by US Department of Labor "Essentially Similar" to Form OSHA-20)

DATE OF PREPARATION  
**OCT 08 1986** AMO 1

### Section 1

**American Art Clay Co., Inc.**  
**Reward Ceramic Color Mfrs., Co.**  
**4717 W. Sixteenth Street**  
**Indianapolis, IN 46222**

EMERGENCY TELEPHONE NO.  
(317) 244-6871, (800) 428-3239, (800) 358-8252,  
or contact your local poison control center.  
TELEX 272145 AMACO IND

PRODUCT CLASS: Liquid Ceramic Product TRADE NAME: AMACO

MANUFACTURERS CODE IDENTIFICATION: Plaster Separator Packaging: 16 oz.  
Gum Solution 16 oz. & 1 Gal.

### Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/M3		
Bears the AP Seal Conforms to ASTM D4236					
Non-Toxic	100%	NA	NA	NA	NA
Section V					

### SPECIAL LABELING INSTRUCTIONS

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with one of the following nontoxic seals:



"Products bearing the Certified Products Seal or the AP Approved Product Seal of The Art Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

In addition, products bearing the CP Seal meet specific requirements of materials, workmanship, working qualities and color described in the appropriate Product Standard issued by The Art and Craft Materials Institute, Inc. or other recognized standards organization."

### Section III - PHYSICAL DATA

BOILING RANGE:  NOT APPLICABLE VAPOR DENSITY:  NOT APPLICABLE,  HEAVIER,  LIGHTER, THAN AIR

EVAPORATION RATE:  NOT APPLICABLE,  FASTER,  SLOWER, THAN ETHER PERCENT VOLATILE BY VOLUME: ( ) ( ) SPECIFIC GRAVITY: Less than 2

### Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: NA FLASH POINT:  NOT APPLICABLE LEL: NA

EXTINGUISHING MEDIA:  NOT APPLICABLE - no fire or explosion hazard  
**No fire or explosion hazard.**

UNUSUAL FIRE AND EXPLOSION HAZARDS:  NONE  
**None**

SPECIAL FIRE FIGHTING PROCEDURES:  NONE

**Section V - HEALTH HAZARD DATA**

THRESHOLD LIMIT VALUE: Non-Toxic - Bears AP Seal - Labeling conforms to ASTM D4236

EFFECTS OF OVEREXPOSURE:  
None

EMERGENCY AND FIRST AID PROCEDURES:  
Not applicable

**Section VI - REACTIVITY DATA**

STABILITY:  UNSTABLE  STABLE      CONDITIONS TO AVOID: None

INCOMPATIBILITY (materials to avoid):

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION:  MAY OCCUR  WILL NOT OCCUR

CONDITIONS TO AVOID:

Keep lid on when storing.  
It will dry out if left uncovered.

**Section VII - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Clean thoroughly with paper towel and wet sponge.

WASTE DISPOSAL METHOD:

Dispose of paper towel in trash and rinse wet sponge.

**Section VIII - SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:

NA

VENTILATION:

Not needed

PROTECTIVE GLOVES: Not needed

EYE PROTECTION: Not needed

OTHER PROTECTIVE EQUIPMENT: Not needed

**Section IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING.

None

OTHER PRECAUTIONS:

None