

Rating\* Health 2 Flammability 4 Reactivity 0 Special 0

HMIS Rating\* Health 2 Flammability 4 Reactivity 0 Personal Protection B

# Material Safety Data Sheet

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200 and OSHA FORM 174.

DOT HAZARD CLASSIFICATION: **Wilcox Paper Co.**  
 Identify (Trade Name As Used On Label) **5916 Court Street Road**  
**MISTY STUCK-UP** **P.O. Box 378**  
 MSDS Number\* **Syracuse, N.Y. 13206-0378**  
**311-2** **(315) 437-1496**

MANUFACTURER'S NAME  
**AMREP, INC.**

CHEM TREC: **1-800-424-9300**

ADDRESS  
**990 Industrial Park Drive**

Date Prepared  
**10/10/89**

**Marietta, Georgia 30062**

Prepared By\*  
**TMJ/STN**


Phone Number (For Information)  
**(404) 386-3083**

Emergency Phone Number  
**(404) 386-3083**

NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

## SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS - Chemical Name & Common Names (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	APPROX. % (wt)*	OSHA PEL (ppm)	ACGIH TLV (ppm)	CARCINOGEN REFERENCE SOURCE**
Acetone	67-64-1	20	100	750	d
Methyl chloroform	71-55-6	20	350	350	d
Isobutane/Propane blend	75-28-5 74-98-6	50	1000	1000	d
<b>WILCOX PAPER COMPANY</b> <b>5916 COURT ST. ROAD</b> <b>BOX EASTWOOD STATION</b> <b>SYRACUSE, N.Y. 13208</b> <b>PHONE: (315) 437-1496</b>					
NOTICE: THIS PRODUCT MAY CONTAIN ONE OF THE LISTED SARA TITLE III SECTION 313 CHEMICALS.					
67-64-1 Acetone	71-55-6 1,1,1-Trichloroethane	1363-67-7 Titanium Dioxide			
50-00-0 Formaldehyde	75-09-2 Methylene chloride	7664-38-2 Phosphoric Acid			
67-56-1 Methanol	107-21-1 Ethylene glycol*	7761-88-8 Silver nitrate			
95-48-7 o-Cresol	114-26-1 Propoxur	7664-93-9 Sulfuric Acid			
94-75-7 2,4-D	108-88-3 Toluene	7440-66-6 Zinc (dust)			
72-43-5 Methoxychlor	127-18-4 Tetrachloroethylene	7647-01-0 Hydrochloric Acid			
78-92-2 sec-Butyl alcohol	139-13-9 Nitritotriacetic Acid	1330-20-7 Xylene, mixed isomers			
*Possible glycol ethers.		76-13-1 Freon 11			



## SECTION 2 - PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point	NA	Specific Gravity (H <sub>2</sub> O = 1) Concentrate Only =	1.07
Vapor Pressure PSIG @ 70°F (Aerosols)	Max. 60	Vapor Pressure (Non-Aerosols) (mm Hg and Temperature)	NA
Vapor Density (Air = 1)	NE	Evaporation Rate (_____ = 1)	NE
Solubility in Water	Insoluble	Water Reactive	No
Appearance and Odor	Straw colored liquid, chlorinated solvent odor.		

## SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (AEROSOLS) <b>FLAMMABLE</b>	Auto-ignition Temperature <b>NE</b>	Flammability Limits in Air % by Volume	LEL <b>NE</b>	UEL <b>NE</b>
Flash Point and Method Used (Non-Aerosols) <b>NA</b>				
Extinguisher Media <b>Foam, dry chemical, carbon dioxide</b>				
Special Fire Fighting Procedures <b>Use water fog to cool containers to prevent rupturing and exploding containers. Provide shielding for personnel. Wear self contained breathing apparatus.</b>				
Unusual Fire and Explosion Hazards <b>Do not expose aerosols to temperatures above 130° F or the container may rupture.</b>				

\*Optional

\*\* Chemical Listed as Carcinogen or Potential Carcinogen

NTP  IARC Monograph  OSHA  Not Listed  Animal Data Only

*Wiley*

K52791

**SECTION 4 - REACTIVITY HAZARD DATA** 311-2

<b>STABILITY</b>	<b>Conditions To Avoid</b>	
<input checked="" type="checkbox"/> Stable	Open flame, welding arcs, heat, sparks	
<input type="checkbox"/> Unstable		
<b>Incompatibility (Materials to Avoid)</b> Strong oxidizing agents, reactive metals such as aluminum, magnesium and sodium.		
<b>Hazardous Decomposition Products</b> CO, CO <sub>2</sub> , HCl, small amounts of phosgene and chlorine.		
<b>HAZARDOUS POLYMERIZATION</b>		<b>Conditions To Avoid</b>
<input type="checkbox"/> May occur		None Known
<input checked="" type="checkbox"/> Will Not Occur		

**SECTION 5 - HEALTH HAZARD DATA**

<b>PRIMARY ROUTES OF ENTRY</b>	<input checked="" type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion	<input type="checkbox"/> Not Hazardous
	<input type="checkbox"/> Skin Absorption	<input type="checkbox"/> Eye	
<b>ACUTE EFFECTS</b>			
Inhalation	Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.		
Eye Contact	Irritation		
Skin Contact	Irritation		
Ingestion	Unlikely route of exposure. Possible chemical pneumonitis if aspirated into the lungs.		
<b>CHRONIC EFFECTS</b> (Effects due to excessive exposure to the raw materials of this mixture) May cause kidney & lung damage, cardiac & liver abnormalities.			
<b>Medical Conditions Generally Aggravated by Exposure</b> May aggravate existing eye, skin, or upper respiratory conditions.			
<b>EMERGENCY FIRST-AID PROCEDURES -</b>			
Eye Contact	Flush with water for 15 minutes. If irritated, see physician.		
Skin Contact	Wash with soap and water. If irritated, see physician.		
Inhalation	Remove to fresh air. Resuscitate if necessary. Get medical aid.		
Ingestion	DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.		

**SECTION 6 - CONTROL AND PROTECTIVE MEASURES**

<b>Respiratory Protection (Specify Type)</b> If vapor conc. exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.	
<b>Protective Gloves</b>	<b>Eye Protection</b>
Rubber gloves	Safety glasses recommended
<b>VENTILATION REQUIREMENTS</b>	Adequate ventilation to keep vapor concentration below TLV.
<b>Other Protective Clothing and Equipment</b> None	
<b>Hygienic Work Practices</b> Wash with soap and water before handling food. Remove contaminated clothing.	

**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES**

<b>Steps to be Taken if Material is Spilled Or Released</b>	Absorb with suitable medium. Incinerate or landfill according to local, state, or federal regulations. Allow solvents to evaporate. Clean up adhesive with sawdust.
<b>Waste Disposal Methods</b>	Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
<b>Precautions to be Taken in Handling and Storage</b>	Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
<b>Other Precautions and / or Special Hazards</b>	
Avoid food contamination. KEEP OUT OF REACH OF CHILDREN. Remove ignition sources.	
Avoid breathing vapors. Do not flush to sewer.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied.