

Material Safety Data Sheet

Revised: 08/30/90

601

Product Name: NYS - ITEM 6 PORCH & DECK ERIE GRAY
 Product Class: Paint

Manufacturer's Identification

Name: AMSTERDAM COLOR WORKS INC.
 Address: 1546 STILLWELL AVE.
 BRONX NY 10461 EMERGENCY TELEPHONE #
 Telephone #: (212)-828-8000 (212) 828-8000

H.M.I.S. Health: 1 Flammability: 3 Reaction: 0 Personal Protection: 0

Hazardous Ingredients

(Components may be listed below more than once. Duplicate listings indicate that the component was entered into the formula more than one time. % weight calculations of duplicate components must be added together for total % weight of the component in the product.)

Component Name	Cas #	% Wgt	OSHA PEC	ACGIH	OTHER
XYLOL	1330-20-7	2.64		100PPM	
MS (MINERAL SPIRITS)	64742-47-8	6.24	100ppm	500ppm	

Physical Data

Appearance and Color: GRAY LIQUID
 Boiling Range: 282F Evaporation Rate: Slower than Ether
 Weight Per Gallon: 9.93 Vapor Density: Heavier than Air
 Percent Volatile By Volume: 44.46 V.O.C. 2.92

Fire And Explosive Data

Flashpoint: 81 F Flammable Limits
 D.O.T. Category: Lel: 1 Uel: 6

Extinguishing media: Foam, Co2, Dry Chemical

Unusual fire fighting hazards: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flames. Closed containers may explode when exposed to extreme heat. Do not apply on hot surfaces.

Special Fire Fighting Procedures: Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build up and possible autoignition or explosion when exposed to extreme heat. Fire fighters should wear self contained breathing apparatus.


Health Hazard Data

Eye Contact: Short term liquid or vapor contact may result in slight eye irritation. Prolonged and repeated contact may be more irritating.

Skin Contact: Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis.

Inhalation: High concentrations or prolonged exposure to lower concentrations may be irritating to the mucus membranes.

Ingestion: Liquid ingestion may result in vomiting. Aspiration (breathing in) of liquid to the lungs must be avoided as liquid contact with lungs may result in chemical pneumonitis and pulmonary edema/hemorrhage



Primary routes of entry: Ingestion, Inhalation:

Emergency and first aid procedures: If this product comes in contact with eyes, flush with large amounts of water for at least 15 minutes, and consult physician if irritation persists. In case of skin contact, wash with soap and large quantities of water, and remove saturated clothing. If breathing difficulties, dizziness or light headedness occur when working in areas with high vapor concentrations, victim should be removed to air that is free from vapors. If victim continues to experience breathing difficulties, oxygen should be administered until medical assistance can be rendered. If breathing stops, begin artificial respiration and seek immediate medical attention. If product is swallowed do not induce vomiting. Seek immediate medical attention.

Reactivity Data

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility (materials to avoid): N/A

Hazardous Decomposition: N/A

Spill Or Leak Procedures:

Steps to be taken if material is released or spilled: If spilled eliminate potential sources of ignition. Provide maximum ventilation. Wear appropriate respirator and other protective clothing. Contain with inert material and place in closed containers for disposal. Floors may be slippery, use care to avoid falls.

Waste disposal method: Waste material must be disposed of in accordance with federal, state, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

Special Protection Information

Ventilation: Provide adequate ventilation to meet TLV requirements. Engineering controls shall be sparkproof and explosion proof.

Respiratory protection: Non required if not sprayed and good ventilation is maintained. Note - Spray from product must not be inhaled. Respirators should be provided if engineering controls are not adequate.

Protective gloves: The use of solvent resistant gloves is advised to prevent skin and contact and possible irritation.

Other protective clothing and equipment: It is suggested that a source of clean water be available in work areas for flushing eyes and skin. Impervious clothing should be worn as needed.

Special Precautions

Precautions to be taken in handling and storage: Keep containers tightly closed. Store containers in cool dry place with adequate ventilation and away from sources of ignition.

Other Precautions: Empty containers contain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, grill, grind or expose such containers to heat, sparks, or other sources of ignition. They may explode and cause injury or death.

