## Ashland Chemical Company

DIVISION OF ASHLAND OIL, ÎNC.

## MATERIAL SAFETY **DATA SHEET**

9. O. BOX 2219, COLUMBUS, OHIO 43216 • (614) 889-3333

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

PAGE: 1

003141

SOD BICARBONATE USP PW #1 100# THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD) PRODUCT NAME: SOD BICARBONATE USP PW #1 180# CAS NUMBER: 144 55 8

CITY OF SYRACUSE, SCHOOL DIST A/P 409 W. GENESEE STREET SYRACUSE, NY 13202

05 50 075 6538930DATA SHEET NO: 0004070-002
LATEST REVISION DATE: 05/85-85136
PRODUCT: 3921000
INVOICE: 695259
INVOICE DATE: 11/11/85
TO: NOTTINGHAM H.S.
3100 E. GENESEE STREET
SYRACUSE, NY 13202

ATTN: PLANT MGR. /SAFETY DIR.

SECTION I-PRODUCT IDENTIFICATION

GENERAL OR GENERIC ID: ALKALI

HAZARD CLASSIFICATION: (99) NOT APPLICABLE

SECTION II-HAZARDOUS COMPONENTS

INGREDIENT CIM AE) PEL

SODIUM BICARBONATE

10

MG/M3

( 1)

>95 15 ( 1): PEL AND TLV ARE FOR TOTAL NUISANCE PARTICULATES.

SECTION III-PHYSICAL DATA

REFINEMENT MEASUREMENT

INITIAL BOILING POINT NOT APPLICABLE

VAPOR PRESSURE NOT APPLICABLE

VAPOR DENSITY

SPECIFIC GRAVITY

2.200 68.00 DEG F 20.00 DEG C)

NOT APPLICABLE PERCENT VOLATILES

EVAPORATION RATE

SECTION IV-FIRE AND EXPLOSION DATA

NOT APPLICABLE

NOT APPLICABLE

EXPLOSIVE LIMIT

NOT APPLICABLE

EXTINGUISHING MEDIA:

UNUSUAL FIRE & EXPLOSION HAZARDS: NOT APPLICABLE

SECTION V-HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL

THRESHOLD LIMIT VALUE

10

MG/M3 MG/M3

EFFECTS OF OVEREXPOSURE: FOR PRODUCT

EYES - CAN CAUSE IRRITATION. SKIN - MAY CAUSE IRRITATION. BREATHING - OF DUST CAN CAUSE IRRITATION OF NASAL AND RESPIRATORY PASSAGES. SWALLOWING - MAY CAUSE GASTROINTESTINAL IRRITATION.

FIRST AID:

- IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.
- IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.
- ALLOWED: IMMEDIATELY DRINK TWO GLASSES OF WATER AND INDUCE VOMITING BY EITHER GIVING IPECAC SYRUP OR BY PLACING FINGER AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION IMMEDIATELY.

IF BREATHED: REMOVE INDIVIDUAL TO FRESH AIR.

SECTION VI-REACTIVITY DATA

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

## **Ashland Chemical Company** DIVISION OF ASHLAND OIL, INC.



MATERIAL SAFETY DATA SHEET

₱. O. BOX 2219, COLUMBUS, OHIO 43216 • (614) 889-3333 24-HOUR EMERGENCY TELEPHONE (606) 324-1133

	SOD BICARBONATE USP PW #1 100#	
	SECTION VI-REACTIVITY DATA (CONTINU	
STABILITY: STABLE		
INCOMPATIBILITY: AVOID	CONTACT WITH:, STRONG MINERAL ACIDS.	
	SECTION VII-SPILL OR LEAK PROCEDURE	
	SE MATERIAL IS RELEASED OR SPILLED:	
SMALL SPILL: SWEEP UP	MATERIAL ONTO PAPER.	
LARGE SPILL: SHOVEL MA TO CLEAN UP ANY R	ERIAL INTO CONTAINERS. THOROUGHLY S ESIDUAL MATERIAL.	SWEEP AREA OF SPILL
WASTE DISPOSAL METHOD:		
SMALL SPILL: DISPOSE OF REGULATIONS.	IN ACCORDANCE WITH ALL LOCAL, STATE	AND FEDERAL
LARGE SPILL: DISPOSE OF REGULATIONS.	IN ACCORDANCE WITH ALL LOCAL, STATE	: AND FEDERAL
SE(	TION VIII-PROTECTIVE EQUIPMENT TO BE	USED
	IF NEEDED USE A NIOSH/MSHA JOINTLY UR SAFETY EQUIPMENT SUPPLIER)	APPROVED DUST
VENTILATION TO MAD	FFICIENT MECHANICAL (GENERAL AND/OR NTAIN EXPOSURE BELOW LEVEL OF OVEREX ENT ADVERSE EFFECTS).	LOCAL EXHAUST) Posure (from known,
EYE PROTECTION: WEAR SA (CONSULT YOUR SAFE	FETY GLASSES IN COMPLIANCE WITH OSHA TY EQUIPMENT SUPPLIER)	REGULATIONS.
THER PROTECTIVE EQUIPM	ENT: NORMAL WORK CLOTHING COVERING A	RMS AND LEGS.
SECTI	ON IX-SPECIAL PRECAUTIONS OR OTHER C	OMMENTS
CONTAINERS RETAIN	RIAL MAY BE HAZARDOUS WHEN EMPTIED.S PRODUCT RESIDUES (VAPOR, LIQUID, AND GIVEN IN THE DATA SHEET MUST BE OBS	/OR SOLID), ALL
WARRANTED TO BE WI ADVISED TO CONFIRM	ATED HEREIN IS BELIEVED TO BE ACCURA ETHER ORIGINATING WITH ASHLAND OR NO IN ADVANCE OF NEED THAT THE INFORMA ITABLE TO THEIR CIRCUMSTANCES.	T. RECIPIENTS ARE