


Klockit

K53323

671 Plumbing & Heating

B. D.
Classic Enterprizes
P.O. Box 2445
Santa Fe Springs, CA. 90670
(213) 944-6177



MATERIAL SAFETY DATA SHEET

Section I

DATE OF PREP: 02/01/88

PRODUCT NAME: ARISTOCRAT POLYMER COATING
PRODUCT CLASS: EPOXY RESIN HARDENER
PRODUCT TYPE: MODIFIED ALIPHATIC POLYAMINE
D.O.T. CATEGORY: CORROSIVE LIQUID N.O.S.
UN 1760, CHEMICALNOIBN

ADDRESS: B.D. CLASSIC ENTERPRISES
12937 Sunshine Ave.
Santa Fe Springs, CA 90670
TELEPHONE: 213-944-6177
EMEERGENCY INFORMATION: 714-963-1398
213-862-1380

Section II - HAZARDOUS INGREDIENTS

A Diethylpiperazine (AEP)
C.A.S. No. 140-31-8

Nonyl Phenol
C.A.S. No. 25154-52-3

THE PERCENTAGES OF EACH OF THESE INGREDIENTS IS PROPRIETARY INFORMATION. SIGNIFICANT AMOUNTS OF EACH, HOWEVER, ARE PRESENT IN THIS MATERIAL.

Section III - PHYSICAL DATA

PHYSICAL STATE: Moderate Viscosity, pale yellow liquid
SPECIFIC GRAVITY: 0.97 at 77°F
DENSITY: 8.1 lbs/gal at 77°F

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 200°F (Bensky Martens Closed Cup)
EXTINGUISHING MEDIA: Foam, Dry Chemical, Carbon Dioxide (CO₂)

NOTE: Toxic fumes will be evolved when this material is involved in a fire. Self-contained breathing apparatus should be available for fire fighters. Cool fire-exposed containers with water.

Section V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE: Will cause burns to skin and eyes. High concentration of vapors can cause severe irritation of eyes and respiratory tract. Liquid causes severe damage to mucous membranes if swallowed.

CHRONIC: Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

Section V - HEALTH HAZARD DATA cont.

EMERGENCY AND FIRST AID PROCEDURES:

- EYES:** Immediately flush with large amounts of water for at least 15 minutes lifting upper and lower lids occasionally. GET IMMEDIATE MEDICAL ATTENTION. If a physician is not immediately available, continue flushing with water.
- SKIN:** Immediately flush skin with water for at least 15 minutes while removing contaminated clothing and shoes. Launder clothing before re-use and discard contaminated leather articles. Get Medical attention if swelling or reddening occurs.
- INHALATION:** Remove to fresh air if effects occur and administer oxygen if necessary. GET MEDICAL ATTENTION if effects persist.
- INGESTION:** DO NOT INDUCE VOMITING. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if victim is conscious. GET MEDICAL ATTENTION IMMEDIATELY.

Section VI - REACTIVITY DATA

- STABILITY:** Stable under normal storage conditions.
- INCOMPATIBILITY:** Avoid contact with strong oxidizing agents, mineral acids (e.g. H_2SO_4 , HCl), and epoxy resins under uncontrolled conditions.
- HAZARDOUS DECOMPOSITION PRODUCTS:** CO (Carbon Monoxide)
 CO_2 (Carbon Dioxide)
 NO_x (Oxides of Nitrogen)

Section VII - SPILL OR LEAK PROCEDURES

- IF MATERIAL IS SPILLED:** Avoid contact with material. Persons not wearing appropriate protective equipment (see below) should be excluded from the area of spill until clean-up is complete. Stop at source, dyke area to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on clay, diatomaceous earth or other absorbent and shoveled into disposal containers.
- WASTE DISPOSAL METHOD:** Dispose of as hazardous waste in accordance with Federal, State, and Local regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

- RESPIRATORY PROTECTION:** NIOSH approved respiratory protection required in the absence of proper environmental control. For emergencies, a self contained breathing apparatus, or a full face respirator is recommended.
- VENTILATION:** Breathing of vapors must be avoided. Ventilation must be sufficient to control vapors. This material should be confined as far as possible within sealed or covered equipment in which case normal ventilation should be adequate. Special (local) ventilation will be needed in areas where vapors are expected to be vented.
- HAND PROTECTION:** Impervious gloves, neoprene or rubber.
- EYE PROTECTION:** Splash proof goggles or safety spectacles with side shields.
- OTHER PROTECTIVE EQUIPMENT:** Clean, body covering clothing. Further safety equipment (apron, footwear, etc.) should be used as necessary to prevent contact with material.

Section IX - SPECIAL PRECAUTIONS

1. Prevent all skin and eye contact.
2. Avoid breathing vapors.
3. Re-seal part used containers.
4. Ensure that all containers are properly labelled to prevent accidental ingestion.
5. Wash with soap and water before eating, drinking, smoking or using toilet facilities.
6. Observe conditions of good industrial hygiene and safe working practice.