

MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

000922

DATE OF PREP 11/4/81

Section I

MANUFACTURER'S NAME W. M. Barr & Company

STREET ADDRESS 2105 Channel Avenue
P. O. Box 1879

CITY, STATE, AND ZIP CODE Memphis, Tennessee 38101

EMERGENCY TELEPHONE NO.

INFORMATION TELEPHONE NO. 901-775-0100

PRODUCT CLASS

MANUFACTURERS CODE IDENTIFICATION 231

TRADE NAME Markerboard Surface Cleaner

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT Wt.	TLV		LEL	VAPOR PRESSURE MM
		PPM	mg/M ³		
Butyl Cellosolve	3	50	240		0.6

Section III - PHYSICAL DATA

BOILING RANGE 212-340°F

VAPOR DENSITY HEAVIER, LIGHTER THAN AIR

EVAPORATION RATE FASTER SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME 98.8

WEIGHT PER GALLON 8.50 lbs./gal.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION N.A.

FLASH POINT None

LEL N.A.

EXTINGUISHING MEDIA N.A.

USUAL FIRE AND EXPLOSION HAZARDS N.A.

SPECIAL FIRE FIGHTING PROCEDURES N.A.



Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE See Section II

EFFECTS OF OVEREXPOSURE None recognized.

ACUTE

CHRONIC

EMERGENCY AND FIRST AID PROCEDURES If swallowed: Do not induce vomiting. Call your Poison Control Center, hospital emergency room or physician immediately. Eye contact: Flush with water for at least 15 minutes. If irritation persists get medical attention.

Section VI — REACTIVITY DATA

STABILITY UNSTABLE STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Small spills can be absorbed by appropriate inert absorbent.

WASTE DISPOSAL METHOD Dispose in accordance with applicable local, state and federal regulations.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION N.A.

VENTILATION N.A.

PROTECTIVE GLOVES N.A.

EYE PROTECTION N.A.

OTHER PROTECTIVE EQUIPMENT N.A.

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DOL STORAGE CATEGORY

OTHER PRECAUTIONS Avoid prolonged skin contact with concentrated solution. Do not take internally. Keep out of reach of children.

MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

56-2478
80

DATE OF PREP May 1, 1981

Section I

MANUFACTURER'S NAME BARRETT VARNISH CO.

STREET ADDRESS 1532 SOUTH 50th COURT

CITY, STATE, AND ZIP CODE CICERO, ILLINOIS 60650

EMERGENCY TELEPHONE NO (312) 242-2462

000973

PRODUCT CLASS Alkyd Varnish

MANUFACTURERS CODE IDENTIFICATION 8J-357

TRADE NAME Master Painter Gloss

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/m ³		
MINERAL SPIRITS (RULE 66)	100	200		0.9%	2.4 mm Hg @ 68° F.

Section III - PHYSICAL DATA

BOILING RANGE 313-374° F.

VAPOR DENSITY HEAVIER LIGHTER THAN AIR

EVAPORATION RATE FASTER SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME 100

WEIGHT PER GALLON 6.44

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY COMBUSTIBLE

FLASH POINT 105° F.

LEL 0.9%

EXTINGUISHING MEDIA DRY CHEMICAL, CO₂, FOAM, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS NONE

SPECIAL FIRE FIGHTING PROCEDURES NONE