

### BENWOOD PASTE WOOD FILLER

BENWOOD Paste Wood Filler is used to fill the voids in open-grained woods such as oak or walnut, to assure a smooth finishing surface. Paste Wood Filler can

### A Paint Product for Interior Use

be used as is, or colored after thinning, by the addition of BENWOOD Interior Stains or MOORE'S Universal Tinting Colors.

#### DIRECTIONS FOR USE

For a smooth varnished—or painted—finish, open-grained woods such as oak, mahogany and walnut require filling. Wood to be finished should be well-sanded, clean and dry; previous coatings must be completely removed.

**For Clear or Painted Finishes:** Thin Natural Paste Wood Filler with mineral spirits to the consistency of heavy cream—you will need almost as much thinner as Filler. Brush mixture freely across the grain, then with the grain. Allow to set 5 to 10 minutes or until Filler loses its gloss. Then wipe off across the grain with burlap or other coarse cloth, rubbing Filler into pores of wood and removing excess Filler. Work on a small area at a time so the Filler can be wiped before it is too dry. After an overnight dry, sand lightly with fine grit paper. Dust carefully. To remove every particle of dust, wipe with a cloth dampened with paint thinner.

pened with paint thinner.

**For Stained Finishes:** Filling is done before or after staining according to directions on Stain label. If desired, Natural Paste Wood Filler can be tinted with BENWOOD Stain or MOORE'S Universal Tinting Colors to approximate color of stained wood. Apply Filler as directed for Clear Finishes.

**Finishing:** After staining and/or filling wood, apply any of the BENWOOD or IMPERVO clear finishes as directed on the label. If filled wood is to be painted, see paint or enamel label for directions on priming and finishing new wood. As received in container, one gallon Paste Wood Filler spreads 300-350 sq. ft. (27.9-32.5 sq. meters).

MOORE'S, BENWOOD and IMPERVO are registered trademarks of Benjamin Moore & Co.

BENJAMIN MOORE & CO., MONTVALE, NJ 07645 - NEW YORK OFFICE, 511 CANAL STREET - MANUFACTURING LOCATIONS IN NEWARK • BOSTON • RICHMOND JACKSONVILLE • CLEVELAND • CHICAGO • ST. LOUIS • HOUSTON • BIRMINGHAM • DENVER • LOS ANGELES • SANTA CLARA • TORONTO • MONTREAL • VANCOUVER

#### CAUTION! COMBUSTIBLE

**CONTAINS PETROLEUM SOLVENTS:** Keep away from heat and open flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Close container after each use. Avoid prolonged contact with skin. Do not take internally.

**Use only with adequate ventilation.**

**KEEP OUT OF THE REACH OF CHILDREN. (11Y)**

**NOTICE:** Reports have associated permanent brain and nervous system damage with repeated prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.



Greensboro Construction Co.  
601 Crescent St.  
Greensboro, NC 27404

FEB 2 3 1990

**BENWOOD**



INTERIOR

**Paste  
Wood Filler**



**NATURAL 238 05**

32 FL. OZ. (1 QUART) 946 ml

**CAUTION!  
COMBUSTIBLE**

See other cautions on back panel.

**Benjamin Moore & Co.**

FEB 2 3 1990

Greensboro Construction Co.  
601 Crescent St.  
Greensboro, NC 27404