

MATERIAL SAFETY DATA SHEET NPCA 1-84  
FOR COATINGS, RESINS, AND RELATED MATERIALS  
REPLACES NPCA 1-82

MANUFACTURER'S NAME

Benjamin Moore & Co.  
51 Chestnut Ridge Rd., Montvale, N.J. 07645

EMERGENCY TELEPHONE NO.

201-344-1200

DATE OF PREPARATION

March 1986

INFORMATION TELEPHONE NO.

201-344-1200

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER 238 05

PRODUCT NAME Benwood Interior Paste Wood Filler,  
Natural

PRODUCT CLASS Wood Filler

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT

NAME

CAS#

PERCENT

OCCUPATIONAL  
EXPOSURE LIMITS  
TLV PEL

VAPOR  
PRESSURE

Mineral Spirits

64742-88-7

11

100 ppm

500 ppm

< 5.0 mm Hg  
@ 100°F

SECTION III - PHYSICAL DATA

BOILING RANGE 310°F - 405°F

VAPOR DENSITY

HEAVIER

LIGHTER THAN AIR

EVAPORATION RATE FASTER

SLOWER THAN ETHER

& VOLATILE VOLUME 21

WT/GAL 2.7 lbs.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION

OSHA

FLASH POINT

LEL

Combustible liquid

DOT

X

120°F

1.0%

EXTINGUISHING MEDIA:

FOAM

"ALCOHOL"

CO2

DRY CHEMICAL

WATER FOG

OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS

NONE

SPECIAL FIREFIGHTING PROCEDURES - Do not use water stream on burning liquid.  
Cool exposed containers with water.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - Inhalation - Respiratory irritation and central nervous  
system effect - Anesthetic.

Skin and Eye Contact - Primary irritation.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Unknown

PRIMARY ROUTE(S) OF ENTRY:

DERMAL

INHALATION

INGESTION

EMERGENCY AND FIRST AID PROCEDURES - Inhalation - Remove from hazard area, maintain  
breathing, call physician. Skin Contact -  
wash with mild soap and water.

---

SECTION VI - REACTIVITY DATA

---

STABILITY    UNSTABLE    STABLE

HAZARDOUS POLYMERIZATION    MAY OCCUR    WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS

Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID

Not Applicable

INCOMPATIBILITY (MATERIALS TO AVOID)

Not Applicable

---

SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Avoid breathing vapors. Use non-sparking tools to return materials to container. Absorb residue with Fuller's earth.

WASTE DISPOSAL METHOD

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

---

SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

**RESPIRATORY PROTECTION** Use NIOSH approved respirator specified for protection against mist spray mist and organic vapors in restricted or confined areas.

**VENTILATION** Adequate to maintain working atmosphere below T.L.V. and L.E.L. (See Section II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

**PROTECTIVE GLOVES** Discharge exhaust only in area away from ignition sources.

Required during repeated contact.

**EYE PROTECTION**

Safety glasses to protect against splashes.

**OTHER PROTECTIVE EQUIPMENT**

Clothing adequate to protect skin.

**HYGIENIC PRACTICES:** Not Applicable

---

SECTION IX - SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Combustible - Keep away from heat and flame.

OTHER PRECAUTIONS

Use only with adequate ventilation.

Avoid prolonged contact with skin and breathing of vapor or spray mist.

Close container after each use.

Keep out of the reach of children.

Do not take internally.

**NOTICE:** Reports have associated permanent brain and nervous system damage with repeated prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.