

**MATERIAL SAFETY DATA SHEET NPCA 1-84  
FOR COATINGS, RESINS, AND RELATED MATERIALS  
REPLACES NPCA 1-82**

MANUFACTURER'S NAME

Benjamin Moore & Co.  
51 Chestnut Ridge Rd.  
Montvale, N.J. 07645

EMERGENCY TELEPHONE NO.

201-344-1200

DATE OF PREPARATION

March 1986

INFORMATION TELEPHONE NO.

201-344-1200

**SECTION I - PRODUCT IDENTIFICATION**

PRODUCT NUMBER 413

PRODUCT NAME Moore's Interior Wood Finishes Quick  
Dry Sanding Sealer

PRODUCT CLASS solvent thinned sealer

**SECTION II - HAZARDOUS INGREDIENTS**

INGREDIENT		PERCENT	OCCUPATIONAL EXPOSURE LIMITS	VAPOR PRESSURE
Name	CAS#		TLV PEL	@ 100°F
VM&P Naphtha	64742-89-8	60	300*	26 mm Hg @ 100°F

\*Recommended by supplier

**SECTION III - PHYSICAL DATA**

BOILING RANGE 256 - 297°F      VAPOR DENSITY HEAVIER THAN AIR  
EVAPORATION RATE: FASTER      SLOWER THAN ETHER      % VOLATILE VOLUME 67%  
WT/GAL 7.0

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLAMMABILITY CLASSIFICATION      OSHA \_\_\_\_\_      FLASH POINT      LEL  
Flammable Liquid      DOT X      56°F      1.0%

EXTINGUISHING MEDIA:  
FOAM      "ALCOHOL"      CO2      DRY CHEMICAL      WATER FOG      OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS  
NONE

SPECIAL FIREFIGHTING PROCEDURES

Do not use water stream on burning liquid. Cool exposed containers with water.

**SECTION V - HEALTH HAZARD DATA**

EFFECTS OF OVEREXPOSURE - Respiratory irritation and central nervous system effect-  
Anesthetic.

Skin and Eye Contact - Primary irritation.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Unknown

PRIMARY ROUTE(S) OF ENTRY:      DERMAL      INHALATION      INGESTION

EMERGENCY AND FIRST AID PROCEDURES - Inhalation - Remove from hazard area,  
maintain breathing, call physician. Eye Contact - Flush thoroughly with water. Call  
physician. Skin Contact - Wash with mild soap and water

---

SECTION VI - REACTIVITY DATA

---

STABILITY    UNSTABLE    STABLE

HAZARDOUS POLYMERIZATION    MAY OCCUR    WILL NOT OCCUR  
HAZARDOUS DECOMPOSITION PRODUCTS  
May produce CO2 and CO.  
CONDITIONS TO AVOID - Not Applicable

INCOMPATIBILITY (MATERIALS TO AVOID) - Not Applicable

---

SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Avoid breathing vapors. Use non-sparking tools to return materials to container, absorb residue with Fuller's earth.

WASTE DISPOSAL METHOD

Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

---

SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

RESPIRATORY PROTECTION Use NIOSH approved respirator specified for protection against paint spray mist and organic vapors in restricted or confined areas.

VENTILATION Adequate to maintain working atmosphere below lowest T.L.V. and L.E.L. (See Section II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES Discharge exhaust only in area away from ignition sources.

Required during repeated contact.

EYE PROTECTION

Safety glasses to protect against splashes.

OTHER PROTECTIVE EQUIPMENT

Clothing adequate to protect skin.

HYGIENIC PRACTICES: Not Applicable

---

SECTION IX - SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

**FLAMMABLE** - Keep away from heat, sparks and flame.

OTHER PRECAUTIONS

Use only with adequate ventilation.

Avoid prolonged contact with skin and breathing of vapor or spray mist.

Close container after each use.

Keep out of the reach of children.

Do not take internally.

**NOTICE:** Reports have associated permanent brain and nervous system damage with repeated prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.