



# MATERIAL SAFETY DATA SHEET

Consumer Products Division, Division of Borden, Inc.  
180 EAST BROAD STREET, COLUMBUS, OHIO 43215

Emergency Telephone  
(614) 431-6600  
(OPERATION ALERT)

THE OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200 REQUIRES THAT THE INFORMATION CONTAINED ON THIS SHEET BE MADE AVAILABLE TO YOUR WORKERS.

INSTRUCT YOUR WORKERS TO HANDLE THIS PRODUCT PROPERLY

NAME: "RAIN DANCE" PASTE CAR WAX 0245N  
TYPE: PASTE  
APPLICATION: CAR WAX

22-Aug-85

### SIGNAL WORD—WARNING!

THIS MATERIAL IS A "HEALTH HAZARD" AND/OR A "PHYSICAL HAZARD" AS DETERMINED WHEN REVIEWED ACCORDING TO THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION 29 CFR PART 1910.1200 "HAZARD COMMUNICATION" STANDARD.

### CHEMICAL HAZARD RATING

HEALTH=1(SLIGHT)

FIRE=3(HIGH)

REACTIVITY=0(LEAST)

### PHYSICAL DATA

GENERAL APPEARANCE: BLUE PASTE

ODOR: SOLVENT PH: 8.0-9.1 FLASH POINT, TCC: 84 F

### ACUTE HEALTH HAZARD DATA FOR RAIN DANCE PASTE CAR WAX

SKIN ABSORPTION: NOT TOXIC DERMALLY WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2).

INGESTION: NOT TOXIC ORALLY WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2).

INHALATION: NOT TOXIC BY INHALATION WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.3 (c) (1) AND (2), BUT OVER-EXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.

SKIN: SLIGHTLY TO MODERATELY IRRITATING (PRIMARY SKIN IRRITATION INDEX LESS THAN 5.0/8.0) WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.41.

EYES: SLIGHTLY TO MODERATELY IRRITATING WHEN TESTED AS DESCRIBED IN 16 CFR PART 1500.42.

### HANDLING PRECAUTIONS

INHALATION: AVOID PROLONGED OR REPEATED BREATHING OF VAPOR.

SKIN: AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. EYES: AVOID PROLONGED OR REPEATED CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING.

### EMERGENCY AND FIRST AID PROCEDURES

INTERNAL: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR.

SKIN CONTACT: IN CASE OF IRRITATION, FLUSH WITH WATER. EYE CONTACT: FLUSH THOROUGHLY WITH WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN.

### 29CFR1910.1200 HAZARDOUS INGREDIENTS/REPORTED HEALTH EFFECTS CAS REGISTRY NO. MATERIAL DESCRIPTION

8008-20-6 KEROSENE (0-10%)  
NIOSH DOCUMENT NUMBER: 77-192

8030-30-6 NAPHTHA (0-2%)  
ACGIH EXPOSURE LIMIT: 300 PPM, 8-HR TWA

64742-88-7 MEDIUM ALIPHATIC SOLVENT NAPHTHA (PETROLEUM) [0-10%]

64742-85-8 LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM) [30-50%]

64742-95-6 LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM) [0-5%]

THE ABOVE INGREDIENTS CAN CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. SIGNS AND SYMPTOMS MAY INCLUDE HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.

ALSO, OVEREXPOSURE TO MEDIUM ALIPHATIC SOLVENT NAPHTHA (CAS NO. 64742-88-7) OR LIGHT AROMATIC SOLVENT NAPHTHA (64742-95-6) MAY CAUSE LUNG AND/OR LIVER AND/OR KIDNEY DAMAGE BASED ON TESTS WITH LABORATORY ANIMALS.

7631-86-9 SILICON DIOXIDE (0-5%)  
OVEREXPOSURE MAY CAUSE PNEUMOCONIOSIS.  
ACGIH EXPOSURE LIMIT: SEE ACGIH TLVS, DUSTS  
OSHA 29CFR1910 EXPOSURE LIMIT: SEE 29 CFR 1910.1000 TABLE Z-3  
NIOSH DOCUMENT NUMBER: 75-120

### STORAGE PRECAUTIONS

KEEP CONTAINERS CLOSED. STORE IN A COOL, DRY PLACE.

### FIRE AND EXPOSION HAZARD DATA—FLAMMABLE.

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS, FLAME AND OTHER IGNITION SOURCES INCLUDING PILOT LIGHTS, HEATERS, CIGARETTES. ELECTRIC MOTORS AND STATIC DISCHARGE. VAPOR IS HEAVIER THAN AIR AND MAY SETTLE IN LOW PLACES OR TRAVEL A LONG DISTANCE TO A SOURCE OF IGNITION AND FLASHBACK.

IN CASE OF FIRE, USE DRY CHEMICAL, FOAM OR CO<sub>2</sub>. WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL.

### REACTIVITY DATA

NORMALLY STABLE AS DEFINED IN NFPA 704.12 (4-3.1)

### SPECIAL PROTECTION INFORMATION

APPROVED RESPIRATORY PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.

WEARING SAFETY GLASSES, SAFETY SHOES, HARD HATS AND SUITABLE CLOTHING IS STANDARD PRACTICE IN MANY INDUSTRIAL OPERATIONS.

### SPILL OR LEAK PROCEDURES

ELIMINATE ALL IGNITION SOURCES.  
SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA.  
PREVENT ENTRY INTO NATURAL BODIES OF WATER.

### WASTE DISPOSAL METHOD

RECOVER FREE LIQUID. ABSORB RESIDUE AND DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS.  
EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEARBY.  
SEE REVERSE SIDE

### DOT CLASSIFICATION

ORM-D CONSUMER COMMODITY