


# MATERIAL HEALTH AND SAFETY BULLETIN



UCD No.: \_\_\_\_\_

Product Code No.: 040186

MANUFACTURER'S NAME  <b>CLC Lubricants Company</b>	
STREET ADDRESS  <b>100 S. Old Kirk Road</b>	
CITY, STATE, AND ZIP CODE  <b>Geneva, IL 60134</b>	Business Phone: (312)  <b>232-7900</b>
EMERGENCY TELEPHONE NO.  Health Emergencies Call: _____ Hours: _____	

PRODUCT: <b>CLC Cut M-0617</b> COMMON NAME: GENERIC NAME: CHEMICAL NAME: CHEMICAL FAMILY: <b>Petroleum Hydrocarbon Blend</b> DOT PROPER SHIPPING NAME:	WARNING STATEMENT:  <b>Eye and Skin Irritant          Harmful Vapors Possible          Harmful if Ingested in Large Amounts</b>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------

Section I -- INGREDIENTS			
	TLV*		TLV*
Petroleum Hydrocarbon Blend 5 mg/m <sup>3</sup> for oil mist in air. CAS # 64742-53-6 CAS # 64741-44-2		(OSHA Regulation 29 CFR 1910.1000) (less than 45%) (less than 60%)	
Sulfurized Lard Oil	N/D	(less than 2%)	

\*Threshold Limit Value    A. OSHA     B. ACGIH     C. See Section III     D. Other

## Section II -- EMERGENCY AND FIRST AID PROCEDURES

EMERGENCY: Have a physician call

Eye  
Contact

Flush with water for 15 min.  
If irritation occurs, consult a physician.

Skin  
Contact

Wash with soap and water.

Inhalation

Remove to fresh air.  
If breathing difficulties arise, consult a physician.

Ingestion

DO NOT induce vomiting.  
Consult a physician.

## Section III -- PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

Eye  
Effects

This product may be an eye irritant.

May cause eye irritation.

Skin  
Effects

Prolonged or repeated skin contact may cause irritation.

Systemic  
Effects

Various studies have shown a possible association with exposure to this product and the following:

**INHALATION:** Possible effects include headache, nasal and respiratory irritation, nausea, drowsiness, fatigue, peumonitis, pulmonary edema, central nervous system depression.

**INGESTION:** Possible effects include headache, drowsiness, nausea, fatigue, peumonitis, pulmonary edema, central nervous system depression. Aspiration hazard.

### Section IV -- SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type)	Normally not needed.		
Ventilation	Sufficient to satisfy TLV.		
Protective Gloves	Chemical resistant to avoid skin irritation.	Eye Protection	Safety goggles always recommended.
Other Protective Equipment	None Special		

### Section V -- REACTIVITY DATA

Stability	Unstable		Conditions to Avoid:  None
	Stable	XX	
Incompatibility (Materials to Avoid)	Strong oxidants, strong acids or bases, selected amines		
Hazardous Decomposition Products	Oxides of carbon		
Hazardous Polymerization	May Occur		Conditions to Avoid:  None
	Will Not Occur	XX	

### Section VI -- SPILL OR LEAK PROCEDURES

HIGHWAY OR RAILWAY SPILLS - CALL CHEMTREC 1-800-424-9300

Precautions In Case of Release or Spill	Prevent product from entering sewers or waterways by diking. Absorb small amounts on inert material.
Reportable Quantity	
Waste Disposal Method	Assure compliance with applicable federal, state and local regulations.

## Section VII -- STORAGE AND SPECIAL PRECAUTIONS

Handling and Storing Precautions	Keep containers closed when not in use. Store away from heat, sparks, flame and strong oxidants. Avoid eye and skin contact. Avoid breathing vapor or mist.
Other Precautions	None

## Section VIII -- FIRE AND EXPLOSION HAZARD DATA

DOT Flammability Classification	Flash Point Range: <input type="checkbox"/> Below 20° F. <input type="checkbox"/> 20° F - 100° F <input type="checkbox"/> 100° F - 200° F <input checked="" type="checkbox"/> Over 200° F <input type="checkbox"/> None to boiling
Extinguishing Media	Foam, dry chemical, CO <sub>2</sub>
Unusual Fire and Explosion Hazards	Avoid contact with strong oxidants
Fire Fighting Procedures	Use supplied-air respirator for confined areas.

## Section IX -- PHYSICAL DATA

Approximate Boiling Range, °F	Above 400	Vapor Density: <input checked="" type="checkbox"/> Heavier Than Air <input type="checkbox"/> Lighter
Evaporation Rate:	<input type="checkbox"/> Faster Than Ether <input checked="" type="checkbox"/> Slower	Percent Volatile: Greater than 50%
Specific Gravity:	<input checked="" type="checkbox"/> Lighter Than Water <input type="checkbox"/> Heavier	Solubility in Water: Negligible Weight per Gallon:
Appearance and Odor: Brownish liquid with petroleum distillate odor.		

## Section X -- DOCUMENTARY INFORMATION

Product Code No. 040186	Issue Date April 1, 1986	Prepared By K. Przybyla
Replaces: UCD No.	Product Code No.	Issued
Reviewed-By: Revised: 04-15-87		
Reviewed By:	Manager, Loss Prevention	
Reviewed By:	Director of Occupational Health & Toxicology	
Reviewed By:	Science and Technology Division	

The above information is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume the risk of his use thereof.