

RCVD OCT 30<sup>th</sup> 2000

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : C-150 WALL GROUT - ALL COLORS  
 UPC NUMBER : 62635, 62641, 62645, 62657, 62672, 63005, 63063,  
 63068, 63073, 65372, 65374, 65376, 65378, 65380,  
 65382, 65384, 65386, 65388, 65390, 65392, 65394,  
 65396, 65398, 65416, 65434, 65436, 65444, 65449,  
 65454, 65456, 65466, 65474, 65484, 65486, 65494,  
 65496, 65502, 65504, 65506, 65508, 65512, 65514,  
 65516, 65518, 65520, 65522

PRODUCT USE/CLASS : Wall Grout

MANUFACTURER: 24 HOUR EMERGENCY:  
 DAP INC. TRANSPORTATION: 1-800-535-5053 (352-323-3500)  
 2400 BOSTON STREET MEDICAL : 1-800-327-3874 (513-558-5111)  
 BALTIMORE, MD 21224

PREPARE DATE : 02/20/1996 GENERAL INFORMATION:  
 REVISION NO. : 7 DAP INC. : 1-888-DAP-TIPS (1-888-327-8477)  
 REVISION DATE: 12/30/1999

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
01	Calcium Carbonate	1317-65-3	55.0-60.0 %
02	Portland cement	65997-15-1	35.0-40.0 %

ITEM	EXPOSURE LIMITS				COMPANY TLV-TWA	SKIN
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING		
01	10 mg/m3	N.E.	15 mg/m3	N.E.	N.E.	NO
02	10 mg/m3dust	N.E.	10 mg/m3dust	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard.

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept. of Labor OSHA Final Rule Limits (CFR 29 1910.1000); limits may vary between states.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Injurious to eyes. Causes skin irritation. Exposure to dust may result in build-up of material in eyes, ears, nose, and mouth which may cause irritation.

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Wet cement can dry skin and cause alkali burns.

EFFECTS OF OVEREXPOSURE - INHALATION: Exposure to dust may cause irritation to nose, throat, and respiratory system.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Inhalation of dust may result in pulmonary and respiratory damages. Prolonged or repeated inhalation of dust may cause lung damage.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: Asthma and asthma-like conditions may worsen from prolonged and repeated exposure.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush with large quantities of water until irritation subsides. Contact a physician.

SKIN CONTACT: Wash with soap and water. If irritation of skin persists, contact a physician.

INHALATION: Remove to fresh air. Contact a physician immediately.

INGESTION: DO NOT INDUCE VOMITING. Contact a physician or Regional Poison Control Center immediately.

COMMENTS: None.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: >200 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.  
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: N.A.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will not burn.

SPECIAL FIREFIGHTING PROCEDURES: No Information.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Sweep up excess powder. Place remaining powder into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN. Keep containers away from excessive heating and freezing. Avoid skin and eye contact. Do not inhale dusts of this product.

STORAGE INFORMATION: Keep container closed when not in use. Store away from caustics and oxidizers.

OTHER PRECAUTIONS: None.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: If dry-sanding, provide sufficient mechanical ventilation to maintain exposure below PEL and TLV. While mixing, provide sufficient mechanical ventilation (local or general exhaust) to maintain exposure below PEL and TLV.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

EYE PROTECTION: Safety glasses with side shields recommended.

SKIN PROTECTION: Gloves recommended for repeated or prolonged contact with skin.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash and coveralls if body contact may occur.

HYGIENIC PRACTICES: Wash contaminated clothing before reuse. Follow all MSDS/label precautions even after container is emptied because they may retain product residues.

(Continued on Page 4)



SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE : N.A. VAPOR DENSITY : N.A.  
ODOR : Low Odor  
APPEARANCE : Colored Powder EVAPORATION RATE: N.A.  
SOLUBILITY IN H2O : Dispersible  
SPECIFIC GRAVITY : 2.8421  
VAPOR PRESSURE : N.A. pH @ 0.0 % :  
PHYSICAL STATE : Powder VISCOSITY :

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Strong oxidizers and caustics.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. CO<sub>x</sub>, NO<sub>x</sub>

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL: Dispose of according to Federal, State, and Local Standards. This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulations, 40 CFR Section 261. Do not reuse empty containers. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261): None.

(Continued on Page 5)



SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Not Regulated by D.O.T.  
DOT HAZARD CLASS: NONE  
DOT UN/NA NUMBER: NONE                      PACKING GROUP: NONE

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313:  
This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % RANGE
No SARA Section 313 components exist in this product.		

TOXIC SUBSTANCES CONTROL ACT:  
This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
No information is available.	

NEW JERSEY RIGHT-TO-KNOW:  
The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
Iron Oxide	1337-61-9
Iron Oxide	20344-49-4
Iron Oxide	1308-338-9
Carbon Black	1333-86-4
Iron Oxide	1309-37-1

PENNSYLVANIA RIGHT-TO-KNOW:  
The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
No non-hazardous ingredients are present at greater than 3%.	

CALIFORNIA PROPOSITION 65:  
WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer:

(Continued on Page 6)

