

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

03-941  
03-948  
000872

IDENTITY (As Used on Label and List)

Redmark Ink 8700 Markers

Note: Blank spaces are not permitted. If any test is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

Dixon Ticonderoga Company

Address (Number, Street, City, State, and ZIP Code)

Route 61

Deer Lake, PA 17961

Emergency Telephone Number

717-366-1011

Telephone Number for Information

same as above

Date Prepared

3/21/88 Update 3/30/89

Signature of Preparer (Optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits Recommended

% (Optional)

Xylene

CAS 1330-20-7

100 ppm

80%

Section III - Physical/Chemical Characteristics

Boiling Point

140C

Specific Gravity (H<sub>2</sub>O = 1)

.91

Vapor Pressure (mm Hg.)

9.5

Melting Point

NA

Vapor Density (AIR = 1)

4.5

Evaporation Rate (Butyl Acetate = 1)

.6

Solubility in Water

Negligible

Appearance and Odor

Uniform Liquid, Aromatic Odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

28C TCC

Flammable Limits

LEL

1.1

UCL No Info

available

Extinguishing Media

NFPA Class B Extinguisher

Special Fire Fighting Procedures

Water spray may be ineffective on fire but can cool containers

Unusual Fire and Explosion Hazards

Keep away from heat and open flames. Closed container may explode if exposed to extreme heat.

Reproduce locally

146

