

4074

K54905

# Material Safety Data Sheet

## U.S. Department of Labor

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

RECEIVED  
APR 14 2009  
Facilities Management  
HEALTH AND SAFETY

### IDENTITY (As Used on Label and List)

30K, 31K and 32K Dry Erase Ink  
Items 412series, 4124P, 4128P, 310 series, 314P, DW  
and DW87series DW866 series

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

### Section I

Manufacturer's Name: <b>Dri Mark Products Inc.</b>	Emergency Telephone Number 1-516-484-6200
Address (Number, Street, City, State, and ZIP Code) 15 Harbor Park Dr. Pt. Washington, New York 11050	Telephone Number for Information 1-516-484-6200 Date Prepared 09/26/07 Signature of Preparer (optional) Roberta S. Dobbs

### Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Ethyl Alcohol				30-70%
Isopropanol				10-30%
Pigments, Resins, and release agents				
Surfactants				20%
Nibs & Reservoirs				Synthetic Fibers
Housing				Non Reactive Plastic

**Section VI - Health Hazard Data**

Route(s) of Entry:	Inhalation?: N/A	Skin?: N/A	Ingestion?: N/A
Health Hazards ( <i>Acute and Chronic</i> ) none			
Carcinogenicity: No known effects	NTP?: N/A	IARC Monographs?: N/A	OSHA Regulated?: No
Signs and Symptoms of Exposure: Alcohol vapors may have narcotic effect.			
Medical Conditions Generally Aggravated by Exposure			
Emergency and First Aid Procedures Provide plenty of fresh air, drink plenty of water and induce vomiting, flush eyes with plenty of water. Call a physician.			

**Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled: As the product is soaked in a porous reservoir. There is no possibility of spillage.
Waste Disposal Method: Dispose of in accordance with local government requirements.
Precautions to Be taken in Handling and Storing: Store in a cool dry area. Keep container tightly closed
Other Precautions: Avoid inhaling and contact with skin, eyes.

**Section III - Physical/Chemical Characteristics**

Boiling Point	78-120°	Specific Gravity (H <sub>2</sub> O = 1)	0.90
Vapor Pressure (mm Hg.)	N/A	Melting Point	
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	>1.0
Solubility in Water: Soluble in water			

Appearance and Odor : Alcoholic solution of organic pigments and additives.

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used): 12°C	Flammable Limits: Non-Flammable	LEL 1.4	UEL 15
---------------------------------	---------------------------------	------------	-----------

Extinguishing Media: CO<sub>2</sub>, Water Spray, Foam, extinguishing powder

Special Fire Fighting Procedures: Standard fire fighting equipment, use large amounts of foam, autoignition temperature C: 20.5

Unusual Fire and Explosion Hazards  
None

(Reproduce locally)

OSHA 174, Sept. 1985

**Section V - Reactivity Data**

Stability	Unstable	Conditions to Avoid: Avoid inhaling, swallowing, exposure to skin and heating up.
	Stable: X	
Incompatibility (Materials to Avoid) None		
Hazardous Decomposition or Byproducts None		
Hazardous Polymerization	May Occur	Conditions to Avoid: None
	Will Not Occur: X	

**Section VIII - Control Measures**

**Respiratory Protection (*Specify Type*)**  
Avoid Inhalation, no additional protection required.

Ventilation	Local Exhaust: No	Special: None
	Mechanical ( <i>General</i> ): No	Other: None

Protective Gloves: No                      Eye Protection: Avoid contact with eyes

Other Protective Clothing or Equipment: None

Work/Hygienic Practices: Avoid contact with skin and eyes. Wash hands after use.