

VINYL ENAMELS, CHASSIS BLACK DUCO® BLACK, VINYL CLEARS

Section I

Manufacturer

E. I. du Pont de Nemours & Co. (Inc.)
Automotive Products Department
Wilmington, Delaware 19898
Telephone: Product information (800) 441-7515
Medical emergency (800) 441-3637
Transportation emergency (800) 424-9300
(CHEMTREC)

Product: Vinyl Enamels, Chassis Black, Duco® Black, 304S, 305S,
306S

D.O.T. Hazard Class: Flammable Liquid
Paint UN 1263

Hazardous Materials Identification Section:
H = 2, F = 3, R = 0.

Section II — Hazardous Ingredients (See Section X for ingredients by product code)

Ingredients	CAS No.	Vapor Pressure (20°C mm Hg.)	Exposure Limits*
1. Vinyl chloride/acetate polymer	9003-22-9	None	10 mg/m ³ -S
2. Butyl acetate	123-86-4	8	150ppm-A, O; 200ppm-A-(STEL)
3. Acetone	67-64-1	184	750ppm-A; 1000ppm-O; 1000ppm-A-(STEL)
4. Methyl ethyl ketone	78-93-3	71	200ppm-A, O; 300ppm-A-(STEL)
5. Methyl isobutyl ketone	108-10-1	15	50ppm-A; 150ppm-O; 75ppm-A-(STEL)
6. Toluene	108-88-3	36.7	100ppm-A; 200ppm-O; 150ppm-A-(STEL) 300ppm-O-C 500ppm-O Max 10 Min
7. Isopropyl alcohol	67-63-0	33	400ppm-A, O; 500ppm-A-(STEL)
8. Propylene glycol monomethyl ether acetate	108-65-6	3.8	Unknown
9. Xylene	1330-20-7	25	100ppm-A, O; 150ppm-A-(STEL)
10. VM&P naphtha	64742-89-8	15	100ppm-D; 300ppm-A; 500ppm-O
11. Dibasic Esters			
a) Dimethyl glutarate	1119-40-0 106-65-0 627-93-0	14 (at 100°C)	10 mg/m ³ -D
b) Dimethyl succinate			
c) Dimethyl adipate			
12. Amorphous silica	7631-86-9	None	10 mg/m ³ -A; 15 mg/m ³ -O; 6.0 mg/m ³ -D

13. Carbon black	1333-86-4	None	3.5 mg/m ³ -A, O
14. Titanium dioxide	13463-67-7	None	10.0 mg/m ³ -A; 15 mg/m ³ -O Unknown
15. Alkyd resin	67922-67-2	None	Unknown

*A=ACGIH TLV, O=OSHA, D=Du Pont internal limit,
S=Supplier Furnished Limit, STEL=Short Term Exposure Limit (15 mins.), C=Ceiling

Section III — Physical Data

Evaporation rate: Slower than ether	Gal. wt. (#/gal): 7.4-7.8
Solubility in water: Miscible	Volume % volatile: 83.4-83.8%
Vapor density: Heavier than air	Weight % volatile: 72.1-75.9%
Boiling range: 54°F-150°F	V.O.C. (#/gal): 5.3-5.9

Section IV — Fire & Explosion Data

Flash point (Closed cup): Below 20°F
Approx. flammable limits: 1.0-13.1%
Extinguishing media: Water spray, foam, carbon dioxide, dry chemical
Special fire fighting procedures: Full protective equipment, including self-contained breathing apparatus, is recommended. Water from fog nozzles may be used to cool closed containers to prevent pressure build up.
Unusual fire & explosion hazards: When heated above the flash point, emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

Section V — Health Hazard Data

General effects

Ingestion: Gastro-intestinal distress.
In the unlikely event of ingestion, call a physician immediately and have names of ingredients available.
Inhalation: May cause nose and throat irritation. Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high.
If affected by inhalation of vapor or spray mist, remove to fresh air. If breathing difficulty persists, or occurs later, consult a physician.
Skin or eye contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.
In case of eye contact, immediately flush with plenty of water for at least 15 minutes; call a physician.
In case of skin contact, wash with soap and water. If irritation occurs, contact a physician.

Specific effects

Butyl Acetate: extremely high concentrations have caused blood changes and weakness in laboratory animals. **Methyl Ethyl Ketone:** High concentrations have caused embryotoxic effects in laboratory animals. Methyl Ethyl Ketone (MEK) has been demonstrated to potentiate (i.e., shorten the time of onset) the peripheral neuropathy caused by either N-Hexane or Methyl N-Butyl Ketone. MEK by itself has not been demonstrated to

Section V — Health Hazard Data — Continued

cause peripheral neuropathy. Liquid splashes in the eye may result in chemical burns. *Methyl Isobutyl Ketone*: Recurrent overexposure may result in liver and kidney injury. *Toluene*: Recurrent overexposure may result in liver and kidney injury. High airborne levels have produced irregular heart beats in animals and occasional palpitations in humans. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. *Isopropyl Alcohol*: Ingestion studies on laboratory animals showed that very high oral doses caused increased liver and kidney weights. High oral doses have caused anemia in laboratory animals. *Propylene Glycol Monomethyl Ether Acetate*: May cause moderate eye burning. Recurrent overexposure may result in liver and kidney injury. *Xylene*: high concentrations have caused embryotoxic effects in laboratory animals. Recurrent overexposure may result in liver and kidney injury. Can be absorbed through the skin in harmful amounts. *VM&P Naphtha*: Laboratory studies with rats have shown that petroleum distillates cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown significant increases of kidney damage nor kidney or liver tumors. *Titanium Dioxide*: In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rats' lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace.

Section VI — Reactivity Data

Stability: Stable
Incompatibility (materials to avoid): none reasonably foreseeable
Hazardous decomposition products: CO, CO₂, smoke, oxides of heavy metals reported in Section II
Hazardous polymerization: will not occur

Section VII — Spill or Leak Procedures

Steps to be taken in case material is released or spilled: Ventilate area. Remove sources of ignition. Prevent skin contact and breathing of vapor. Confine and remove with inert absorbent.
Waste disposal method: Do not allow material to contaminate ground water systems. Incinerate absorbed material in accordance with federal, state, and local requirements. Do not incinerate in closed containers.

Section VIII — Special Protection Information

Respiratory: Do not breathe vapors or mists.
Wear a properly fitted vapor/particulate respirator approved by NIOSH/MSHA (TC-23C) for use with paints during application and until all vapors and spray mists are exhausted. In confined spaces or in situations where continuous spray operations are typical or if proper respirator fit is not possible, wear a positive pressure, supplied-air respirator (TC-19C). Do not permit anyone without protection in the painting area. In all cases, follow the respirator manufacturer's directions for respirator use.
Ventilation: Provide sufficient ventilation in volume and pattern to keep contaminants below applicable OSHA requirements.
Protective clothing: Neoprene gloves and coveralls are recommended.
Eye protection: Desirable in all industrial situations. Include splash guards or side shields.

Section IX — Special Precautions

Precautions to be taken in handling and storing: Observe label precautions. Keep away from heat, sparks and flame. Close container after each use. Ground containers when pouring. Wash thoroughly after handling and before eating or smoking. Do not store above 120°F.
Other precautions: Do not sand, flame cut, braze or weld dry coating without a NIOSH/MSHA approved respirator or appropriate ventilation.

Section X — Hazardous Ingredients by Product Code

Product Code	Ingredients (See Section II)
310S	1, 2, 3, 4, 6, 8, 9, 10, 12, 13, 15
330S	1, 2, 3, 4, 5, 6, 8, 9, 10, 13, 14, 15
2460S	2, 3, 5, 6, 7, 9, 10, 13, 15
304S, 305S, 306S	1, 2, 3, 4, 10, 11, 12, 15

Notice: The data in this material safety data sheet relate only to the specific material designated herein and do not relate to use in combination with any other material or in any process.

"The following notice is required by California Proposition 65.
'Warning: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.'"

Product Manager
Refinish Sales