

All Scribbles except Neon  
731

103-3400 thru 103-3755  
103-4400 thru 103-4490



MATERIAL SAFETY DATA SHEET

Identity Duncan Scribbles SC 100, SC 200, SC300-316, [redacted] MSDS # 703

SECTION I

Manufacturer's Name Duncan Enterprises	Emergency Telephone Number (209) 445-1222	
Address 5673 E. Shields Ave. Fresno, CA 93727	Telephone Number (209) 291-4444	
HMIS Codes	Date Prepared August 1987	
Health 0	Reactivity 0	Revised January 1992
Fire 1	Protective Equip. G (if spraying)	Prepared By Curt Sathre

SECTION II  
HAZARDOUS INGREDIENTS

Hazardous Components none	OSHA PEL	ACGIH TLV	CAS #
Other Information none			

RECEIVED  
2013 JUN 18 PM 12:59  
ACCOUNTS PAYABLE

SECTION III  
PHYSICAL DATA

Boiling Point, (DEG°F) 212°F	Vapor Pressure, (MM HG.) n/a
Melting Point, (DEG°F) n/a	Vapor Density (AIR=1) Less than 1 water
Specific Gravity (Water=1): 1.1	Water Solubility, % Insoluble
Appearance And Odor Opaque colored latex paint	Freezing Point n/a
pH 8.0 - 9.0	Evaporation Rate (Butyl Acetate=1) Less than 1 water

103-3400a, thru 103-3755a  
103-4400a, thru 103-4490a

MSDS 703

SECTION VII  
PRECAUTIONS FOR SAFE HANDLING

**Steps To Be Taken In Case Material Is Released Or Spilled**

Clean up properly with paper towels and a wet sponge.

**Waste Disposal Method**

Put paper towels in trash and rinse out sponge. Follow Federal, State and Local regulations for disposal.

**Precautions To Be Taken In Handling And Storing**

Keep container sealed.

**Other Precautions**

n/a

SECTION VIII  
CONTROL MEASURES

**Respiratory Protection (Specify Type)**

If spraying, do not inhale mist. Use respirator that is NIOSH approved for sprays and mists.

**Ventilation**

**Local Exhaust**

Recommended

**Mechanical (General)**

Recommended when spraying

**Protective Gloves**

no

**Other Protective Clothing Or Equipment**

None needed

**Work/Hygienic Practices**

Good hygiene practices should be followed.

**Special**

Use respirator when spraying

**Other**

none

**Eye Protection**

Safety glasses with side shields. Do not wear contact lenses.

SECTION IX  
ADDITIONAL INFORMATION

CALIFORNIA Proposition 65

n/a



"Products bearing the Nontoxic Product Seal are certified in a program to toxicological evaluation by a nationally recognized toxicologist to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200(c)."

DISCLAIMER -- Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied.

103-3400 B-THU 103315  
103-4400 B-THU 103-4490

MSDS 703

SECTION IV  
FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) n/a Flammable Limits LEL n/a UEL n/a  
Extinguishing Media Use appropriate techniques and media for surrounding fire.  
Special Fire Fighting Procedures None.  
Unusual Fire And Explosion Hazards Material can spatter above 212°F. Polymer film can burn.

SECTION V  
REACTIVITY DATA

Stability Unstable: Stable: X  
Conditions To Avoid n/a  
Incompatibility (Materials To Avoid) n/a  
Hazardous Decomposition or Byproducts n/a  
Hazardous Polymerisation May Occur: Will Not Occur: X  
Conditions To Avoid n/a

SECTION VI  
HEALTH HAZARD DATA

Routes Of Entry Inhalation? no Skin? no Ingestion? no  
Health Hazards (Acute and Chronic) None. Nontoxic  
Carcinogenicity NTP? no IARC Monographs? no OSHA Regulated? no  
Signs And Symptoms of Exposure n/a  
Medical Conditions Generally Aggravated by Exposure Abrasive, can scratch eyes.  
Emergency And First Aid Procedures Eye contact: Flush with water at least 15 minutes. Skin contact: Wash with soap and water.