

K/19619

970 8956

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

1425

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
SUPER DUTY MOUNTING CEMENT

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name DURAL COMPANY INC.	Emergency Telephone Number 414-466-7060
Address (Number, Street, City, State, and ZIP Code) 5724 W. FLORIST AVE	Telephone Number for Information 414-466-7060
MILWAUKEE, WI. 53218	Date Prepared JANUARY 3, 1998
	Signature of Preparer (optional) D.M. WAMSER

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
HEXANE CAS#110-54-3	500PPM	50 PPM	NA	90
NATURAL RUBBER CAS#69006-04-6	(NON-HAZARDOUS)			10

RECEIVED
MAR 6 2006

(1) NIOSH RECOMMENDS A LIMIT OF 100 PPM - 8 HOUR TIME WEIGHTED AVERAGE, 510 PPM CEILING. THESE LIMITS ARE FOR N-HEXANE. THE ACGIH TLV FOR OTHER ISOMERS OF HEXANE IS 500 PPM, TWA; 1000 PPM SHORT TERM EXPOSURE LIMIT (STEL)

SECTION III-PHYSICAL DATA

PROPERTY	REFINEMENT	MEASUREMENT
BOILING POINT	FOR PRODUCT	147.00 - 189.00 DEG F (58.00 - 70.55 DEG C)
VAPOR PRESSURE	FOR PRODUCT	125.00 MMHG (57.00 DEG F 20.00 DEG C)
SPECIFIC VAPOR DENSITY	AIR = 1	0.0
SPECIFIC GRAVITY		0.72 - 0.84 (60.00 DEG F 15.55 DEG C)
PERCENT VOLATILES		100.00%
EVAPORATION RATE	(N-BUTYL ACETATE = 1)	9.00

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT(100) -25.0 DEG F
(-31.7 DEG C)

EXPLOSIVE LIMIT (PRODUCT) LOWER = 1.0%

EXTINGUISHING MEDIA: REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS; CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

SPECIAL FIRE & EXPLOSION HAZARD: MATERIAL IS HIGHLY VOLATILE AND READILY GIVES OFF VAPORS WHICH MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING POINT.

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

ALL FIVE GALLON PAIL AND LARGER METAL CONTAINERS INCLUDING TANK CARS AND TANK TRUCKS SHOULD BE GROUNDED AND/OR BONDED WHEN MATERIAL IS TRANSFERRED.

NFPA CODES: HEALTH- 1 FLAMMABILITY- 3 REACTIVITY- 0

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



001037 HEXANE PAGE: 2

SECTION V-HEALTH HAZARD DATA (CONTINUED)

EFFECTS OF ACUTE OVEREXPOSURE, FOR PRODUCT

EYES - CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION,
SKIN - PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING,
DERMATITIS.
BREATHING - EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY
IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DIZZINESS, WEAKNESS,
FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONSCIOUSNESS, AND EVEN DEATH.
SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA,
ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN
BE FATAL.

FIRST AID:

IF ON SKIN; THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED
CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE.
IF IN EYES; FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS
OCCASIONALLY, GET MEDICAL ATTENTION.
IF SWALLOWED; DO NOT INDUCE VOMITING. KEEP PERSON WARM, QUIET, AND GET MEDICAL
ATTENTION. ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
IF BREATHED; IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS
DIFFICULT ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL
RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY:

INHALATION
SKIN CONTACT

EFFECTS OF CHRONIC OVEREXPOSURE, FOR PRODUCT

PROLONGED AND REPEATED EXPOSURE TO N-HEXANE MAY DAMAGE PERIPHERAL NERVE TISSUE
(THAT OF THE ARMS AND LEGS) AND RESULT IN MUSCULAR WEAKNESS AND LOSS OF
SENSATION IN THE EXTREMITIES (PERIPHERAL NEUROPATHY).
OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF
THE FOLLOWING EFFECTS IN HUMANS: CENTRAL NERVOUS SYSTEM EFFECTS

SECTION VI-REACTIVITY DATA

HAZARDOUS POLYMERIZATION; CANNOT OCCUR

STABILITY; STABLE

INCOMPATIBILITY; AVOID CONTACT WITH, STRONG OXIDIZING AGENTS.

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL; ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER
ABSORBENT MATERIAL AND TRANSFER TO HOOD.
LARGE SPILL; ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS,
ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE
EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT
SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK.
REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR
OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

WASTE DISPOSAL METHOD:

SMALL SPILL; ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR
VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATERIAL IN
ACCORDANCE WITH APPLICABLE REGULATIONS.
LARGE SPILL; DESTROY BY LIQUID INCINERATION.
CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS.

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



001037

HEXANE

PAGE, 3

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED

RESPIRATORY PROTECTION: IF WORKPLACE EXPOSURE LIMIT(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II), A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS, NITRILE RUBBER

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES,

(CONSULT YOUR SAFETY EQUIPMENT SUPPLIER)

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.