

0000 135

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
A-078 Jell Vandal Mark Remover

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Dymon, Inc.	Emergency Telephone Number 800-255-4564
Address (Number, Street, City, State, and ZIP Code) 3401 Kansas Ave. Kansas City, KS 66106	Telephone Number for Information 800-255-4564
	Date Prepared 6-13-86
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Isobutane Propellant CAS#75-28-5		20		10
Toluene Flammable CAS#108-88-3		100		20-40
Acetone Flammable CAS#67-64-1		750		1-10
Butyl Cellosolve CAS#111-76-2		25		10-20

MAINTENANCE PRODUCTS & EQUIPMENT COMPANY
By: Weinheimer
709 Erie Blvd. West
Syracuse, NY 13204
1-315-475-6301

Section III — Physical/Chemical Characteristics

Boiling Point	131 °F	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg.)	U/K	Melting Point	N/A
Vapor Density (AIR = 1)	U/K	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	100%		
Appearance and Odor	White liquid - solvent odor		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	45 °F T.O.C.	Flammable Limits	LEL	UEL
		Not known	N/A	N/A
Extinguishing Media	Foam			
Special Fire Fighting Procedures	None			
Unusual Fire and Explosion Hazards	Aerosol under pressure. Do not heat or store above 130 °F.			

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts CO, CO₂

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) Inhalation may cause nasal irritation.

Carcinogenicity: None known^{NTP?} IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure Skin irritation - dizziness on excessive inhalation.

Medical Conditions Generally Aggravated by Exposure

Emergency and First Aid Procedures Provide proper ventilation. Wash skin well with mild soap and water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled Wash well with water.

Waste Disposal Method Approved landfill.

Precautions to Be Taken in Handling and Storing Store in cool dry area.

Other Precautions Do not expose to temperatures above 130° F.

Section VIII — Control Measures

Respiratory Protection (Specify Type) Not required

Ventilation	Local Exhaust	Satisfactory	Special	N/A
	Mechanical (General)	Not required	Other	N/A

Protective Gloves Neoprene Eye Protection Goggles

Other Protective Clothing or Equipment Protect all body parts.

Work/Hygienic Practices Normal practices.