



May 21, 1993

PURCHASE ORDER NUMBER: K98026

SYRACUSE CITY SCHOOL
DISTRICT
725 HARRISON ST
SYRACUSE, NY 13210

CUST#: 8963407

TO: Safety Director/Plant Manager/Lab Director
SUBJECT: Material Safety Data Sheets

Enclosed are the Material Safety Data Sheets (MSDS's) listed below for KODAK chemical products you have purchased.

You should maintain a file of these sheets in the event you receive requests for them or have to provide them to your customers or employees as required by certain state right-to-know laws and/or the Federal Hazard Communication Standard. The information contained in a product's MSDS should be provided to each person prior to that person using the product. For customers and users in the State of California, your attention is especially directed to the information provided in the Section of the MSDS entitled, Toxicity and Health Hazard Data. Please feel free to duplicate the information we have provided.

You will not be sent another Material Safety Data Sheet for this product with subsequent orders unless a significant change in information occurs, which would result in a revised MSDS. When a revised MSDS is provided, indicated by an asterisk (*) following the Index No., you should replace any MSDS previously received with the revised MSDS.

Thank you for purchasing KODAK products.

Eastman Kodak Company

<u>Index No.</u>	<u>MSDS Name</u>
J-0002.730B *	KODAK C Toner, Black



E000070-2-04-04

MATERIAL SAFETY DATA SHEET

200001062/F/USA - J-0002.730B

Approval Date: 04/28/1993

Print Date: 05/01/1993

Page 1

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: KODAK C Toner, Black

Catalog Number(s): 841 9822 - 1165 gram(s)
836 5561 - 620 gram(s)

Manufacturer/Supplier: EASTMAN KODAK COMPANY, Rochester, New York 14650

For Emergency Health, Safety & Environmental Information, call: 716-722-5151

For Other Information, call the Marketing and Distribution Center in Your Area.

Synonym(s): KAN 471470; J-0002.730

2. COMPOSITION/INFORMATION ON INGREDIENTS

Weight % - Component - (CAS Registry No.)

90-95	Styrene acrylate copolymer (057516-68-4)
5-10	Carbon black (001333-86-4)
< 1	Benzene methanamine salt (124088-59-1)
< 1	Strontium ferrite (012023-91-5)
< 1	Vinylidene fluoride homopolymer (024937-79-9)

3. HAZARDS IDENTIFICATION

LOW HAZARD FOR RECOMMENDED HANDLING

4. FIRST-AID MEASURES

Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms persist.

Eyes: Any material that contacts the eye should be washed out immediately with water. Get medical attention if symptoms occur.

Skin: Wash with soap and water. Get medical attention if symptoms occur.

Ingestion: Drink 1-2 glasses of water. Seek medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Water spray, carbon dioxide (CO2), dry chemical



E000070-2-03-04

MATERIAL SAFETY DATA SHEET

200001062/F/USA - J-0002.730B

Approval Date: 04/28/1993

Print Date: 05/01/1993

Page 2

Special Fire-Fighting Procedures: None

Hazardous Combustion Products: Carbon dioxide, carbon monoxide

Unusual Fire and Explosion Hazards: Powdered material may form explosive dust-air mixtures.

6. ACCIDENTAL RELEASE MEASURES

Do not use a vacuum cleaner to clean up spills of powdered toners. The very fine particles can cause a fire or explosion. Sweep material onto paper and place in a fiber carton. Clean surface thoroughly to remove residual contamination.

7. HANDLING AND STORAGE

Personal Precautionary Measures: Avoid breathing dust. Use with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials. Minimize dust generation and accumulation. Refer to NFPA Pamphlet No. 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries." Use with adequate ventilation.

Storage: Keep container closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

ACGIH Threshold Limit Value (TLV):

Carbon black: 3.5 mg/m³ TWA

OSHA (USA) Permissible Exposure Limit (PEL):

Carbon black: 3.5 mg/m³ TWA

Ventilation: Good ventilation (typically 4-6 room volumes per hour) should be used. Ventilation rates should be matched to conditions.

Personal Protection: Good industrial hygiene practice should be followed which includes preventing eye contact and minimizing skin contact and inhalation.

Respiratory Protection: None should be needed.

MATERIAL SAFETY DATA SHEET

200001062/F/USA - J-0002.730B

Approval Date: 04/28/1993

Print Date: 05/01/1993

Page 3

Eye Protection: It is a good industrial hygiene practice to minimize eye contact.

Skin Protection: For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Recommended Decontamination Facilities: Washing facilities

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Solid (powder)

Color: Black

Odor: Slight

Specific Gravity (water = 1): Not available

Vapor Pressure: Negligible

Vapor Density (Air = 1): Negligible

Evaporation Rate (n-butyl acetate = 1): Negligible

Volatile Fraction by Weight: Negligible

Melting Point: Not available

Solubility in Water: Negligible

pH: Not applicable

Flash Point: Not applicable, combustible solid

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Strong oxidizing agents

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Effects of Exposure:

Inhalation: Expected to be a low hazard for recommended handling.

Eyes: No specific hazard known. May cause transient irritation.

Skin: Expected to be a low hazard for recommended handling.

Ingestion: Expected to be a low ingestion hazard.

Overexposure to carbon black dust may result in irritation of the respiratory tract and pneumoconiosis. Dust sampling performed by Eastman Kodak Company during typical Eastman Kodak copier operation has indicated that levels are well below occupational exposure guidelines and do not



E000070-2-02-04

MATERIAL SAFETY DATA SHEET

200001062/F/USA - J-0002.730B

Approval Date: 04/28/1993

Print Date: 05/01/1993

Page 4

present a respirable dust hazard. A Health Profile Study of electrographic toner manufacturing employees found no evidence of increased health risk when compared to other hourly employees. This finding is based on a review of health history questionnaires, medical examinations, sickness-absence reports, and death certificates.

Mutagenicity/Genotoxicity Data:

Salmonella typhimurium assay (Ames test): Negative

12. ECOLOGICAL INFORMATION

This material has not been tested for environmental effects. In a spill situation this material may be visually unpleasant; however, it is not expected to cause any adverse environmental effects.

13. DISPOSAL CONSIDERATIONS

Incinerate or landfill. Can be incinerated when in compliance with local regulations. Discharge, treatment, or disposal may be subject to national, state, or local laws.

14. TRANSPORT INFORMATION

- For transportation information regarding this product, please phone the Eastman Kodak Distribution Center nearest you: Rochester, NY (716) 588-3536 or 588-3573 or 588-3035; Oak Brook, IL (312) 954-6000; Chamblee, GA (404) 455-0123; Dallas, TX (214) 241-1611; Whittier, CA (213) 945-1255; Honolulu, HI (808) 833-1661.

15. REGULATORY INFORMATION

- Material(s) known to the State of California to cause cancer: None
- Material(s) known to the State of California to cause adverse reproductive effects: None
- Carcinogenicity Classification (components present at 0.1% or more):
 - International Agency for Research on Cancer (IARC): None
 - American Conference of Governmental Industrial Hygienists (ACGIH): None
 - National Toxicology Program (NTP): None
 - Occupational Safety and Health Administration (OSHA): None
- Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: None

MATERIAL SAFETY DATA SHEET

200001062/F/USA - J-0002.730B

Approval Date: 04/28/1993

Print Date: 05/01/1993

Page 5

16. OTHER INFORMATION

US/Canadian Label Statements:

LOW HAZARD FOR RECOMMENDED HANDLING

For additional information, see Material Safety Data Sheet (MSDS) for this material.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.



E000070-2-01-04