

FIRESTONE  
MATERIAL SAFETY  
DATA SHEET

DEEMED HAZARDOUS ACCORDING TO  
OSHA HAZARD COMMUNICATION  
RULE 29 CFR 1910.1200

FIRESTONE CODE: NE  
DATE ENTERED : 06/20/90  
DATE REVISED : 03/15/91  
CLASSIFICATION: BP

\*\*\*\*\*  
SECTION 1 PRODUCT IDENTIFICATION  
\*\*\*\*\*

PRODUCT NAME: SPLICE WASH SW-100  
CHEMICAL NAME/SYNONYMS: N.A.V.

CHEMICAL FAMILY: ALIPHATIC HYDROCARBON

CHEMICAL FORMULA: N.A.V.  
24-HOUR EMERGENCY PHONE NO: (216) 379-6409  
CHEMTREC PHONE NO: (800) 424-9300

MANUFACTURER'S NAME: FIRESTONE BUILDING PRODUCTS  
MANUFACTURER'S ADDRESS: 525 CONGRESSIONAL BLVD.  
CARMEL, IND. 46032

NFPA ACUTE HAZARD RATING: N.A.V.  
HEALTH: FLAMMABILITY: REACTIVITY:

\*\*\*\*\*  
SECTION 2 CHEMICAL COMPOSITION  
\*\*\*\*\*  
SEE SECTION 12 FOR LD50 AND LC50 DATA

INGREDIENT (CHEMICAL NAME)	CAS NO.	%	PEL	TLV
*SOLVENT, NAPHTHA (LIGHT ALIPHATIC SOLVENT)	64742-89-8	100	N.A.V.	400 PPM
*BENZENE	71-43-2	0.01	1 PPM	10 PPM

\*\*\*\*\*  
SECTION 3 EMERGENCY AND FIRST AID PROCEDURES  
\*\*\*\*\*

EYE CONTACT:  
-HOLD EYELIDS OPEN AND FLUSH IMMEDIATELY WITH GENTLE STREAM OF WATER FOR AT  
LEAST 15 MINUTES, PREFERABLY AT EYEWASH FOUNTAIN.  
-GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN CONTACT:  
-WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER WHEN TIME PERMITS.  
-WASH HANDS AND FACE THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR  
SMOKING.

INHALATION:  
-REMOVE TO FRESH UNCONTAMINATED AIR.  
-ADMINISTER OXYGEN IF BREATHING IS LABORED. GIVE ARTIFICIAL RESPIRATION IF  
BREATHING HAS STOPPED.  
-GET MEDICAL ATTENTION IMMEDIATELY IF OXYGEN OR ARTIFICIAL RESPIRATION ARE  
ADMINISTERED.

INGESTION:  
-CONTAINS PETROLEUM DISTILLATES. IN CASE OF ACCIDENTAL INGESTION, DO NOT INDUCE  
VOMITING.  
-GET MEDICAL ATTENTION AND ADVISE THE PHYSICIAN OF THE NATURE OF THE MATERIAL.

SPECIAL INSTRUCTIONS FOR PHYSICIAN:  
N.A.V.



\*\*\*\*\*  
SECTION 7 FIRE AND EXPLOSION HAZARD DATA  
\*\*\*\*\*

FLASH POINT: 22 DEG. F  
METHOD USED:  
-NOT AVAILABLE  
FLAMMABLE (EXPLOSIVE) LIMITS IN AIR: LEL: 1.0 UEL: 7.0  
AUTOIGNITION TEMPERATURE: N.AV DEG.  
SUITABLE EXTINGUISHING MEDIA:  
-ALCOHOL FOAM, CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS COMBUSTION PRODUCTS:  
-CARBON DIOXIDE AND CARBON MONOXIDE  
-ALDEHYDES  
-PARTIALLY BURNED CARBON

RECOMMENDED FIREFIGHTING PROCEDURE:  
-WEAR IMPERMEABLE PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS.  
TOXIC FUMES AND VAPORS MAY BE EVOLVED.

UNUSUAL FIRE & EXPLOSION HAZARD:  
-HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER STREAM.

\*\*\*\*\*  
SECTION 8 REACTIVITY DATA  
\*\*\*\*\*

THERMAL STABILITY: STABLE  
CONDITIONS TO AVOID:  
-HEAT, SPARKS, AND OPEN FLAMES.

HAZARDOUS DECOMPOSITION PRODUCTS:  
-NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID:  
-N.AV.

INCOMPATIBILITY:  
MATERIALS TO AVOID:  
-STRONG OXIDIZING AGENTS

CORROSIVE ACTION ON MATERIALS:  
-N.AV.

\*\*\*\*\*  
SECTION 9 STORAGE AND HANDLING PRECAUTIONS  
\*\*\*\*\*

STORAGE:  
-KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.  
-KEEP CONTAINERS CLOSED.  
-STORE AT ROOM TEMPERATURE WITH GOOD VENTILATION.

HANDLING:  
-VAPORS OF THIS MATERIAL ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW OR  
CONFINED AREAS.  
-GROUND DISPENSING EQUIPMENT TO AVOID STATIC DISCHARGE.  
-EMPTIED CONTAINERS MAY RETAIN HAZARDOUS PROPERTIES. DO NOT CUT OR WELD ON OR  
NEAR CONTAINER.

PRECAUTIONARY LABELING:  
WARNING! FLAMMABLE. BREATHING OF VAPORS MAY CAUSE  
HEADACHES, DIZZINESS, NAUSEA & UNCONSCIOUSNESS.

\*\*\*\*\*  
SECTION 10 ENVIRONMENTAL INFORMATION  
\*\*\*\*\*

SPILL OR LEAK PROCEDURES:  
ELIMINATE ALL IGNITION SOURCES. CONTROL THE SOURCE OF THE  
SPILL IF IT IS SAFE TO DO SO. VENTILATE ENCLOSED AREAS TO  
PREVENT VAPOR ACCUMULATION. RESTRICT ACCESS BY UNAUTHORIZED  
PERSONNEL. ABSORB SPILLED PRODUCT WITH VERMICULITE OR  
OTHER ABSORBANT MATERIAL. SHOVEL OR SCOOP INTO A SEALABLE  
CONTAINER FOR DISPOSAL.

SPILL REPORTABLE QUANTITY: N.AV. LBS. (N.AV.)

WASTE DISPOSAL METHOD(INCLUDING CLEAN-UP MEDIA)  
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL  
ENVIRONMENTAL AND WASTE REGULATIONS.

EPA OR APPROPRIATE WASTE CLASSIFICATION: N.AV.

PROCEDURE FOR HANDLING EMPTY CONTAINERS:  
N.AV.

ENVIRONMENTAL TOXICITY DATA:  
N.AV.

OTHER REGULATORY CONTROLS: N.AV.

MATERIAL CLASSIFIED UNDER THE CLEAN WATER ACT(USA) OR APPROPRIATE WATER REGULATIONS AS A: N.AV.

TOXIC POLLUTANT(SECTION 307)? YES NO

HAZARDOUS SUBSTANCE(SECTION 311)?

OIL(SECTION 311)? YES NO

HAZARDOUS CLASS (SECTION 311): YES NO

ACUTE CHRONIC FIRE PRESSURE REACTIVE

MATERIAL CLASSIFIED UNDER THE CLEAN AIR ACT(USA) OR APPROPRIATE CLEAN AIR REGULATIONS AS A: N.AV.

HAZARDOUS AIR POLLUTANT(SECTION 12)?

YES NO

COMMENTS:

NO SARA REPORTABLE CHEMICALS

MATERIAL CLASSIFICATION UNDER CLEAN WATER ACT: N.AV.

MATERIAL CLASSIFICATION UNDER CLEAN WATER ACT: N.AV.

\*\*\*\*\*  
SECTION 11 TRANSPORTATION/SHIPPING  
\*\*\*\*\*

INDICATE COUNTRY/REGULATORY AGENCY WHICH SPECIFIES REQUIREMENTS:  
-USA-DOT-IMO

PROPER SHIPPING NAME:  
NAPHTHA SOLVENT

HAZARD CLASS:  
-FLAMMABLE LIQUID  
IDENTIFICATION NO.: UN 1256

LABELS REQUIRED:  
-FLAMMABLE LIQUID

OTHER REQUIREMENTS:  
REFERENCE CFR 49, PRINCIPLE INGRED.: NAPHTHA SOLVENT, IMDG  
CLASS 3.2, PG 3264, FLASHPOINT -6 C

\*\*\*\*\*  
SECTION 12 ADDITIONAL DATA/COMMENTS  
\*\*\*\*\*

SOLVENT NAPHTHA LD50 ORAL(RAT) = >5 G/KG, LC50 N. AV.

\*\*\*\*\*  
SECTION 13 MISCELLANEOUS INFORMATION  
\*\*\*\*\*

INFORMATION SUPPLIED BY: R. HOFER, CIH  
TITLE: SR. IND. HYGIENIST  
TELEPHONE NUMBER FOR ROUTINE INQUIRIES: (216) 379-7394

DATE OF PREPARATION OF MSDS: 03/15/91  
REVISED, SUPERSEDES 09/28/90  
COMPANY NAME: BRIDGESTONE/FIRESTONE, INC.  
ADDRESS: 1200 FIRESTONE PKWY., AKRON, OH 44317  
TELEPHONE NUMBER: (216) 379-7000

The information contained in this material safety data sheet is based on data and recommendations considered accurate. In some cases, the information has been obtained from other organizations and companies. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Bridgestone/Firestone Inc. assumes no responsibility for injury to buyer, the buyer's employees, or any thirdpersons, if reasonable safety procedures are not followed. Additionally, Bridgestone/Firestone Inc. assumes no responsibility for injury to buyer, the buyer's employees, or any third persons, if such injury is the result of abnormal use of the material, even if reasonable safety procedures are followed.