

***UNIVERSAL INDICATOR SOL
***UNIVERSAL INDICATOR SOL
***UNIVERSAL INDICATOR SOL

MATERIAL SAFETY DATA SHEET

FISHER SCIENTIFIC
CHEMICAL DIVISION
1 REAGENT LANE
FAIR LAWN NJ 07410
(201) 796-7100

EMERGENCY CONTACTS
GASTON L. PILLORI
(201) 796-7100

DATE 04/30/88
PO NBR: K12085
ACCT: 818730-99
INDEX: 25881100141
CAT NO: S1601

THE INFORMATION BELOW IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES.

SUBSTANCE IDENTIFICATION

SUBSTANCE: ***UNIVERSAL INDICATOR SOLUTION***

TRADE NAMES/SYNONYMS:
S0-1-60; ACC40100

CERCLA RATINGS (SCALE 0-3): HEALTH=1 FIRE=3 REACTIVITY=0 PERSISTENCE=0
NFPA RATINGS (SCALE 0-4): HEALTH=1 FIRE=3 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

- COMPONENT : ISOPROPYL ALCOHOL
CAS 67-63-0
PERCENT : 37.0
- COMPONENT : METHANOL
CAS 67-56-1
PERCENT : 0.8
- COMPONENT : SODIUM HYDROXIDE
CAS 1310-73-2
PERCENT : 0.003
- COMPONENT : METHYL RED
CAS 493-52-7
PERCENT : 0.02
- COMPONENT : THYMOL BLUE
CAS 76-61-9
PERCENT : 0.03
- COMPONENT : BROMOTHYMOL BLUE SODIUM SALT
CAS 34722-90-2
PERCENT : 0.03
- COMPONENT : PHENOLPHTHALEIN
CAS 81-90-3
PERCENT : 0.03
- COMPONENT : WATER
PERCENT : 62.0

EXPOSURE LIMITS:
 ISOPROPYL ALCOHOL
 400 PPM OSHA TWA
 400 PPM ACGIH TWA
 500 PPM ACGIH STEL
 400 PPM NIOSH RECOMMENDED TWA
 800 PPM NIOSH RECOMMENDED 15 MINUTE CEILING

PHYSICAL DATA

DESCRIPTION: CLEAR GREENISH SOLUTION WITH AN ODOR OF ALCOHOL. ODOR
 TAKEN WITH THE IRRITANCY GIVES PRODUCT SATISFACTORY WARNING PROPERTIES.
 BOILING POINT: NOT AVAILABLE MELTING POINT: NOT AVAILABLE
 SPECIFIC GRAVITY: 0.93 VAPOR PRESSURE: NOT AVAILABLE
 EVAPORATION RATE: (ETHER=1) >1 (TTE) SOLUBILITY IN WATER: COMPLETE
 VAPOR DENSITY: NOT AVAILABLE

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD:
 DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT, FLAME OR SHOCK. VAPORS ARE HEAVIER
 THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO AN IGNITION SOURCE AND
 FLASH BACK.
 FLASH POINT: 75 F (24 C) UPPER EXPLOSIVE LIMIT: 12.0%
 LOWER EXPLOSIVE LIMIT: 2.0% FLAMMABILITY CLASS(OSHA): IC
 FIREFIGHTING MEDIA:
 DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY
 FIREFIGHTING:
 WEAR PERSONAL PROTECTIVE EQUIPMENT. MOVE CONTAINER FROM FIRE AREA IF POSSIBLE.
 COOL FIRE-EXPOSED CONTAINERS WITH WATER FROM SIDE UNTIL WELL AFTER FIRE IS
 OUT.
 USE FLOODING AMOUNTS OF WATER AS FOG; SOLID STREAMS MAY BE INEFFECTIVE. COOL
 CONTAINERS WITH FLOODING AMOUNTS OF WATER FROM AS FAR A DISTANCE AS POSSIBLE.
 AVOID BREATHING VAPORS; KEEP UPWIND (BUREAU OF EXPLOSIVES, EMERGENCY HANDLING
 OF HAZARDOUS MATERIALS IN SURFACE TRANSPORTATION, 1981).

TOXICITY

ISOPROPYL ALCOHOL: 20 PPM EYE-HUMAN IRRITATION; 16 MG EYE-RABBIT IRRITATION;
 400 PPM INHALATION-MAN TLD; 8600 MG/KG ORAL-MAN LDLO; 15,710MG/KG
 ORAL-HUMAN TLD; 5840 MG/KG ORAL-RAT LD50; 935 MG/KG INTRAPERITONEAL-MOUSE
 LD50; 16000 PPM/8 HOURS INHALATION-RAT LC50; 6150 MG/KG ORAL-DOG LD50;
 5120 MG/KG INTRAVENOUS-DOG LDLO; 1965 MG/KG INTRAVENOUS-CAT LDLO; 5000 MG/KG
 ORAL-RABBIT LDLO; 13 GM/KG SKIN-RABBIT LD50; MUTAGENIC DATA (RTCS);
 CARCINOGEN STATUS: NONE. A SKIN AND MUCOUS MEMBRANE IRRITANT, SEVERE EYE

HEALTH EFFECTS AND FIRST AID

INHALATION:
IRRITANT/NARCOTIC.

20,000 PPM ISOPROPYL ALCOHOL IMMEDIATELY DANGEROUS TO LIFE OR HEALTH.
ACUTE EXPOSURE-- ISOPROPYL ALCOHOL CAUSES DIZZINESS, INCOORDINATION, HEAD-
ACHE, CONFUSION, PERSISTENT NAUSEA, HEMATEMESIS, ABDOMINAL PAIN, STUPOR,
HYPOTENSION, ANEMIA, REFRACTORY NARCOSIS, AREFLEXIA, DEPRESSED RESPIR-
ATION, DECREASED URINATION FOLLOWED BY DIURESIS, AND UREMIA.
TENDERNESS AND EDEMA OF MUSCLES MAY ALSO OCCUR. SEVERE CASES MAY CAUSE
COMA.

CHRONIC EXPOSURE-- SEE MUTAGENIC DATA REFERENCE IN TOXICITY SECTION.

FIRST AID-- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING
HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST.
GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:
IRRITANT/NARCOTIC.

ACUTE EXPOSURE-- ISOPROPYL ALCOHOL CAUSES NARCOSIS WITH NAUSEA, VOMITING,
HYPOTENSION, DEPRESSED RESPIRATION, ANEMIA, UREMIA, AND COMA.

CHRONIC EXPOSURE-- ISOPROPYL ALCOHOL MAY CAUSE DERMATITIS DUE TO THE
DEFATTING ACTION ON THE SKIN. SEE MUTAGENIC DATA REFERENCE IN TOXICITY
SECTION.

FIRST AID-- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED
AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO
EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL
ATTENTION IMMEDIATELY.

EYE CONTACT:
CORROSIVE.

ACUTE EXPOSURE: ISOPROPYL ALCOHOL VAPORS MAY BE IRRITATING AND MAY CAUSE
PROFUSE LACRIMATION. DIRECT CONTACT CAUSES IRRITATION, BURNS AND
PERMANENT CORNEAL DAMAGE.

CHRONIC EXPOSURE: PROLONGED OR REPEATED EXPOSURE TO ISOPROPYL ALCOHOL VAPORS
MAY CAUSE CONJUNCTIVITIS.

FIRST AID-- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER. OCCASIONALLY
LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS
(AT LEAST 15-20 MINUTES). IN CASE OF BURNS, APPLY STERILE BANDAGES LOOSELY
WITHOUT MEDICATION. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:
NARCOTIC.

ACUTE EXPOSURE-- ISOPROPYL ALCOHOL CAUSES NARCOSIS WITH HEADACHE, NAUSEA,
HEMATEMESIS, DIZZINESS, INCOORDINATION, ABDOMINAL PAIN, STUPOR, DEPRESSED
RESPIRATION, OLIGURIA, UREMIA, DIURESIS, AND COMA. DEATH MAY OCCUR FROM
RESPIRATORY PARALYSIS.

UNIVERSAL INDICATOR SOL PAGE 04 OF 05
FIRST AID- IF VICTIM IS CONSCIOUS, IMMEDIATELY GIVE 2 TO 4 GLASSES OF WATER.
INDUCE VOMITTING BY TOUCHING FINGER TO BACK OF THROAT. IF NOT BREATHING,
GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION IMMEDIATELY.

REACTIVITY

REACTIVITY:
STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.
INCOMPATIBILITIES:
OXIDIZERS AND OTHER MATERIALS, EXAMPLES FOLLOW:

ISOPROPYL ALCOHOL
PHOSGENE: IN THE PRESENCE OF IRON SALTS, MAY EXPLODE.
NITROFORM (>50%): DISSOLVES LIBERATING HEAT AND POSSIBLY EXPLODING.
TRINITROMETHANE: POSSIBLE EXPLOSION.
HYDROGEN: WHEN A STREAM OF HYDROGEN ENTRAINED ISOPROPYL ALCOHOL VAPORS AND
PALLADIUM PARTICLES, THE MIXTURE CAUGHT FIRE UPON CONTACT WITH AIR.
POTASSIUM TERT-BUTOXIDE: IGNITION.
DIOXYGENYL TETRAFLUOROBORATE: IGNITION AT AMBIENT TEMPERATURES.
CHROMIUM TRIOXIDE (GRANULAR): IGNITION.
2-BUTANONE: ACCELERATES THE PEROXIDATION OF THE ALCOHOL, RESULTING IN
FORMATION OF POTENTIALLY EXPLOSIVE PRODUCTS.
HYDROGEN PEROXIDE: FORMATION OF A SHOCK- OR HEAT-SENSITIVE, DETONATABLE
PRODUCT.
OXYGEN (GAS): AUTOXIDATION, ON EXPOSURE TO LIGHT, RESULTS IN FORMATION OF
POTENTIALLY EXPLOSIVE KETONES AND HYDROGEN PEROXIDE.
OLEUM: REACTS WITH AN INCREASE IN TEMPERATURE AND PRESSURE.
ALUMINUM: DISSOLUTION IS EXOTHERMIC.
STRONG OXIDIZERS: FIRE AND EXPLOSION HAZARD.

DECOMPOSITION:
COMBUSTION MAY RELEASE TOXIC OXIDES OF CARBON.

POLYMERIZATION:
WILL NOT OCCUR.

XX
CONDITIONS TO AVOID
XX

AVOID HEATING TO THE POINT WHERE AN UNACCEPTABLE AMOUNT OF ISOPROPYL ALCOHOL
VAPOR (OR MIST) ACCUMULATES. AVOID CONTACT WITH OR STORAGE WITH INCOMPATIBLE
MATERIALS, INCLUDING THOSE LISTED IN THE REACTIVITY SECTION.

XX
SPILL AND LEAK PROCEDURES
XX

OCCUPATIONAL SPILL:
REMOVE SOURCES OF IGNITION. PROVIDE VENTILATION. ABSORB WITH VERMICULITE AND
SCOOP INTO CONTAINER. KEEP OUT OF SEWERS AND WATER SOURCES.

PROTECTIVE EQUIPMENT

VENTILATION:
PROVIDE LOCAL EXHAUST VENTILATION OR PROCESS ENCLOSURE TO MEET PERMISSIBLE

UNIVERSAL INDICATOR SOL PAGE 05 OF 05
EXPOSURE LIMIT REQUIREMENTS. EQUIPMENT MUST BE EXPLOSION-PROOF. ODOR DETECTION
ALONE MUST NOT BE USED AS A SUBSTITUTE FOR MONITORING METHODS.

RESPIRATOR:
EXPOSURE LIMIT TO 1000 PPM (ISOPROPYL ALCOHOL)-
CHEMICAL CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE
AND A FULL FACEPIECE.

5000 PPM (ISOPROPYL ALCOHOL)-
CHIN STYLE GAS MASK WITH AN ORGANIC VAPOR CANISTER.

>5000 PPM (ISOPROPYL ALCOHOL) INCLUDING THE IDLH LEVEL, 20,000 PPM (2%)-
SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE
OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

NOTE THAT AT 20,000 PPM, THIS IS THE LOWER EXPLOSIVE LIMIT: SEE FIRE AND
EXPLOSION HAZARDS.

FIREFIGHTING-- SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE
OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:
EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE CLOTHING AND EQUIPMENT TO PREVENT
REPEATED OR PROLONGED SKIN CONTACT WITH THIS SOLUTION.

GLOVES:
EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT REPEATED OR
PROLONGED CONTACT WITH THIS SOLUTION. PREFERRED MATERIALS: BUTYL, NEOPRENE
AND NITRILE RUBBLE GLOVES.

EYE PROTECTION:
EMPLOYEE MUST WEAR SPLASH-PROOF SAFETY GOGGLES AND A FACESHIELD WHENEVER
THERE IS REASONABLE PROBABILITY OF CONTACT WITH THIS SOLUTION. DO NOT WEAR
CONTACT LENSES WHEN WORKING WITH CHEMICALS.

WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY BE EXPOSED TO THIS
SOLUTION, THE EMPLOYER SHALL PROVIDE AN EYE-WASH FOUNTAIN WITHIN THE IMMEDIATE
WORK AREA FOR EMERGENCY USE.

AUTHORIZED - FISHER SCIENTIFIC GROUP, INC.
CREATION DATE: 11/01/85 REVISION DATE: 11/14/85

-ADDITIONAL INFORMATION-
THE INFORMATION BELOW IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST
INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF
MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO
SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS
SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE
INFORMATION FOR THEIR PARTICULAR PURPOSES.