Tox: 017554 Product: COOLING SYSTEM FAST ELUSH

APPROVED to ACTIVE NAAO prod. spec ESR-M14P7-A.

This material is a LIQUID under normal conditions. The Specific Gravity is 0.912 . The Boiling Point is ± 177 C. The Flash Point is ± 068 C (Tag. Closed Cup). The results for pH are not available.

* * * * * * Toxicology Review * * * * *
Tox: 017554 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 07/12/82

50ppm CEILING 95-50-1 * 0-DICHLOROBENZENE

* See chemical fact sheets (CFS) for additional details on these ingredients.

Also Contains: KEROSENE
----- Signal Word -------

DANGER

---- Hazards ------

IRRITATING TO EYES AND SKIN MAY BE FATAL IF SWALLOWED COMBUSTIBLE

----- Safe Handling and Storage -----

AVOID PROLONGED OR REPEATED SKIN CONTACT USE WITH ADEQUATE VENTILATION KEEP FROM HEAT, SPARKS, OR OPEN FLAME

PETROLEUM LUBRICATING OILS (TB 101)

---- Protective Measures and Treatments- ---

Tox: 017554 Product: COOLING SYSTEM FAST FLUSH

FNHI : FP-210 (11 OZ CAN)

The chemical identification and properties for this material were provided by the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety, Ford Motor Company 900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)