

Tox: 014445 Product: GRAY PAINT (M1750A)
FNHI : M20J1750SE5 (13 OZ AEROSOL CAN)

000173

APPROVED to ACTIVE NAAO prod. spec ESN-MIJ101-A.

----- Chemical and Physical Properties -----

This material is a AEROSOL under normal conditions.
The results for Specific Gravity are not available.
The results for Boiling Point are not applicable.
The Flash Point is -011 C.
The results for pH are not applicable.

***** Toxicology Review *****

Tox: 014445 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 03/19/87

----- Hazardous Ingredients (HAZCOM) -----

-- TLV --	CAS number	Chemical name
750ppm TWA	67-64-1 *	ACETONE
asphyxiant	74-98-6 *	PROPANE
100ppm TWA+N	75-09-2 *	METHYLENE CHLORIDE
100ppm TWA	108-88-3 *	TOLUENE
2.5mg/m3 (FORD) TWA	8012-95-1 *	PARAFFIN OIL
10mg/m3 TWA	13463-67-7 *	TITANIUM DIOXIDE

-- N=NTP

* See chemical fact sheets (CFS) for additional details on these ingredients.

----- Signal Word -----

WARNING

----- Hazards -----

HARMFUL BY INHALATION
IRRITATING TO RESPIRATORY SYSTEM
IRRITATING TO EYES AND SKIN
CONTENTS UNDER PRESSURE
MAY BE HARMFUL OR TOXIC BY SKIN ABSORPTION
CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. OVEREXPOSURE MAY CREATE
CANCER RISK

----- Safe Handling and Storage -----

DO NOT BREATHE GAS/FUMES/VAPOR/SPRAY
AVOID CONTACT WITH EYES
AVOID PROLONGED OR REPEATED SKIN CONTACT
USE WITH ADEQUATE VENTILATION
DO NOT PUNCTURE CONTAINER
DO NOT STORE, INCINERATE, OR HEAT ABOVE 120 DEGREES FAHRENHEIT

Tox: 014445 Product: GRAY PAINT (M1750A)
FNHI : M20J1750SE5 (13 OZ AEROSOL CAN)

- - - - - Protective Measures and Treatments- - - - -

IMPERVIOUS GLOVES

SAFETY GLASSES

VENTILATION (CONTACT INDUSTRIAL HYGIENE FOR SPECIFIC DETAILS)

THIS MATERIAL CONTAINS A SUBSTANCE REGULATED UNDER A SPECIFIC OSHA STANDARD,
SEE CHEMICAL FACT SHEET FOR DETAILS

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK
MEDICAL ADVICE

WASH THOROUGHLY AFTER HANDLING

- - - - - Toxicology Bulletins- - - - -

CHLORINATED AND NONCHLORINATED SOLVENTS AS MIXTURES (TB 107)

The chemical identification and properties for this material were provided by
the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,
Ford Motor Company
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)