

Tox: 039554 Product: 80W-90 MULTI-PURPOSE GEAR LUBRICANT
FNHI : 2GM19580AA (2 GAL CONTAINER)

This material has not been identified against a material Specification.

- - - - - Chemical and Physical Properties - - - - -

This material is a LIQUID under normal conditions.
The Specific Gravity is 0.890 .
The results for Boiling Point are unknown.
The Flash Point is +162 C (not specified).
The results for pH are not applicable.
The viscosity is 75 SUS (210 F).

***** Toxicology Review *****

Tox: 039554 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 12/23/87

----- Hazardous Ingredients (HAZCOM) -----

-- TLV --	CAS number	Chemical name
2.5mg/m3 (FORD) TWA	64742-01-4	+ RESIDUAL OILS (PETROLEUM), SOLVENT REFINED

+ For more information on CAS 64742-01-4, see CFS for CAS 8012-95-1.

- - - - - Signal Word - - - - -

CAUTION

- - - - - Hazards - - - - -

PROLONGED AND/OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION/DERMATITIS.
MAY CAUSE IRRITATION TO EYES

- - - - - Safe Handling and Storage - - - - -

AVOID CONTACT WITH EYES
AVOID PROLONGED OR REPEATED SKIN CONTACT
USE WITH ADEQUATE VENTILATION

- - - - - Protective Measures and Treatments - - - - -

IMPERVIOUS GLOVES
SAFETY GLASSES
IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK
MEDICAL ADVICE
WASH THOROUGHLY AFTER HANDLING

- - - - - Toxicology Bulletins - - - - -

PETROLEUM LUBRICATING OILS (TB 101)

Tox: 039554 Product: 80W-90 MULTI PURPOSE GEAR LUBRICANT
FNHI : 2GM19580AA (2 GAL CONTAINER)

The chemical identification and properties for this material were provided by the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,
Ford Motor Company
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)