

Tox: 039538 Product: BLUE PAINT (M1639A)  
FNHI : M2P1001639SE5 (-13 OZ AREOSOL CAN)

~~Duplicate~~ 167

APPROVED to ACTIVE NAAO prod. spec ESR-M2P100-B.

----- Chemical and Physical Properties -----

This material is a AEROSOL under normal conditions.  
The Specific Gravity is 0.600 .  
The Boiling Point is -039 to +198 C.  
The Flash Point is -039 C (Tag. Closed Cup).  
The results for pH are not applicable.

\*\*\*\*\* Toxicology Review \*\*\*\*\*

Tox: 039538 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 01/12/88

----- Hazardous Ingredients (HAZCOM) -----

-- TLV --	CAS number	Chemical name
1000ppm TWA	64-17-5 *	ETHYL ALCOHOL
750ppm TWA	67-64-1 *	ACETONE
asphyxiant	74-98-6 *	PROPANE
100ppm TWA+N	75-09-2 *	METHYLENE CHLORIDE
100ppm TWA	108-88-3 *	TOLUENE
400ppm TWA	141-78-6 *	ETHYL ACETATE
100ppm TWA	1330-20-7 *	XYLENE (ALL ISOMERS)

-- N=NTP

\* See chemical fact sheets (CFS) for additional details on these ingredients.

----- Signal Word -----

DANGER

----- Hazards -----

EXTREMELY FLAMMABLE  
HARMFUL BY INHALATION  
IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN  
CONTENTS UNDER PRESSURE  
MAY CAUSE LIVER/KIDNEY DAMAGE  
MAY BE HARMFUL OR TOXIC BY SKIN ABSORPTION  
CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. OVEREXPOSURE MAY CREATE  
CANCER RISK  
EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA AND INCOORDINATION  
PROLONGED OR REPEATED CONTACT MAY DRY AND/OR DEFAT THE SKIN

----- Safe Handling and Storage -----

DO NOT BREATHE GAS/FUMES/VAPOR/SPRAY  
KEEP IN A COOL, WELL-VENTILATED PLACE  
ELIMINATE ALL SOURCES OF IGNITION  
USE WITH ADEQUATE VENTILATION  
DO NOT PUNCTURE CONTAINER  
KEEP FROM HEAT, SPARKS, OR OPEN FLAME  
DO NOT GET IN EYES, ON SKIN OR CLOTHING  
DO NOT STORE, INCINERATE, OR HEAT ABOVE 120 DEGREES FAHRENHEIT

Tox: 039538 Product: BLUE PAINT (M1639A)  
FNHI : M2P1001639SE5 ( 13 OZ AREOSOL CAN)

- - - - - Protective Measures and Treatments - - - - -

IMPERVIOUS GLOVES

CHEMICAL GOGGLES

IMPERVIOUS APRON

VENTILATION (CONTACT INDUSTRIAL HYGIENE FOR SPECIFIC DETAILS)

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK  
MEDICAL ADVICE

REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE

FOR SKIN CONTACT, WASH IMMEDIATELY WITH SOAP AND WATER

IF INHALATION OF MATERIAL IS EXCESSIVE (AIR CONCENTRATION IS GREATER THAN THE  
TLV OR HEALTH EFFECTS ARE NOTICED), REMOVE IMMEDIATELY TO FRESH AIR.

The chemical identification and properties for this material were provided by  
the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,  
Ford Motor Company  
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)