

Tox: 016677 Product: SAE 10 ENGINE OIL  
FNHI : 1QM2C121-A10 ( 1 QT CAN)

000184

Tox: 016677 Product: SAE 30 ENGINE OIL  
FNHI : 1QM2C121-A30 ( 1 QT CAN)

Tox: 016677 Product: SAE 30 ENGINE OIL  
FNHI : 2GM2C121-A30 ( 2 GAL CAN)

Tox: 016677 Product: SAE 30 ENGINE OIL  
FNHI : 55M2C121-A30 ( 55 GAL DRUM)

Tox: 016677 Product: 15W-40 ENGINE OIL  
FNHI : 1QM2C121-AMV ( 1 QT CAN)

Tox: 016677 Product: 15W-40 ENGINE OIL  
FNHI : 2GM2C121-AMV ( 2 GAL CAN)

Tox: 016677 Product: 15W-40 ENGINE OIL  
FNHI : 55M2C121-AMV ( 55 GAL DRUM)

Tox: 016677 Product: 15W-40 ENGINE OIL  
FNHI : 5GM2C121-AMV ( 5 GAL CAN)

- APPROVED to INACTIVE NAAO prod. spec ESN-M2C121-B.
- APPROVED to ACTIVE NAAO prod. spec ESR-M2C171-A.
- APPROVED to ACTIVE NAAO prod. spec ESE-M2C176-A.
- APPROVED to ACTIVE NAAO prod. spec ESN-M2C121-C1.
- APPROVED to ACTIVE NAAO prod. spec ESN-M2C121-C2.
- APPROVED to ACTIVE NAAO prod. spec ESN-M2C121-C3.

- - - - - Chemical and Physical Properties - - - - -

This material is a LIQUID under normal conditions.  
The Specific Gravity is 0.880 .  
The results for Boiling Point are not applicable.  
The Flash Point is >216 C (Cleveland Open Cup).  
The results for pH are not applicable.

\*\*\*\*\* Toxicology Review \*\*\*\*\*

Tox: 016677 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 03/24/87

----- Hazardous Ingredients (HAZCOM) -----

-- TLV --	CAS number	Chemical name
2.5mg/m3 (FORD) TWA	64741-88-4 +	PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY

+ For more information on CAS 64741-88-4, see CFS for CAS 8012-95-1.

Also Contains: ZINC DIALKYL DITHIOPHOSPHATE

- - - - - Signal Word - - - - -

CAUTION

- - - - - Hazards - - - - -

PROLONGED AND/OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION/DERMATITIS.  
MAY CAUSE IRRITATION TO EYES

Tox: 016677 Product: SAE 10 ENGINE OIL  
FNHI : 1QM2C121-A10 ( 1 QT CAN)

- - - - - Safe Handling and Storage - - - - -

AVOID CONTACT WITH EYES  
AVOID PROLONGED OR REPEATED SKIN CONTACT  
INCOMPATIBLE WITH STRONG OXIDIZING AGENTS  
AVOID GENERATION OF OIL MISTS  
For fires, use extinguishing media for Class B hazards.

- - - - - Protective Measures and Treatments- - - - -

IMPERVIOUS GLOVES  
SAFETY GLASSES  
IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK  
MEDICAL ADVICE  
IF SWALLOWED, GET IMMEDIATE MEDICAL ATTENTION OR ADVICE, GIVE SEVERAL GLASSES  
OF WATER OR MILK  
WASH THOROUGHLY AFTER HANDLING  
Inhalation not a problem during normal conditions of use.

- - - - - Special Remarks - - - - -

ANIMAL TESTING DATA INDICATE THAT THE REPRODUCTIVE EFFECT (TESTICULAR ATROPY)  
FROM EXPOSURE TO ZINC DIALKYL DITHIOPHOSPHATE IS CAUSED BY STRESS FROM SEVERE  
SKIN IRRITATION AND WEIGHT LOSS  
For spills and leaks, treat as an oil spill. Dispose according to local,  
state, and federal environmental regulations.

The petroleum distillate oils are solvent-refined and are not considered  
to have skin carcinogenic potential by IARC.

- - - - - Toxicology Bulletins- - - - -

PETROLEUM LUBRICATING OILS (TB 101)

The chemical identification and properties for this material were provided by  
the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,  
Ford Motor Company  
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)