

Tox: 002115 Product: SILICONE GREASE  
FNHI : MIC43A ( 5.3 OZ TUBE)

000164

APPROVED to ACTIVE NAAO prod. spec ESF-MIC43-A.

- - - - - Chemical and Physical Properties - - - - -

This material is a PASTE under normal conditions.  
The Specific Gravity is 1.000 .  
The Boiling Point is >149 C.  
The Flash Point is +094 C (Tag. Open Cup).  
The results for pH are not applicable.

\* \* \* \* \* Toxicology Review \* \* \* \* \*

Tox: 002115 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 02/13/85

- - - - - Signal Word - - - - -

WARNING

- - - - - Hazards - - - - -

MAY CAUSE IRRITATION TO EYES

- - - - - Safe Handling and Storage - - - - -

AVOID CONTACT WITH EYES  
AVOID BREATHING FUME IF PRODUCT IS USED AT HIGH TEMPERATURES

- - - - - Protective Measures and Treatments - - - - -

IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK  
MEDICAL ADVICE  
WASH THOROUGHLY AFTER HANDLING

- - - - - Toxicology Bulletins - - - - -

PETROLEUM LUBRICATING OILS (TB 101)

The chemical identification and properties for this material were provided by  
the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,  
Ford Motor Company  
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)