

Tox: 036164 Product: WHITE PAINT (M1525A)  
FNHI : M1525ASE5 ( 13 OZ AEROSOL CAN)

Duplicate

APPROVED to ACTIVE NAAO prod. spec ESN-M1J101-A.

----- Chemical and Physical Properties -----

This material is a AEROSOL under normal conditions.  
The Specific Gravity is 0.800 .  
The Boiling Point is -039 to +198 C.  
The Flash Point is -039 C (Tag. Open Cup).  
The results for pH are not applicable.

\*\*\*\*\* Toxicology Review \*\*\*\*\*

Tox: 036164 Tox Status: C2 (COMPLETE TOX REVIEW) Last Revised: 01/12/88

----- Hazardous Ingredients (HAZCOM) -----

-- TLV --	CAS number	Chemical name
750ppm TWA	67-64-1 *	ACETONE
asphyxiant	74-98-6 *	PROPANE
100ppm TWA+N	75-09-2 *	METHYLENE CHLORIDE
100ppm TWA	108-88-3 *	TOLUENE
25ppm TWA (skin)	111-76-2 *	ETHYLENE GLYCOL MONOBUTYL ETHER
300ppm TWA	8030-30-6 *	PETROLEUM NAPHTHA
500ppm (OSHA) TWA	8032-32-4 +	MINERAL SPIRITS
10mg/m3 TWA	13463-67-7 *	TITANIUM DIOXIDE
500ppm (OSHA) TWA	64742-88-7 +	SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.

-- N=NTP

\* See chemical fact sheets (CFS) for additional details on these ingredients.

+ For more information on CAS 8032-32-4, see CFS for CAS 8030-30-6.

+ For more information on CAS 64742-88-7, see CFS for CAS 8030-30-6.

----- Signal Word -----

DANGER

----- Hazards -----

EXTREMELY FLAMMABLE  
HARMFUL BY INHALATION  
IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN  
CONTENTS UNDER PRESSURE  
MAY CAUSE LIVER/KIDNEY DAMAGE  
MAY BE HARMFUL OR TOXIC BY SKIN ABSORPTION  
CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. OVEREXPOSURE MAY CREATE  
CANCER RISK  
EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS, NAUSEA AND INCOORDINATION  
MAY CAUSE BLOOD DISORDERS (ANEMIA, ABNORMAL BLOOD PATTERNS)  
PROLONGED OR REPEATED CONTACT MAY DRY AND/OR DEFAT THE SKIN

Tox: 036164 Product: WHITE PAINT (M1525A)  
FNHI : M1525ASE5 ( 13 OZ AEROSOL CAN)

- - - - - Safe Handling and Storage - - - - -

DO NOT BREATHE GAS/FUMES/VAPOR/SPRAY  
KEEP IN A COOL, WELL-VENTILATED PLACE  
ELIMINATE ALL SOURCES OF IGNITION  
USE WITH ADEQUATE VENTILATION  
DO NOT PUNCTURE CONTAINER  
KEEP FROM HEAT, SPARKS, OR OPEN FLAME  
DO NOT GET IN EYES, ON SKIN OR CLOTHING  
DO NOT STORE, INCINERATE, OR HEAT ABOVE 120 DEGREES FAHRENHEIT

- - - - - Protective Measures and Treatments- - - - -

IMPERVIOUS GLOVES  
CHEMICAL GOGGLES  
IMPERVIOUS APRON  
VENTILATION (CONTACT INDUSTRIAL HYGIENE FOR SPECIFIC DETAILS)  
IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK  
MEDICAL ADVICE  
REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE  
FOR SKIN CONTACT, WASH IMMEDIATELY WITH SOAP AND WATER  
IF INHALATION OF MATERIAL IS EXCESSIVE (AIR CONCENTRATION IS GREATER THAN THE  
TLV OR HEALTH EFFECTS ARE NOTICED), REMOVE IMMEDIATELY TO FRESH AIR.

- - - - - Toxicology Bulletins- - - - -

GLYCOL ETHERS (TB 104)

The chemical identification and properties for this material were provided by  
the manufacturer. Health and safety information has been evaluated by:

Environmental & Occupational Toxicology, Occupational Health & Safety,  
Ford Motor Company  
900 Parklane Towers West, Dearborn, MI 48126

For emergency call: (313) 337-3182 -or- (313) 323-0045 (for 24 hour service)