

DATE OF PREPARATION **July 21, 1986**

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyer's risk. We make no guarantee that the health and safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling and use. No warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet.

Section I

MANUFACTURER'S NAME

H.B. Fuller Company

STREET ADDRESS

1200 Wolters Boulevard

CITY, STATE, AND ZIP CODE

Vadnais Heights, Minnesota 55110

EMERGENCY TELEPHONE NO.

612-481-3300

PRODUCT CLASS

Adhesive

MANUFACTURER'S CODE IDENTIFICATION

2115

TRADE NAME

NA

DOT PROPER SHIPPING NAME **Not a regulated material.**

Section II - HAZARDOUS INGREDIENTS

INGREDIENT/CAS NUMBER	PERCENTAGE RANGE	OSHA PEL	ACGIH TLV	LEL	VAPOR PRESSURE mm Hg. 20°C
This product does not contain regulated levels of hazardous ingredients as defined in 29 CFR 1910.1200.					

NA - NOT APPLICABLE

Section III - PHYSICAL DATA

NE - NOT ESTABLISHED

BOILING RANGE	>200°F	pH	7.0	PERCENT VOLATILE BY WEIGHT	62	WEIGHT PER GALLON	9.2 lbs.
---------------	--------	----	-----	----------------------------	----	-------------------	----------

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT

NA

EXTINGUISHING MEDIA

Liquid material - non-flammable. Use water spray, foam, dry chemical or carbon dioxide on dried product.

UNUSUAL FIRE AND EXPLOSION HAZARDS

There is the possibility of pressure build-up in closed containers when heated. Water spray may be used to cool the containers.

SPECIAL FIRE FIGHTING PROCEDURES

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

Section V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

ACUTE

Eye contact may cause irritation. Prolonged or repeated skin contact with liquid product may cause irritation.

CHRONIC

No anticipated chronic effects.

FIRST AID PROCEDURES

EYES: Flush immediately with large amounts of water for at least 15 minutes. Consult a physician if irritation persists. SKIN: Wash contact area with soap and water.

INHALATION: Remove to fresh air.

Section IV - REACTIVITY DATA

STABILITY

UNSTABLE

STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (Materials to avoid) Not established.

HAZARDOUS COMBUSTION PRODUCTS

Incomplete combustion can yield low molecular weight hydrocarbons and carbon monoxide.

HAZARDOUS POLYMERIZATION

MAY OCCUR

WILL NOT OCCUR

CONDITIONS TO AVOID

NA

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Contain and remove with inert absorbent. Keep spill out of sewers.

WASTE DISPOSAL METHOD This product does not meet the definition of hazardous waste under 40 CFR 261. Solidify and dispose of in an approved industrial landfill; consult your state or local authorities in the event more restrictive requirements apply.

Section VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION

Safety glasses.

SKIN PROTECTION

Rubber gloves recommended for prolonged or repeated contact with product. Remove and launder contaminated clothing before reuse.

RESPIRATORY PROTECTION

Not normally required.

VENTILATION

Standard industrial ventilation.

Section IX - ADDITIONAL INFORMATION

No additional information.