

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

00051

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Halsread Instant Bonding Adhesive

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

General Adhesive

Emergency Telephone Number

615/386-9955

Address (Number, Street, City, State, and ZIP Code)

6100 Centennial Blvd.

Telephone Number for Information

615/386-9955

Nashville, TN 37209

Date Prepared

10/28/85

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Toluene 108-88-3	200 ppm	100 ppm	STEL 150 ppm CEIL 200 ppm PEAK 500 ppm	
Acetone 67-64-1	1000 ppm	750 ppm	STEL 1000 ppm	
N-Hexane 110-54-3	500 ppm	50 ppm	N/A	
C6 Isomers of Hexane N/E	N/A	500 ppm	STEL 1000 ppm	

Section III - Physical/Chemical Characteristics

Boiling Point	131-135 °F	Specific Gravity (H ₂ O = 1)	.812
Vapor Pressure (mm Hg)	140 @20° C	Melting Point	N/A
Vapor Density (AIR = 1)	> 1.0	Evaporation Rate (Butyl Acetate = 1)	< 1

Solubility in Water: Partially. Acetone is soluble in water

Appearance and Odor

Yellow in color. Solvent odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	< OF TCC	Flammable Limits	LEL 1.2%	UEL 13.0%
---------------------------	----------	------------------	----------	-----------

Extinguishing Media

CO₂, Dry chemical, Foam, Halon

Special Fire Fighting Procedures

Self-contained breathing apparatus must be worn

Unusual Fire and Explosion Hazards

Cool drums with water spray to prevent pressure explosion.

Vapors may ignite explosively.

(Reproduce locally)