MSDS: B1043

ITEM: 5E355 - Adhesive ORDER: 0055131701

LP NUMBER: U837113616

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with	n the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - B1043

Associated Grainger Items 5E355

LOCTITE (R*)

MATERIAL SAFETY DATA SHEET

HENKEL TECHNOLOGIES

REVISION DATE: 05/02/2007

ISSUE DATE: 05/02/2007

- 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 495 SUPER BONDER (R*) INSTANT ADHESIVE

ITEM NO.: 49504

PRODUCT TYPE: CYANOACRYLATE

REGION: UNITED STATES

COMPANY ADDRESS: HENKEL CORPORATION 1001 TROUT BROOK CROSSING ROCKY HILL, CONNECTICUT 06067

CONTACT INFORMATION:

TELEPHONE: 860.571.5100 EMERGENCY TELEPHONE: 860.571.5100

INTERNET: WWW.LOCTITE.COM

- 2. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

ACCITH TIM

OSHA PET

OTHER

ETHYL CYANOACRYLATE 7085-85-0

60-100

0.2 PPM TWA

NONE

- 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

PHYSICAL STATE: LIOUID

COLOR: CLEAR COLORLESS TO STRAW

ODOR: SHARP, IRRITATING

HMIS:

HEALITH 2
FLAWMABILITY 2
PHYSICAL HAZARD 1
PERSONAL PROTECTION SEE SECTION 8

MANUTURY:
BONDS SKIN IN SECONDS.
MAY CAUSE EYE AND RESPIRATORY IRRITATION.
COMBUSTIBLE LIQUID AND VAPOR.

RELEVANT ROUTES OF EXPOSURE: SKIN, INHALATION, EYES

POTENTIAL HEALTH EFFECTS:

INDIANATION:
EXPOSURE TO VAPORS ABOVE THE ESTABLISHED EXPOSURE LIMIT RESULTS IN RESPIRATORY IRRITATION WHICH MAY LEAD TO DIFFICULTY IN BREATHING AND TIGHTNESS IN THE CHEST.

SKIN CONTACT:
BONDS SKIN IN SECONDS. MAY CAUSE SKIN IRRITATION. CYANOACRYLATES HAVE BEEN
REPORTED TO CAUSE ALLERGIC REACTION BUT DUE TO RAPID POLYMERIZATION AT THE
SKIN SURFACE, AN ALLERGIC RESPONSE IS RARE.

CYANOACRYLATES GENERATE HEAT ON SOLIDIFICATION. IN RARE CIRCUMSTANCES A LARGE DROP WILL BURN THE SKIN. CURED ADHESIVE DOES NOT PRESENT A HEALTH HAZARD EVEN IF BONDED TO THE SKIN.

EYE CONTACT:

IRRITATING TO EYES, CAUSES EXCESSIVE TEARING, EYELIDS MAY BOND.

INGESTION:

NOT EXPECTED TO BE HARMFUL BY INGESTION. RAPIDLY POLYMERIZES (SOLIDIFIES) AND BONDS IN MOUTH. IT IS ALMOST IMPOSSIBLE TO SWALLOW.

EXISTING CONDITIONS AGGRAVATED BY EXPOSURE: EYE, SKIN, AND RESPIRATORY DISORDERS.

SEE SECTION 11 FOR ADDITIONAL TOXICOLOGICAL INFORMATION.

--- 4. FIRST AID MEASURES -

INHALATION: REMOVE TO FRESH AIR. IF DISCOMFORT PERSISTS SEEK MEDICAL ATTENTION.

SAIN CONTACT:

DO NOT PULL BONDED SKIN APART. SOAK IN WARM SOAPY WATER. GENTLY PEEL APART
USING A BLUNT INSTRUMENT. IF SKIN IS BURNED DUE TO THE RAPID GENERATION OF
HEAT BY A LARGE DROP, SEEK MEDICAL ATTENTION. IF LIPS ARE BONDED, APPLY
WARM WATER TO THE LIPS AND ENCOURAGE WEITING AND PRESSURE FROM SALIVA IN
MOUTH. PEEL OR ROLL LIPS APART. DO NOT PULL LIPS APART WITH DIRECT OPPOSING
FORCE.

EYE CONTACT:
IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL
ATTENTION. IF EYELIDS ARE BONDED CLOSED, RELEASE EYELASHES WITH WARM WATER
BY COVERING WITH A WEIT PAD. DO NOT FORCE EYE OPEN. CYANOACRYLATE WILL BOND
TO EYE PROTEIN AND WILL CAUSE A LACHRYMATORY EFFECT WHICH WILL BEILD TO
DEBOND THE ADHESIVE. KEEP EYE COVERED UNTIL DEBONDING IS COMPLETE, USUALLY
WITHIN 1-3 DAYS. MEDICAL ATTENTION SHOULD BE SOUGHT IN CASE SOLID PARTICLES
OF POLYMPRIZED CYANOACRYLATE TRAPPED BEHIND THE EYELID CAUSED ABRASIVE
DAMAGE.

INGESTION:
ENSURE BREATHING PASSAGES ARE NOT OBSTRUCTED. THE PRODUCT WILL POLYMERIZE
RAPIDLY AND BOND TO THE MOUTH MAKING IT ALMOST IMPOSSIBLE TO SWALLOW.
SALIVA WILL SEPARATE ANY SOLIDIFIED PRODUCT IN SEVERAL HOURS. PREVENT THE
PATIENT FROM SWALLOWING ANY SEPARATED MASS.

NOTES TO PHYSICIAN:

NUMES TO PHYSICIAN: SURGERY IS NOT NECESSARY TO SEPARATE ACCIDENTALLY BONDED TISSUES. EXPERIENCE HAS SHOWN THAT BONDED TISSUES ARE BEST TREATED BY PASSIVE, NON-SURGICAL FIRST AID. IF RAPID CURING HAS CAUSED THERMAL BURNS THEY SHOULD BE TREATED SYMPTOMATICALLY AFTER ADHESIVE IS REMOVED.

- 5. FIRE-FIGHTING MEASURES -

FLASH POINT: 80 DEG. C (176 DEG. F) TO 93.4 DEG. C (200 DEG. F) TAGLIABUE CLOSED CUP

AUTOIGNITION TEMPERATURE: 485 DEG. C (905 DEG. F)

FLAMMABLE/EXPLOSIVE LIMITS-LOWER %: NOT DETERMINED FLAMMABLE/EXPLOSIVE LIMITS-UPPER %: NOT DETERMINED

EXTINGUISHING MEDIA: WATER SPRAY, DRY POWDER, FOAM, CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD WEAR POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS (SCBA)

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE

HAZARDOUS COMBUSTION PRODUCTS: TRACE AMOUNIS OF TOXIC AND/OR IRRITATING FUMES MAY BE RELEASED AND THE USE OF BREATHING APPARATUS IS RECOMMENDED.

- 6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS: VENTILATE AREA. PREVENT PRODUCT FROM ENTERING THE DRAINS.

CLEAN-UP METHODS: DO NOT USE CLOTHS FOR MOPPING UP. FLOOD WITH WATER TO COMPLETE POLYMERIZATION AND SCRAPE OFF THE FLOOR. CURED MATERIAL CAN BE DISPOSED OF AS NON-HAZARDOUS WASTE.

- 7. HANDLING AND STORAGE -

HANDLING: AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING VAPOR AND MIST. WASH THOROUGHLY AFTER HANDLING. AVOID COMFACT WITH FABRIC OR PAPER GOODS. CONTACT WITH THESE MATERIALS MAY CAUSE RAPID POLYMERIZATION WHICH CAN GENERATE SMOKE AND STRONG IRRITATING VAPORS, AND CAUSE THERMAL BURNS.

STORAGE:

KEEP IN A COOL, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP CONTAINER TIGHTLY CLOSED UNTIL READY FOR USE.

INCOMPATIBLE PRODUCTS: NO SPECIAL RESTRICTIONS ON STORAGE WITH OTHER PRODUCTS.

FOR INFORMATION ON PRODUCT SHELF LIFE CONTACT HENKEL CUSTOMER SERVICE AT (800) 243-4874.

- 8. EXPOSURE CONTROLS / PERSONAL PROTECTION -

ENGINEERING CONTROLS:
USE POSITIVE DOWN-DRAFT EXHAUST VENTILATION IF GENERAL VENTILATION IS
INSUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW ESTABLISHED EXPOSURE

RESPIRATORY PROTECTION:
USE NIOSH APPROVED RESPIRATOR IF THERE IS POTENTIAL TO EXCEED EXPOSURE
LIMIT(S). OBSERVE OSHA REGULATIONS FOR RESPIRATORY USE (29 CFR 1910.134).

SKIN PROTECTION:
USE NITRILE GLOVES AND APRONS AS NECESSARY TO PREVENT CONTACT. DO NOT USE
PVC, NYLON OR COTTON.

EYE/FACE PROTECTION: CHEMICAL SPLASH GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

SEE SECTION 2 FOR EXPOSURE LIMITS.

- 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: LIQUID

COLOR: CLEAR COLORLESS TO STRAW

ODOR: SHARP, IRRITATING

ODOR THRESHOLD: 1-2 PPM

VAPOR PRESSURE: LESS THAN 0.2 MMHG

pH: NOT APPLICABLE

BOILING POINT/RANGE: GREATER THAN 149 DEG. C (300 DEG. F) MELTING POINT/RANGE: NOT DETERMINED SPECIFIC GRAVITY: 1.1 AT 23.9 DEG. C (75 DEG. F) VAPOR DENSITY: APPROXIMATELY 3 EVAPORATION RATE: NOT AVAILABLE SOLUBILITY IN WATER: POLYMERIZES IN PRESENCE OF WATER PARTITION COEFFICIENT (n-OCTANOL/WATER): NOT APPLICABLE VOC CONTENT: LESS THAN 2%; 20 G/L (CALIFORNIA SCAQMD METHOD 316B) (ESTIMATED) - 10. STABILITY AND REACTIVITY STABILITY: STABLE UNDER RECOMMENDED STORAGE CONDITIONS HAZARDOUS POLYMERIZATION: RAPID EXOTHERMIC POLYMERIZATION WILL OCCUR IN THE PRESENCE OF WATER, AMINES, ALKALIS AND ALCOHOLS. HAZARDOUS DECOMPOSITION PRODUCTS: NONE INCOMPATIBILITY: WATER, AMINES, ALKALIS AND ALCOHOLS. CONDITIONS TO AVOID: SPONTANEOUS POLYMERIZATION - 11. TOXICOLOGICAL INFORMATION PRODUCT TOXICITY DATA:
ACUTE ORAL LD50: >5000 MG/KG (RAT) (ESTIMATED).
ACUTE DERMAL LD50: >2000 MG/KG (RABBIT) (ESTIMATED). CARCINGGEN STATUS: NTP CARCTNOSEN TARC CARCTNOSEN OSHA CARCINOSEN HAZARDOUS COMPONENTS ETHYL CYANOACRYLATE 7085-85-0 LITERATURE REFERENCED TARGET ORGAN & OTHER HEALTH EFFECTS: HEALTH EFFECTS/TARGET ORGANS HAZARDOUS COMPONENTS ETHYL CYANOACRYLATE 7085-85-0 ALLERGEN, IRRITANT, RESPIRATORY - 12. ECOLOGICAL INFORMATION ECOLOGICAL INFORMATION: NOT KNOWN - 13. DISPOSAL CONSIDERATIONS INFORMATION PROVIDED IS FOR UNUSED PRODUCT ONLY. RECOMMENDED METHOD OF DISPOSAL:
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER: NOT A RCRA HAZARDOUS WASTE. - 14. TRANSPORT INFORMATION U.S. DEPARIMENT OF TRANSPORTATION GROUND (49 CFR):
PROPER SHIPPING NAME: COMBUSTIBLE LIQUIDS, N.O.S. (CYANOACRYLATE ESTER)
HAZARD CLASS OR DIVISION: COMBUSTIBLE LIQUID
IDENTIFICATION NUMBER: NA 1993
PACKING GROUP: NONE
EXCEPTIONS: (NOT MORE THAN 450 LITERS) UNRESTRICTED
MARINE POLLUTANT: NONE INTERNATIONAL AIR TRANSPORTATION (ICAO/TATA): PROPER SHIPPING NAME: AVIATION REGULATED LIQUIDS, N.O.S (CYANOACRYLATE ESTER) HAZARD CLASS OR DIVISION: 9 IDENTIFICATION NUMBER: UN 3334 PACKING GROUP: NONE EXCEPTIONS: (NOT MORE THAN 500 ML) UNRESTRICTED WATER TRANSPORTATION (IMO/IMDG):
PROPER SHIPPING NAME: UNRESTRICTED
HAZARD CLASS OR DIVISION: NONE
IDENTIFICATION NUMBER: NONE
PACKING GROUP: NONE
MARINE POLLUTANT: NONE

- 15. REGULATORY INFORMATION .

UNITED STATES REGULATORY INFORMATION:

TSCA 8 (B) INVENTORY STATUS: ALL COMPONENTS ARE LISTED OR ARE EXEMPT FROM LISTING ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY.

TSCA 12 (B) EXPORT NOTIFICATION: NONE.

CERCLA/SARA SECTION 302 EHS: NONE ABOVE REPORTING DE MINIMUS.

CERCLA/SARA SECTION 311/312: IMMEDIATE HEALTH HAZARD, DELAYED HEALTH HAZARD, FIRE, REACTIVE

CERCLA/SARA 313: NONE ABOVE REPORTING DE MINIMUS.

CALIFORNIA PROPOSITION 65: NO CALIFORNIA PROPOSITION 65 LISTED CHEMICALS ARE KNOWN TO BE PRESENT.

CANADA REGULATORY INFORMATION:

CEPA DSL/NDSL STATUS: ALL COMPONENTS ARE LISTED ON OR ARE EXEMPT FROM LISTING ON THE DOMESTIC SUBSTANCES LIST.

WHMIS HAZARD CLASS: B.3, D.2.B

10	6. (OTHER	INF	ORMATION	 		
					 	2017/17/17	TOTOLOGICA

THIS MATERIAL SAFETY DATA SHEET CONTAINS CHANGES FROM THE PREVIOUS VERS IN SECTIONS: 15

PREPARED BY: C.J. MICHAELS, MANAGER, REGULATORY AFFAIRS

DISCLAIMER:
THE DATA CONTAINED HEREIN ARE FURNISHED FOR INFORMATION ONLY AND ARE
BELLEVED TO BE RELIABLE. HOWEVER, HENCEL CORPORATION DOES NOT ASSUME
RESPONSIBILITY FOR ANY RESULTS OBTAINED BY PERSONS OVER WHOSE METHODS
HENKEL CORPORATION HAS NO CONTROL. IT IS THE USER'S RESPONSIBILITY TO
DETERMINE THE SULTABILITY OF HENKEL'S PRODUCTS OR ANY PRODUCTION METHODS
MENTIONED HEREIN FOR A PARTICULAR PURPOSE, AND TO ADOPT SUCH PRECAUTIONS AS
MAY BE ADVISABLE FOR THE PROTECTION OF PROPERTY AND PERSONS ACAINST ANY
HAZARDS THAT MAY BE INVOLVED IN THE HANDLING AND USE OF ANY OF HEAKEL
CORPORATION'S PRODUCTS. IN LIGHT OF THE PORECOING, HENKEL CORPORATION
SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE,
ARISING FROM SALE OR USE OF HENKEL CORPORATION'S PRODUCTS. HENKEL
CORPORATION FURTHER DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR
INCIDENTAL DAWAGES OF ANY KIND, INCLUDING LOST PROFITS.