

✓ NOV 11 '94 01:45PM HUNT COST SERVICE

13202. all codes
EXCEPT
- 1003
- 1013
- 1014

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration - 1013
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List) **FOAMBOARD**

Section I

Manufacturer's Name HUNT BIENFANG PRODUCTS	Emergency Telephone Number (704) 872-9511
Address (Number, Street, City, State, and ZIP Code) 2020 WEST FRONT STREET	Telephone Number for Information (704) 872-9511
STATESVILLE, NC 28677	Date Prepared May 26, 1993
	Signature of Preparer (optional) ^ <i>Dud Martin</i>

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Isopentane 78-78-4	NE	NE		
n-Pentane 109-66-0	1000 ppm	600 ppm		
Polystyrene 9003-53-6	NA	NA		
n-Butane 106-97-8	800 ppm	800 ppm		
2,2-Dimethylpropane 463-82-1	NE	NE		
Pentenes Various	NE	NE		
Talc 14807-96-6	NE	NE		

V 2260

Section III — Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	< 1
Vapor Pressure (mm Hg.)	NA	Melting Point	106°C
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water Insoluble			
Appearance and Odor Solid, Odorless			

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) NA	Flammable Limits	LEL NA	UEL NA
---------------------------------	------------------	--------	--------

Extinguishing Media
Water Spray

Special Fire Fighting Procedures
Treat as combustible solid fire. Firefighters should use self-contained breathing apparatus.

Unusual Fire and Explosion Hazards
Polystyrene emits styrene, carbon monoxide, and other hydrocarbons when burning.

