

MATERIAL SAFETY DATA SHEETS
FOR COATINGS, RESINS AND RELATED MATERIALS
(APPROVED BY U.S. DEPARTMENT OF LABOR)

52163-12

SECTION I

(PAGE

Manufacturers Name: ILLINOIS BRONZE
Street Address: 26300 FARGO AVE
City, State, and Zip Code: BEDFORD HTS OH
Product Class (AEROSOL) COATINGS
Trade Name: I0500 CRYSTAL CLEAR GLAZE
Emergency Phone No: 216/292-7400
Code Identification: I0500
Rev. Date: 05/08/91
Date: 11/12/91
Lab No.: 53612

SECTION II - HAZARDOUS INGREDIENTS

Table with columns: INGREDIENT, PERCENT, OSHA PEL, TLV PPM, TLV MG/M3, LEL, CAS NUMBER. Rows include XYLENE, ETHYL BENZENE, TOLUENE, ISOBUTANE, PROPANE.

AEROSOL - CONTENTS UNDER PRESSURE 55 +/- 5 PSIG

Carcinogenicity: THIS PRODUCT IS NOT CONSIDERED TO BE A CARCINOGEN BY THE NATIONAL TOXICOLOGY PROGRAM, THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER, THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION, OR NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY & HEALTH.

SARA: These ingredients are subject to SARA TITLE III Section 313 reporting for Superfund Amendments and Reauthorization Act of 1986 and CFR 40 part 372.

SARA: Aerosol products are subject to SARA TITLE III Section 312 reporting for Superfund Amendments and Reauthorization Act of 1986 and CFR 40 part 372.

Pursuant to Proposition 65: CERTAIN RAW MATERIALS USED IN MAKING THIS PRODUCT MAY CONTAIN SMALL AMOUNTS OF MATERIALS AS IMPURITIES WHICH ARE REGULATED BY PROPOSITION 65. SEE SECTION IX.

SECTION III - PHYSICAL DATA

Boiling Range: PROPELLANT BELOW 0 O F Vapor Density: HEAVIER THAN AIR
EVAPORATION RATE FASTER THAN ETHER
Percent Volatile By Weight: 86
Weight Per Gallon: NOT APPLICABLE
Specific Gravity: NOT APPLICABLE
Appearance & Odor: COATINGS
PH: NOT APPLICABLE
Vapor Pressure: NOT APPLICABLE
Solubility in Water: NOT APPLICABLE
Melting Point: NOT APPLICABLE

Customer No: 06262 Name: ILLINOIS BRONZE Lab No.: 53612 (PAGE 2)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

DOT Category: CONSUMER COMMODITY Flash Point: PROPELLANT BELOW 20 F LEL: SEE SECTION II
ORM-D (T.O.C.)

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM.

Unusual Fire and Explosion Hazards: DO NOT SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING.

Special Fire Fighting Procedures: WATER MAY BE INEFFECTIVE - WATER MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: (SEE SECTION II HAZARDOUS INGREDIENTS)

Effects of Overexposure: IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC. IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. OVER-EXPOSURE MAY RESULT IN LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. CONTAINS PETROLEUM DISTILLATES - HARMFUL OR FATAL IF SWALLOWED

Chronic: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE, ALSO KIDNEY AND LIVER DAMAGE.

Medical Conditions Prone to Aggravation by Exposure: NONE ESTABLISHED.

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Emergency and First Aid Procedures: Breathing: REMOVE PATIENT TO FRESH AIR. Eyes: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. Skin: WASH WITH SOAP AND WATER. Swallowing: CALL PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

SECTION VI - REACTIVITY DATA

Stability: STABLE Conditions to Avoid: DO NOT STORE ABOVE 120 F
Incompatibility (NONE)
Hazardous Decomposition Products By open flame: CARBON MONOXIDE, CARBON DIOXIDE
Hazardous Polymerization: WILL NOT OCCUR

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: REMOVE ALL SOURCES OF IGNITION, VENTILATE AVOID BREATHING VAPORS (SEE SECTION X) AND REMOVE WITH INERT ABSORBENT

Waste disposal method: DO NOT INCINERATE - DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Order No: 06262 Name: ILLINOIS BRONZE

Lab No.: 53612 (PAGE 3

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: AVOID BREATHING OF VAPOR OR SPRAY MIST (SEE SECTION X

IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION II.

WHEN SANDING OR ABRADING THE DRIED FILM, WEAR A DUST/MIST RESPIRATOR APPROVED BY NIOSH/MSHA FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT, OR THE ABRASIVE.

THE APPLICABLE LIMITS FOR NUISANCE DUSTS ARE ACGIH TLV 10 mg/m3 (TOTAL DUST), OSHA PEL 15 mg/m3 (TOTAL DUST), 5 mg/m3 RESPIRABLE FRACTION).

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF ALL HAZARDOUS INGREDIENTS IN SECTION II BELOW ACCEPTABLE LIMIT, AND LEL IN SECTION II BELOW STATED LIMIT.

Protective Gloves: FOR PROLONGED OR REPEATED CONTACT, WEAR GLOVES WHICH ARE RECOMMENDED BY GLOVE SUPPLIER FOR PROTECTION AGAINST MATERIALS IN SECTION II.

Eye Protection: FOR PROLONGED USE IN CLOSE QUARTERS RECOMMEND SAFETY GLASSES WITH UNPERFORATED SIDESHIELDS.

Protective Equipment:

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing:

DO NOT STORE ABOVE 120 F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING.

Precautions: KEEP AWAY FROM CHILDREN. DO NOT PUNCTURE OR INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

Warning to Proposition 65: PROPOSITION 65 APPLIES TO A LIST OF CHEMICALS NAMED BY THE GOVERNOR OF CALIFORNIA AS CARCINOGENS OR REPRODUCTIVE TOXINS. WARNING REQUIREMENTS FOR SPECIFIC CHEMICALS TAKE EFFECT ONE YEAR AFTER THEY ARE ADDED TO THE GOVERNOR'S LIST. OTHER CHEMICALS ALREADY ADDED TO THE GOVERNOR'S LIST WILL BE REGULATED LATER UNDER PROPOSITION 65.

SECTION X HAZARDOUS MATERIAL IDENTIFICATION

COMMUNICATION OF PHYSICAL PROPERTY, HEALTH, AND SAFETY INFORMATION IS A KEY FACTOR IN OUR PRODUCT SAFETY PROGRAM. WITH THIS INFORMATION YOU CAN BETTER FULFILL YOUR OBLIGATION TO EDUCATE EXPOSED PERSONNEL IN THE PROPER HANDLING TECHNIQUES REQUIRED TO MAINTAIN SAFETY IN THE WORKPLACE. LISTED IN THIS SECTION IS NFPA-HMIS CLASSIFICATION FOR THIS PRODUCT.

HMIS. CLASSIFICATION CODE

Health: 2 MODERATE HAZARD
Flammability: 4 SEVERE HAZARD
Reactivity: 1 SLIGHT HAZARD
Personal protection: D FACE SHIELD, GLOVES, APRON

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.

Post-It brand fax transmittal memo 7671 # of pages 4
To LISA ROBERTS From MIKE WELCH
Co. DICK BLICK Co. SPEC. DIV.
Dept. Phone #
Fax # Fax #