

for All Inks & Pigments.

MATERIAL SAFETY DATA SHEET

INMONT

DATE: 5-26-86

J.R. Heuser

Color Systems - Textile Industries

Pigment Printing

Section I

MANUFACTURER'S NAME INMONT CORPORATION		EMERGENCY PHONE NO. 704-588-2020 or 201-365-3512
STREET ADDRESS (No., City, State, Zip) 1701 Westinghouse Blvd., Charlotte, NC 28217		Chemtrec. 1-800-424-9300
PRODUCT CLASS Aqueous Textile Ink	TRADE NAME <i>PRO 96 Textile Ink</i>	MANUFACTURERS CODE 05-55104

Section II - HAZARDOUS INGREDIENTS

PRO
Chemical & Dye
P.O. BOX 14
SOMERSET, MASS. 02726
TEL. (617) 676-3838
Inc.

	CAS NO.	AMOUNT	ACGIH TLV-TWA
Ammonia	7664-41-7	Less than 1.0%	25 ppm
Amino methyl propanol	124-68-5	Less than 1.0%	None

NJ MA RI

THE INFORMATION CONTAINED HEREIN IS BASED ON TECHNICAL DATA WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, SINCE THE CONDITIONS UNDER WHICH THIS INFORMATION MAY BE APPLIED ARE BEYOND OUR CONTROL, WE CAN ASSUME NO LIABILITY FOR RESULTS OF ITS APPLICATION. THIS INFORMATION SHOULD BE USED ONLY BY PERSONS HAVING SUFFICIENT TECHNICAL SKILL TO MAKE INFORMED JUDGMENTS REGARDING ITS APPLICATION.

Section III - PHYSICAL DATA

BOILING RANGE	F° 212	TYPE OF ODOR		Slight Ammonia
VAPOR DENSITY	HEAVIER () LIGHTER (X) vs. AIR	EVAPORATION RATE vs ETHER	FASTER	
			SLOWER	XX
LIQUID DENSITY	HEAVIER (XX) LIGHTER () vs WATER	PERCENT VOLATILE WT		79
APPEARANCE	Brown Paste			

Section IV - FIRE & EXPLOSION DATA

FLASH POINT CATEGORY (NFPA)	NA	LOWEST FLASH POINT	NA	L E L	NA
EXTINGUISHING MEDIA No fire hazard					
SPECIAL FIRE FIGHTING PROCEDURE None					
UNUSUAL FIRE & EXPLOSION HAZARDS None					
NA - Not Applicable.					

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

See Section II.

EFFECTS OF OVEREXPOSURE: Vapors may be irritating to the eyes and nose. Prolonged or repeated skin contact may cause skin irritation. Direct eye contact will cause eye irritation.

EMERGENCY FIRST AID: Inhalation: Remove individual to fresh air. Eye and Skin Contact: Immediately flush eyes with water for 15 minutes; if irritation persists, get medical attention. Wash skin thoroughly with soap and water; remove soiled clothing and wash before reuse. Ingestion: Call a physician immediately.

Section VI — REACTIVITY DATA

PRODUCT STABILITY

STABLE

UNSTABLE

XXX

CONDITIONS TO AVOID

None

Section VII — SPILL OR LEAK PROCEDURES

PROCEDURE WHEN MATERIAL SPILLED OR RELEASED

Dike and contain spill and absorb with inert materials (dry sand, sawdust, etc.). Transfer to containers for disposal, keep spill out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHOD

Sanitary landfill in accordance with local, state and federal regulations.

Section VIII — SPECIAL PROTECTION INFORMATION

VENTILATION

Product should be used with adequate ventilation.

PROTECTIVE EQUIPMENT RESPIRATORY EYE ETC

Rubber gloves and safety glasses should be used when skin contact or splashing may occur.

Section IX - SPECIAL PRECAUTIONS

Storage & Handling

Keep containers closed when not in use. Do not freeze. Store between 40-100° F.