

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid NONE (NON-REACTIVE)
	Stable	X	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid POOR VENTILATION CAN CAUSE EXCESSIVE INHALATION OF SOLVENT VAPORS.
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry:	Inhalation? YES	Skin? YES	Ingestion? N/A
--------------------	---------------------------	---------------------	--------------------------

Health Hazards (Acute and Chronic)

INHALATION OF SOLVENT IN A POORLY VENTILATED AREA CAN CAUSE DIZZINESS AND HEADACHES. EXCESSIVE SKIN CONTACT CAN LEAD TO DRY AND IRRITATED SKIN POSSIBLY CAUSING DERMATITIS.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
------------------	------	------------------	-----------------

ASBESTOS - WHEN COMPOUNDED IN AN ASPHALTIC BASE IS ENCAPSULATED AND CANNOT BE AIRBORNE AND THEREFORE IS NOT A CARCINOGENIC HAZARD.

Signs and Symptoms of Exposure

Medical Conditions

Generally Aggravated by Exposure **N/A**

Emergency and First Aid Procedures

REMOVE TO FRESH AIR AND CALL A PHYSICIAN. IF SPLASHED IN EYES FLUSH WITH COLD WATER UNTIL FIRST AID CAN BE ADMINISTERED.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

POUR ABSORBENT SAND OR SAWDUST OVER SPILL AREA**AND SHOVEL EXCESS INTO CONTAINERS.**

Waste Disposal Method

DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Precautions to Be Taken in Handling and Storing

DO NOT STORE AT TEMPERATURES ABOVE 120°F.

Other Precautions

Section VIII — Control Measures

Respiratory Protection (Specify Type)

AREA SHOULD BE WELL VENTILATED. RESPIRATORS CAN BE USED.

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves

NORMAL WORK GLOVES

Eye Protection

SAFETY GLASSES OR GOGGLES

Other Protective Clothing or Equipment

Work/Hygiene Practices