

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

#255183
#255196
Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET 600700

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME KLEER-FLO Company		EMERGENCY TELEPHONE NO. 612 941-6710
ADDRESS (Number, Street, City, State, and ZIP Code) 6970 Shady Oak Rd., Eden Prairie, MN 55344		
CHEMICAL NAME AND SYNONYMS N/A	TRADE NAME AND SYNONYMS DEGREASOL	
CHEMICAL FAMILY Aliphatic petroleum hydrocarbons	FORMULA N/A	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS		N/A	BASE METAL		
CATALYST		N/A	ALLOYS		
VEHICLE		N/A	METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	IBP	325	SPECIFIC GRAVITY (H ₂ O=1)	0.79 (0.782)
VAPOR PRESSURE (mm Hg.)	less than	5	PERCENT VOLATILE BY VOLUME (%)	99.9
VAPOR DENSITY (AIR=1)		5	EVAPORATION RATE	butyl acetate = 1 0.1
SOLUBILITY IN WATER		slight		
APPEARANCE AND ODOR	Cherry red color, mild hydrocarbon odor			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	124°F TOC	FLAMMABLE LIMITS	Lel	Uel
			0.8%	6.5%
EXTINGUISHING MEDIA	Foam, dry chemical, CO ₂			
SPECIAL FIRE FIGHTING PROCEDURES	Use self-contained apparatus for enclosed areas. Cool exposed containers with water. Consult local fire marshal.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Combustible--Do not store or mix with strong oxidants.			