1981

MAYCO MSDS SHEET #3 Active Products

9721765 C.D. 9218089 V, MA, AB

Prepared: September 22, 2003

Supersedes: All previous

MAYCO COLORS division of Coloramics, LLC Manufacturer:

> 4077 Weaver Court South Hilliard, Ohio 43026 United States of America

MAR 7 2006

Facilities Management TEALTH AND SAFET

EC	 Local Phone
Australia	 Local Phone

IN CASE OF EMERGENCY PLEASE CONTACT YOUR LOCAL POISON CONTROL

CENTER

Ceramic Glaze and underglazes and Miscellaneous.

Astro Gem Glazes

Distributor USA

AS-510, 512, 513, 515, 516, 518, 519, 520, 521, 523, 524, 527,

528, 531, 532

534, 535, 539, 541, 545, 547, 548, 551

One Stroke Colors

OS-1, 2, 3, 4, 6, 8, 9, 17, 18, 21, 26, 29, 32, 34, 36, 38, 41, 43, 44, 45,

Local Phone

46, 47

48, 52, 54, 58, 59, 60, 61, 62, 63, 65, 66, 104, 105, 132, 136, 137, 138,

140

142, 143, 144, 147, 153

Underglazes

UG-1, 2, 3, 7, 8, 10, 11, 12, 15, 17, 18, 19, 21, 22, 24, 25, 26, 27, 30,

31, 32, 33,

34, 35, 37, 38, 39, 41, 42, 43, 45, 46, 50, 51, 52, 53, 56, 57, 58, 67, 68, 69, 70, 71, 72, 73, 75, 78, 80, 81, 82, 83, 84, 85, 86, 87, 89, 90, 91, 92, 93, 94, 95, 97, 98, 100, 103, 104, 105, 108, 109, 110, 111, 116, 119, 125, 127, 128, 130, 131, 136, 141, 142, 144, 145, 146, 150, 178, 180,

181, 189, 191, 192, 194, 195, 196, 198, 201, 202

Pottery Coats

PC-501 through PC-505 Pottery Coat Stuccos PS-551 through PS-555

PC-601 through PC-604

Pottery Cascades Miscellaneous

AC-306, AC-308

Series 2000 Glazes

*S-2101-2168

S-2560, 2561, 2562, 2564, 2565, 2566, 2574, 2577, 2578, 2579, 2580,

2581, 2585

S-2587, 2588, 2589, 2590, 2591, 2592, 2593

*Excluding: S-2104, 2105, 2122, 2130, 2168, and 2586

Series 2000 Mattes*

S-2200, 2201, 2208, 2209, 2218, 2223, 2226, 2227, 2228, 2229, 2230,

2231, 208, S-2232, 2233, 2234, 2235, 2236, 2237, 2239, *Excluding

S-2224, S-2225,

Stroke and Coat Series

All Stroke and Coat (SC's) except SC-23, 58, 59, 62, 24, 20, 4,

67, 68, 50,

SP-204, SD-304, SD-323 all SP series except SP-204

Specstone Glazes

S-2167, 2169, 2401, 2402, 2408, 2421, 2422, 2423, 2424,

2425, 2427

Crystalites

S-2701 through S-2718 & S-2719, S-2722, S-2723

Roll a Coat

SC-210

Elements

EL-101 through EL-118

Chunky Elements

EL-201 through EL-209 CC-500 through CC-507

Classic Crackles

Clear Glaze

S-2000, S-2101, SC-209

Stoneware Like Glaze SLG-02, 06, 17

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS			ACGIH PFL	OSHA
		TLV		
Alumina Silicate	1332-58-7		NA	NA
Bentonite / Clay	1302-78-9		NA	NA
Water	7732-18-5	NA	NA	

SECTION 3 HAZARDS IDENTIFICATION

Crystalline Silica may be present.

(OSHA PEL .1mg/m3)

Route(s) of Entry: Ingestion, absorption through the skin is negligible.

Inhalation only if sprayed.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of

TLV, over an extended period of time may result in injury to the lungs.

SECTION 4 FIRST AID MEASURES

If Inhaled:

Remove from exposure

If on skin:

Wash skin with soap and water

If in eves:

Flush eyes with large quantities of water for at least 15 minutes. If

irritation

persists after washing, contact a physician.

If swallowed: Dilute by drinking water

SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used): N/A

LEL: N/A

UEL: N/A Flammable Limits: N/A

Extinguishing Media: None required, not combustible.

Special Fire Fighting Procedures: None Unusual Fire and Explosion Hazards: None

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal. Testing of the waste may be required to determine status under the hazardous waste regulations.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AND USE

Engineer Control - None

Work practices- Store away from feed and food. Do not smoke, eat or drink while handling.

Procedure / equipment- None

Procedure for leaks or spills: Uncontaminated material may be recovered and reused. If contaminated, scoop, vacuum, or wash into a receptacle for disposal. Waste Disposal Method: Follow Federal or State and Local regulations for disposal.

SECTION 8 EXPOSURE CONTROLLS / PERSONAL PROTECTION

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The Work/Hygienic Practices apply regardless of the method of application. Respiratory Protection (Specify Type): Use a NIOSH approved dust and/or fume respirator as necessary.

Ventilation: Local Exhaust - for spraying

Protective Gloves: N/A Eye Protection: for spraying

Other Protective Clothing or Equipment: Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons. Work/Hygienic Practices: Food, beverages, and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking, smoking, or applying cosmetics.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Various colors

Odor and odor threshold: Negligible

PH: Not available Boiling Point: None

Vapor Pressure: NA Vapor Density: NA

Melting Point: above 1000oF Specific Gravity (H2O=1): 1.4 to 1.6

Flammable Limits: None Explosive limits: None Partition Coefficient: None Oxidizing Properties: None Solubility in Water: Negligible Percent Volatile by Volume: None

Evaporation Rate: None Freezing point: NA Flash Point: None

Auto ignition temperature: None

SECTION 10 STABILITY AND REACTIVITY DATA

Incompatibility (material to avoid): Avoid fumes from firing by venting kiln area.

Stability: Stable (conditions to avoid: N/A)

Hazardous Decomposition or Byproducts: Not available

Hazardous Polymerization: Will not occur

Conditions to avoid: Furnes from firing in kiln. Inhalation of spray.

SECTION 11 TOXICOLOGICAL INFORMATION

Hazard to Human: None during normal use. Harmful if inhaled or swallowed. DO NOT SPRAY APPLY

If glaze is spray applied the following warnings apply: Warning: Contains Quartz.

- 1. Possible cancer agent based on tests with laboratory animals.
- 2. Exposure may cause lung damage.
- 3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to the State of California to cause cancer.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of

TLV, over an extended period of time may result in injury to the lungs. Additional information: Frits are fused silica glass like substances. The

bioavailability may

be limited because of the physical nature of the frit.

SECTION 12 ECOLOGICAL INFORMATION

Mobility: Not Available

Persistence/degradability: Not Available

Bioaccumulation: Not Available Ecotoxicity: Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal Method: Follow your Federal or State and Local regulations for

disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24. Testing of the waste may be required to determine status under the hazardous waste regulations.

Waste from residue/unused product: Can be landfilled according to local regulations.

Contaminated packing: Can be landfilled according to local regulations.

SECTION 14 TRANSPORTATION INFORMATION

UN Number: None for this product.

SECTION 15 REGULATORY INFORMATION

Silica is listed by California, Proposition 65
Silica is listed on the IARC, OSHA or NTp carcinogen list.
All ingredients are on U.S. TSCA / EC / AICS / DSL Inventory.
See local requirements.

EU Status: Symbol- None

WHMIS Status: Not Controlled

SECTION 16 ADDITIONAL INFORMATION

This information is furnished with out warranty, representation, inducement or license of any

Kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained

from sources believed to be accurate. COLORAMICS, LLC does not assume any legal

responsibility for use or reliance on same. Customers are encouraged to conduct their own

tests before using any product. Read the product label.

For more information in AUSTRALIA see web site www.nohsc.gov.au

Page PAGE 1 of NUMPAGES 4