


MAYCO MSDS SHEET #3
Active Products



SECTION 1 Chemical Product and Company Information

pg 1 of 4

Prepared September 22, 2003

Supersedes: All previous

Manufacturer: **MAYCO COLORS** division of Coloramics, LLC
 4077 Weaver Ct. South
 Hilliard, Ohio 43026
 United States of America

Distributor USA _____ Local Phone _____
 EC _____ Local Phone _____
 Australia _____ Local Phone _____

IN CASE OF EMERGENCY PLEASE CONTACT YOUR LOCAL POISON CONTROL CENTER

Prepared by: MSDS department Information Telephone Number: 614-876-1171
 Ceramic Glaze and underglazes and Miscellaneous.

Astro Gem Glazes	AS-510, 512, 513, 515, 516, 518, 519, 520, 521, 523, 524, 527, 528, 531, 532, 534, 535, 539, 541, 545, 547, 548, 551
One Stroke Colors	OS-1, 2, 3, 4, 6, 8, 9, 17, 18, 21, 26, 29, 32, 34, 36, 38, 41, 43, 44, 45, 46, 47, 48, 52, 54, 58, 59, 60, 61, 62, 63, 65, 66, 104, 105, 132, 136, 137, 138, 140, 142, 143, 144, 147, 153
Underglazes	UG-1, 2, 3, 7, 8, 10, 11, 12, 15, 17, 18, 19, 21, 22, 24, 25, 26, 27, 30, 31, 32, 33, 34, 35, 37, 38, 39, 41, 42, 43, 45, 46, 50, 51, 52, 53, 56, 57, 58, 67, 68, 69, 70, 71
	72, 73, 75, 78, 80, 81, 82, 83, 84, 85, 86, 87, 89, 90, 91, 92, 93, 94, 95, 97, 98, 100, 103, 104, 105, 108, 109, 110, 111, 116, 119, 125, 127, 128, 130, 131, 136, 141, 142, 144, 145, 146, 150, 178, 180, 181, 189, 191, 192, 194, 195, 196, 198, 201, 202
Pottery Coats	PC-501 through PC-505
Miscellaneous	AC-306, AC-308
Series 2000 Glazes	*S-2101-2168
2585	S-2560, 2561, 2562, 2564, 2565, 2566, 2574, 2577, 2578, 2579, 2580, 2581, S-2587, 2588, 2589, 2590, 2591, 2592, 2593
	*Excluding: S-2104, 2105, 2122, 2130, 2168, 2586
Series 2000 Mattes*	S-2200, 2201, 2208, 2209, 2218, 2223, 2226, 2227, 2228, 2229, 2230, 2231, 2208,
	S-2232, 2233, 2234, 2235, 2236, 2237, 2239,
	*Excluding S-2224, S-2225
Stroke and Coat Series	All Stroke and Coat (SC's) except SC-23, 58, 59, 62, 24, 20, 4, 67, 68, 50, SP-204, SD-304, SD-323 all SP series except SP-204
Specstone Glazes	S-2167, 2169, 2401, 2402, 2408, 2421, 2422, 2423, 2424, 2425, 2427
Crystalites	S-2701 through S-2718 & S-2719, S-2722, S-2723
Roll a Coat	SC-210
Elements	EL-101 through EL-118
Chunky Elements	EL-201 through EL-206
Classic Crackles	CC-500 through CC-507
Clear Glaze	S-2000, S-2101, SC-209
Stoneware Like Glaze	SLG-02, 06, 17

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS Pg 2 of 4

INGREDIENTS	CAS	ACGIH TLV	OSHA PEL
Alumina Silicate	1332-58-7	NA	NA
Bentonite / Clay	1302-78-9	NA	NA
Water	7732-18-5	NA	NA

SECTION 3 HAZARDS IDENTIFICATION

Crystalline Silica may be present.
(OSHA PEL .1mg/m3)

Route(s) of Entry: Ingestion, absorption through the skin is negligible.
Inhalation only if sprayed.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

SECTION 4 FIRST AID MEASURES

If inhaled: Remove from exposure
If on skin: Wash skin with soap and water
If in eyes: Flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a physician.
If swallowed: Dilute by drinking water

SECTION 5 FIRE FIGHTING MEASURES**FIRE AND EXPLOSION HAZARD DATA**

Flash Point (method used): N/A

LEL: N/A

UEL: N/A Flammable Limits: N/A

Extinguishing Media: None required, not combustible.

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.
Waste Disposal Method: Follow Federal or State and Local regulations for disposal. Testing of the waste may be required to determine status under the hazardous waste regulations.

SECTION 7 HANDLING AND STORAGE**PRECAUTIONS FOR SAFE HANDLING AND USE**

Engineer Control - None

Work practices- Store away from feed and food. Do not smoke, eat or drink while handling.

Procedure / equipment- None

Procedure for leaks or spills: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

pg 3 of 4

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The Work/Hygienic Practices apply regardless of the method of application. Respiratory Protection (Specify Type): Use a NIOSH approved dust and/or fume respirator as necessary.

Ventilation: Local Exhaust - for spraying

Protective Gloves: N/A

Eye Protection: for spraying

Other Protective Clothing or Equipment: Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons. Work/Hygienic Practices: Food, beverages, and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking, smoking, or applying cosmetics.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Various colors

Odor and odor threshold: Negligible

Ph: Not available

Boiling Point: None

Vapor Pressure: NA

Vapor Density: NA

Melting Point: above 1000oF

Specific Gravity (H₂O=1): 1.4 to 1.6

Flammable Limits: None

Explosive limits: None

Partition Coefficient: None

Oxidizing Properties: None

Solubility in Water: Negligible

Percent Volatile by Volume: None

Evaporation Rate: None

Freezing point: NA

Flash Point: None

Auto ignition temperature: None

SECTION 10 STABILITY AND REACTIVITY DATA

Incompatibility (material to avoid): Avoid fumes from firing by venting kiln area.

Stability: Stable (conditions to avoid: N/A)

Hazardous Decomposition or Byproducts: Not available

Hazardous Polymerization: Will not occur

Conditions to avoid: Fumes from firing in kiln. Inhalation of spray.

SECTION 11 TOXICOLOGICAL INFORMATION pg 4 of 4

Hazard to Human: None during normal use. Harmful if inhaled or swallowed.
DO NOT SPRAY APPLY

If glaze is spray applied the following warnings apply: Warning: Contains Quartz.

1. Possible cancer agent based on tests with laboratory animals.
2. Exposure may cause lung damage.
3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to the State of California to cause cancer.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

Additional information: Frits are fused silica glass like substances. The bioavailability may be limited because of the physical nature of the frit.

SECTION 12 ECOLOGICAL INFORMATION

Mobility: Not Available

Persistence/degradability: Not Available

Bioaccumulation: Not Available

Ecotoxicity: Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal Method: Follow your Federal or State and Local regulations for disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24. Testing of the waste may be required to determine status under the hazardous waste regulations.

Waste from residue/unused product: Can be landfilled according to local regulations.

Contaminated packing: Can be landfilled according to local regulations.

SECTION 14 TRANSPORTATION INFORMATION

UN Number: None for this product.

SECTION 15 REGULATORY INFORMATION

Silica is listed by California, Proposition 65

Silica is listed on the IARC, OSHA or NTP carcinogen list.

All ingredients are on U.S. TSCA / EC / AICS / DSL Inventory.

See local requirements.

EU Status:

Symbol- None

WHMIS Status : Not Controlled

SECTION 16 ADDITIONAL INFORMATION

This information is furnished with out warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained from sources believed to be accurate. COLORAMICS, LLC does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.

For more information in AUSTRALIA see web sight www.nohsc.gov.au