



CONSTRUCTION PRODUCTS DIVISION

102 CHESTNUT RIDGE PLAZA • MONTVALE • NEW JERSEY 07645

SEE HAZARD RATING DEFINITIONS PAGE 4

HAZARD RATING	SEE	ADDITIONAL
4 or EXTREME		
3 or HIGH		
2 or MODERATE		
1 or SLIGHT		
0 or INSIGNIFICANT		
* CHRONIC HEALTH HAZARD—SEE SECTION V		

DATE OF PREP
8/22/89

MATERIAL SAFETY DATA SHEET

EMERGENCY PHONE NO
DAY (201) 291-0233
NIGHT (201) 573-5700

SECTION I - IDENTIFICATION

PRODUCT NAME POR-ROR ANCHORING CEMENT	
PRODUCT CLASS Gypsum	
CODE NUMBER 08-00484-000	UN No. NONE
DOT	HAZARD CLASS (49CFR 172.101) NONE
	PROPER SHIPPING NAME (49CFR 172.101) Hydraulic Cement

SECTION II - INGREDIENTS

PAINTS, PRESERVATIVES, SOLVENTS OR OTHER LIQUIDS, SOLIDS AND GASES	%	TLV (Units)
PIGMENTS		
CATALYST		
VEHICLE		
SOLVENTS		
ADDITIVES		
OTHERS		
Portland Cement	CAS #65997-15-1 - 2.0	50 mppcf
Calcium Sulphate	CAS #7778-18-9 68.0	50 mppcf
Crystalline Silica	CAS #14808-60-7 30.0	10 mg/m ³
		÷ 8 SiO ₂ -2

SECTION III - PHYSICAL DATA

APPEARANCE Gray Powder No Odor	VAPOR DENSITY: HEAVIER/LIGHTER THAN AIR (Air = 1) Not Applicable	
SOLUBILITY IN WATER Partial	VAPOR PRESSURE (mm Hg.) Not Applicable	PERCENT VOLATILE BY VOLUME (%) Not Applicable
BOILING POINT (°F) Not Applicable	EVAPORATION RATE (Butyl Acetate = 1) Not Applicable	WEIGHT PER GALLON 80# per cu. ft.

This information is furnished without warranty, representation, or license of any kind, except that it is accurate to the best of Minwax Company Incorporated's knowledge or obtained from sources believed by the Minwax Company Inc. to be accurate. The Minwax Company Inc. shall have no legal responsibility for use or reliance upon any information provided herewith. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TEST, BEFORE USING ANY PRODUCT READ ITS LABEL.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME

FOR-ROK ANCHORING CEMENT

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT

NA

FLAMMABLE LIMITS

LEL

NA

UEL

NA

EXTINGUISHING MEDIA

Not Applicable

AUTOIGNITION TEMPERATURE

NA

SPECIAL FIRE FIGHTING PROCEDURES

Not Applicable

UNUSUAL FIRE AND EXPLOSION HAZARDS

Not Applicable

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

See Page 5

EFFECTS OF OVEREXPOSURE - ROUTES OF EXPOSURE

INGESTION:

May cause obstruction.

INHALATION:

Inhalation of silica dust can produce pneumoconiosis, commonly called silicosis, which is a chronic, slowly developing disease. Symptoms are dyspnea, pain in chest, decreased vital capacity and cough.

EYE CONTACT:

Dust irritant.

SKIN CONTACT:

Abrasive.

CARCINOGENICITY:

NTP - No

OSHA - No

IARC - Yes

EMERGENCY AND FIRST AID PROCEDURES

IF SWALLOWED:

If patient is conscious, first give large quantities of water or milk, and then induce vomiting using syrup of ipecac according to directions or by touching back of patient's throat with finger. CALL PHYSICIAN IMMEDIATELY.

FOR EYE CONTACT:

If present, remove contact lens, flush with plenty of water for at least 15 minutes. CALL PHYSICIAN.

FOR SKIN CONTACT:

Wash thoroughly with soap and water. If irritation persists, consult a physician.

IF AFFECTED BY

INHALATION:

Remove to fresh air.