

MATERIAL SAFETY DATA SHEET

257

INASCOR BULK-INK 97-3639 - 97-3645

PAINT DISTRIBUTING CORPORATION

TRADE NAME ON LABEL 32-174, 42-167-42-172, 42-161, 42-182-42-187,

TURER

MSDS NUMBER 32-118(A-H), 42-100-42-106

INSIDE DR. P.O. BOX 482

CAS NUMBER 97-1408(H), 97-6461 97-3040(A-m), 97-6607

WI 53563

MARCH 10, 1994

DATE PREPARED 97-14728 A-L

8-6873 (414) 563 8545

97-14729 A-L

NUMBER (FOR INFORMATION)

PREPARED BY 97-14730 A-L

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS	CHEMICAL NAME & COMMON NAMES	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
TER					
MENT: ASSORTED NON-TOXIC COLORS					
YCERINE					
CIUM CARBONATE					
MS					

ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI), INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT ABOUT 212 F	SPECIFIC GRAVITY (H2O = 1) ABOUT 9 LBS/GAL
VAPOR PRESSURE(mm Hg & TEMPERATURE) 17 mmHG	MELTING POINT 32 F
DENSITY (AIR=1) LIGHTER	EVAPORATION RATE (WATER=1) SLOWER
SOLUBILITY IN WATER DILUTABLE	WATER REACTIVE N/A

SMELL & ODOR SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

TESTING METHOD USED N/A	AUTO - IGNITION TEMPERATURE N/A	FLAMMABILITY LIMITS IN AIR % BY VOLUME N/A	LEL	UEL
-------------------------	---------------------------------	--	-----	-----

EXTINGUISHING MEDIA FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG

FIRE FIGHTING PROCEDURES

N/A

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE	CONDITIONS TO AVOID
COMPATIBILITY (MATERIALS TO AVOID) NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS	
HAZARDOUS DECOMPOSITION PRODUCTS THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER.	
HAZARDOUS POLYMERIZATION <input type="checkbox"/> MAY OCCUR <input checked="" type="checkbox"/> WILL NOT OCCUR	CONDITIONS TO AVOID

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY <input type="checkbox"/> INHALATION <input type="checkbox"/> SKIN ABSORPTION	<input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> NOT HAZARDOUS	CARCINOGEN LISTED IN <input type="checkbox"/> NTP <input type="checkbox"/> IARC MONOGRAPH	<input type="checkbox"/> OSHA <input type="checkbox"/> NOT LISTED
ACUTE HAZARDS	ACUTE		
CHRONIC HAZARDS	CHRONIC		
SIGNS AND SYMPTOMS			
SPECIAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE			
EMERGENCY FIRST AID PROCEDURES - SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IF NECESSARY.			
EYE CONTACT	DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM.		
SKIN CONTACT	PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE.		
RELATION	N/A		
RESOLUTION	IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.		

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPES)			
PROTECTIVE GLOVES RUBBER GLOVES RECOMMENDED	EYE PROTECTION CHEMICAL GOGGLES WITH EYE GUARD		
FILTERATION TO BE USED	LOCAL EXHAUST	MECHANICAL (GENERAL)	SPECIAL
OTHER (SPECIFY)			
OTHER PROTECTIVE CLOTHING AND EQUIPMENT N/A			
HYGIENIC WORK PRACTICES			

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED SOAK WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.
SITE DISPOSAL METHODS
DISPOSITION OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND AWAY FROM EXCESSIVE HEAT.
OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS