

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

NASHUA CORPORATION

44 FRANKLIN ST., NASHUA, NH 03061

MATERIAL SAFETY DATA SHEET

AP 807 (4/86)

IDENTITY (As Used on Label and List)

FUSER OIL: XEROX FO

Note: Blank spaces are not permitted. If any item is not applicable, or no
 information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Nashua Corporation	Emergency Telephone Number 1-(603)-880-5555
Address (Number, Street, City, State, and ZIP Code) 44 Franklin Street	Telephone Number for Information 1-800-258-1370
Nashua, NH 03061	Date Prepared 4-15-86 Revised 1-26-87
	Printed Name of Preparer R.L. Sevigny Manufacturing Div. O.P.D.

Section II — Components and Hazardous Information

Components (Specific Chemical Identity; Common Name(s))	PERCENT	OSHA PEL	ACGIH TLV	CAS NO.
POLYDIMETHYLSILOXANE	100%	NA	NA	63148-62-9

Section III — Physical/Chemical Characteristics

Boiling Point (°F)	>600°F	Specific Gravity (H ₂ O = 1)	0.98
Vapor Pressure (mm Hg.)	<5MM	Melting Point	NA
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	<1
Solubility in Water	<0.1%		

Appearance and Odor

Clear colorless liquid, very little odor**Section IV — Fire and Explosion Hazard Data**

Flash Point (Method Used)	Open Cup 600°F	Flammable Limits Not determined (ND)	LEL ND	UEL ND
Extinguishing Media	Water Fog, CO₂, Dry Chemical, Foam			
Special Fire Fighting Procedures	Self contained breathing apparatus, Protective Clothing.			

Unusual Fire and Explosion Hazards

None known

While this material is furnished in good faith, NO WARRANTY EXPRESS OR IMPLIED, OF MERCHANTABILITY FITNESS OR OTHERWISE IS MADE as to the product described above. This material is offered only for your consideration and Nashua Corporation including its divisions, affiliates and subsidiaries, shall not in any event be liable for special, incidental or consequential damages in connection with its publication. Likewise, no statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.

(Continued on reverse side) N.H. NASHUA CORP. DEC 19 88 10:32

FIRST AID: EYES:	Flush with large amounts of water.
SKIN:	Flush with water.
INHALATION:	No effects expected.
INGESTION:	Give several glasses of water or milk to dilute ingested product.
PRIMARY ROUTES OF ENTRY: INHALATION <u>No</u> SKIN CONTACT <u>No</u> OTHER <u>Ingestion</u>	

SECTION VI — REACTIVITY DATE:

STABILITY: STABLE <u>Yes</u> UNSTABLE _____ HAZARDOUS POLYMERIZATION WILL NOT OCCUR
CONDITIONS TO AVOID: Do not mix liquid acids or reducing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Chlorimines



SECTION VII — SPILL, LEAK AND DISPOSAL PROCEDURE:

SPILL OR RELEASE PROCEDURE: CONCENTRATE:	Sweep up but do not use sweeping compounds. Place in suitable containers.
USE SOLUTION:	Flush with water into waste treatment systems.
DISPOSAL INFORMATION: CONCENTRATE:	Bury in suitable landfill and/or in accordance with Federal, State and Local ordinances.
SPENT SOLUTION AND RINSES:	Flush with water into waste treatment systems and/or in accordance with Federal, State and Local ordinances.

SECTION VIII — SPECIAL PROTECTION INFORMATION:

RESPIRATORY PROTECTION:	None required
VENTILATION:	Normal ventilation means
PROTECTIVE EQUIPMENT: CHEMICAL FACE SHIELD OR GOGGLES: <u>No</u> GLOVES <u>Yes</u> BOOTS <u>No</u> APRON <u>No</u> PROTECTIVE SUIT <u>No</u> GLOVES, BOOTS, APRON AND SUIT MADE FROM: Rubber or Vinyl	
RECOMMENDED PERSONAL HYGIENE:	Use adequate washing facilities. Wash hands or other contact areas thoroughly. Change clothing if wetted with product. Do not reuse clothing wetted with product before clothing is laundered.

SECTION IX — OTHER INFORMATION:

SPECIAL PRECAUTIONS — STORAGE AND HANDLING:	Normal handling methods; inside storage at 30-120°F. recommended. Keep dry.
MIXING:	Not normal to usage.
REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT:	A program of regular cleaning, repairing and replacing of worn-out parts and contaminated equipment is highly desirable.
DATE PREPARED: 11/86 DATE REVIEWED:	
APPROVED:	Q.C. DEPT./  R & D DEPT./  SAFETY & ENVIRON.