## **MATERIAL SAFETY DATA SHEET**

| Simoniz USA Inc.    | REVISION DATE:01/24/02   |
|---------------------|--------------------------|
|                     | DATE PRINTED: 12/15/06   |
| 201 Boston Turnpike |                          |
| Bolton, CT 06043    | PRODUCT NUMBER: O2455XXX |
|                     | CONTROL NUMBER: 02455XXX |
| (860) 646-0172      |                          |
|                     |                          |
|                     |                          |
|                     |                          |

#### **SECTION I - IDENTIFICATION**

PRODUCT NAME: One Step

PRODUCT TYPE: ..... Automobile Finish/Protectant

INGREDIENT

#### **SECTION II - INGREDIENTS**

CAS NUMBER

PEL

**PERCENT** 

ID NUMBER:

PACKING GROUP:

| Water                | 7732-18-5  | No limits established     | Not<br>Listed. |
|----------------------|------------|---------------------------|----------------|
| Isopropyl Alcohol    | 67-63-0    | 400 ppm, 500 ppm<br>STEL  |                |
| 2-Butoxy Ethanol     | 111-76-2   | 20 ppm TLV, 25 ppm<br>PEL |                |
| Polydimethylsiloxane | 63148-62-9 | No limits established     |                |

#### **SECTION III - PHYSICAL DATA**

APPEARANCE: Opaque light blue liquid, slight solvent odor.

**BOILING POINT: 210 degrees F.** VAPOR PRESSURE: N/A VAPOR DENSITY: Greater than 1. SPECIFIC GRAVITY: 0.99

PH: 6.5-7.5 **SOLUBILITY IN WATER: Completely soluble.** 

### **SECTION IV - FIRE AND EXPLOSION DATA**

| OLOTION IV - TINE AND EXI LOCION DATA   |
|---|
| FLASHPOINT: Greater than 150 degrees F.   |
| EXTINGUISHING MEDIA: Water fog or fine spray. Carbon dioxide, Dry chemical, or          |
| Alcohol resistant foam.   |
| SPECIAL FIRE FIGHTING PROCEDURES: Firefighters working in areas                         |
| where this product is present should be equipped with an approved, fully enclosed SCBA. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS:None known.  |
| SECTION V - REACTIVITY DATA   |
| STABILITY: Stable under normal conditions.  |
| HAZARDOUS POLYMERIZATION: This product not known to polymerize.                         |
| INCOMPATIBILITY: Avoid strong oxidizers. Avoid heat, sparks or open                     |
| flames.   |
| HAZARDOUS BYPRODUCTS: Carbon monoxide, carbon dioxide.                                  |
| SECTION VI - HEALTH DATA  |
| ROUTE(S) OF ENTRY: Inhalation, skin absorption, or ingestion.                           |
| LISTED CARCINOGEN: Not listed by IARC, NTP or OSHA.                                     |
| MEDICAL CONDITION AGGRAVATED:May aggravate pre-existing                                 |
| dermatitis.   |
| INHALATION: Inhalation of large amounts of this product may cause                       |
| dizziness and/or nausea. Maintain adequate ventilation in the work area.                |
| INGESTION: This material can cause irritation or damage to stomach                      |
| and esophagus.  |
| EYES: May cause eye irritation.   |
|   |

| SKIN (DERMAL): This product ma  | y cause irritation or redness of the skin  |
|---|--|
| SECTION VII FIRS  | T AID                                      |
| BREATHING (INHALATION): If victim shows s                               | igns of discomfort or irritation, remove   |
| to fresh air. If symptoms persist, get immediate medical att            |  |
| SWALLOWING (INGESTION): DO NOT INDUC                                    |  |
| of water or milk. Do not attempt to give liquids to an uncon attention! | scious person. Get immediate medical       |
| EYES: Flush eyes with a   | a large quantity of fresh water for at lea |
| 15 minutes. If irritation persists, consult a physician.                | · ·  |
| SKIN (DERMAL): Flush from skin  | and clothing with large amounts of fres    |
| water. If irritation persists, consult physician. Wash contar           | ninated clothing before wearing.           |
| SECTION VIII EMPLOYEE   |  |
| RESPIRATORY PROTECTION: Not usually need                                | ed in well ventilated areas. If needed, u  |
| an OSHA approved respirator.  |  |
| PROTECTIVE CLOTHING: Nitrile or PVC g                                   | loves, and chemical splash goggles.        |
| ADDITIONAL MEASURES: Do not place this                                  |  |
| Keep away from children! Spilled material is slippery.                  |  |
| SECTION IX - SPILL AND DI   | SDOSAL DATA                                |
|   |  |
| SPILL: Dike to prevent s  | spinage into streams or sewer systems.     |
| Consult local, state and federal authorities.                           | 11 1 1 4 4 16 1 1 41 44                    |
| WASTE DISPOSAL: As recommended  |  |
| HANDLING & STORAGE PRECAUTIONS  | Store in a cool, well ventilated           |
| area. Avoid overheating or freezing.                                    |  |
| SECTION X -OTHER REGULATO   |  |
| PROPER SHIPPING NAME: Not D.O.T. regulated.                             | NFPA HEALTH: 1                             |
| CONSTITUENT:  | NFPA FLAMMABILITY: 2                       |
| HAZARD CLASS AND LAREL:   | NEPA REACTIVITY 0                          |

# **SECTION XI - PRECAUTIONARY STATEMENTS**

NFPA OTHER: None

WARNING:..... The information contained in this MSDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be saferead this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it.