

MATERIAL SAFETY DATA SHEET
COATINGS AND RESINS GROUP



SECTION I - PRODUCT INFORMATION

MANUFACTURER'S NAME: PPG INDUSTRIES INC.
PRODUCT SAFETY LOC.: 260 KAPPA DRIVE
PITTSBURGH, PA 15238
MSDS CONTACT: MANAGER, INDUSTRIAL HYGIENE
AND PRODUCT SAFETY
(412) 963-5822
EMERGENCY TELEPHONE: (304) 843-1300

CODE/IDENTITY : DTU501 (0922870)
TRADE NAME: COOL WEATHER ACRYLIC URETHANE REDUCER
CHEMICAL FAMILY: SOLVENT BLEND
US-DOT: PAINT RELATED MATERIAL, FLAMMABLE LIQUID
DATE OF PREPARATION: 11/10/87
CUSTOMER PART #:

SECTION II - INGREDIENTS

	APPROX. %WT.	CAS NO.	EXPOSURE LIMITS		
			ACGIH TLV	OSHA PEL	PPG IPEL
ACETONE	35	67-64-1	750.00PPM	1000.00PPM	750.00PPM
LIGHT ALIPHATIC SOLVENT NAPHTHA	30	64742-89-8	NOT EST.	NOT EST.	NOT EST.
LIGHT ALIPHATIC SOLVENT NAPHTHA	25	64742-89-8	NOT EST.	NOT EST.	NOT EST.
N-BUTYL ACETATE	10	123-86-4	150.00PPM	150.00PPM	150.00PPM

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE : 56 - 128 DEG C
VAPOR PRESSURE: 143.8 mmHg
VAPOR DENSITY : HEAVIER THAN AIR
% VOL/VOLUME : 100.0
EVAP RATE(BLOAc=100): 755

SOLUBILITY IN WATER: 37.0 %
WT/GAL (LBS): 6.19 (U.S.)
PH: U/I
% SOLID BY WEIGHT: .01
SPECIFIC GRAVITY: .74

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

US-DOT CATEGORY: EXTREMELY FLAMMABLE
FLASHPOINT: 10 DEG. F PHCC

FLAMMABLE LIMITS: LEL 1.4 UEL U/I

EXTINGUISHING MEDIA:

USE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL, OR UNIVERSAL AQUEOUS FILM FORMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS B FLAMMABLE LIQUID FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES. TOXIC GASES MAY FORM WHEN PRODUCT IS CONTACTED BY FLAME OR HOT SURFACES.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. FIRE-FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: NOT EXPECTED TO OCCUR

INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID):

AVOID CONTACT WITH STRONG ALKALIES, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS WHEN HEATED, INCLUDING:

Carbon Monoxide

SECTION VI - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

PROVIDE MAXIMUM VENTILATION. ONLY PERSONNEL EQUIPPED WITH PROPER RESPIRATORY AND SKIN AND EYE PROTECTION SHOULD BE PERMITTED IN THE AREA. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD:

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED WASTE MANAGEMENT FACILITY.

SECTION VII - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE FROM:

INGESTION:

HARMFUL OR FATAL IF SWALLOWED.

EYE CONTACT:

CAUSES SEVERE EYE IRRITATION.

SKIN CONTACT:

MAY CAUSE MODERATE SKIN IRRITATION.

INHALATION:

VAPOR AND SPRAY MIST MAY BE HARMFUL IF INHALED.

VAPOR IRRITATES EYES, NOSE, AND THROAT.

REPEATED EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM AND PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

CONTINUED ON PAGE 2



INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

CHRONIC OVEREXPOSURE:

AVOID LONG-TERM AND REPEATED CONTACT.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, AND LOSS OF COORDINATION ARE INDICATIONS THAT SOLVENT LEVELS ARE TOO HIGH.

REDNESS, ITCHING, BURNING SENSATION AND VISUAL DISTURBANCES MAY INDICATE EXCESSIVE EYE CONTACT.

DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE CONDITIONS ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NOT APPLICABLE**SECTION VIII - FIRST AID PROCEDURES****INGESTION:**

IF SWALLOWED, DO NOT INDUCE VOMITING.

EYE CONTACT:

IN CASE OF EYE CONTACT, FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT:

IN CASE OF SKIN CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOLLOWED BY WASHING WITH SOAP AND WATER.

INHALATION:

IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION AND OTHER SUPPORTIVE MEASURES AS REQUIRED.

OTHER:

IF ANY OF THE FOLLOWING OCCUR DURING OR FOLLOWING USE OF THIS PRODUCT, CONTACT A POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY; HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE. *INGESTION *EXCESSIVE EXPOSURE TO A CORROSIVE MATERIAL.
* PERSISTENT SKIN/EYE IRRITATION OR BREATHING DIFFICULTIES.

SECTION IX - PROTECTION INFORMATION**PERSONAL PROTECTIVE EQUIPMENT FOR:****EYE PROTECTION:**

WEAR CHEMICAL-TYPE SPLASH GOGGLES OR FULL FACE SHIELD.

SKIN PROTECTION:

WEAR PROTECTIVE CLOTHING, INCLUDING IMPERMEABLE APRON AND GLOVES CONSTRUCTED OF: POLYVINYL ALCOHOL, NEOPRENE RUBBER, NITRILE RUBBER OR LATEX RUBBER

RESPIRATORY PROTECTION:

OVEREXPOSURE TO VAPORS MAY BE PREVENTED BY ENSURING VENTILATION CONTROLS, VAPOR EXHAUST OR FRESH AIR ENTRY. NIOSH/MSHA-APPROVED (TC-23C-) PAINT SPRAY OR AIR SUPPLIED (TC-19C-) RESPIRATORS MAY ALSO REDUCE EXPOSURE. READ RESPIRATOR MANUFACTURER'S INSTRUCTIONS AND LITERATURE CAREFULLY TO DETERMINE THE TYPE OF AIRBORNE CONTAMINANTS AGAINST WHICH THE RESPIRATOR IS EFFECTIVE AND HOW IT IS TO BE PROPERLY FITTED.

OTHER EQUIPMENT:

CLEAN OR DISCARD CONTAMINATED CLOTHING AND SHOES.

VENTILATION REQUIREMENTS:

PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE CONCENTRATION OF INGREDIENTS IN SECTION II BELOW THE LOWEST SUGGESTED EXPOSURE LIMIT, AND LEL IN SECTION IV BELOW STATED LIMIT.

SECTION X - SPECIAL PRECAUTIONS**HANDLING AND STORAGE PRECAUTIONS:**

DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS 1B FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS:

IF THIS MATERIAL IS PART OF A MULTIPLE COMPONENT COATING SYSTEM, READ THE MATERIAL SAFETY DATA SHEET(S) FOR THE OTHER COMPONENT OR COMPONENTS BEFORE BLENDING AS THE RESULTING MIXTURE MAY HAVE THE HAZARDS OF ALL OF ITS PARTS.
CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A FEW INCHES.

ALL CHEMICAL SUBSTANCES IN THIS PRODUCT COMPLY WITH ALL APPLICABLE RULES OR ORDERS UNDER THE ENVIRONMENTAL PROTECTION AGENCY'S TOXIC SUBSTANCES CONTROL ACT.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

U/I = UNKNOWN INFORMATION

N/A = NOT APPLICABLE

NOT EST. = NOT ESTABLISHED

(CUSTOMER NO.) LOCATION : 87DTU501////1110