

**MATERIAL SAFETY DATA SHEET
COATINGS AND RESINS GROUP**



SECTION I - PRODUCT INFORMATION

MANUFACTURER'S NAME: PPG INDUSTRIES INC.	CODE/IDENTITY : DP40	(091185D)
PRODUCT SAFETY LOC.: 260 KAPPA DRIVE	TRADE NAME: EPOXY PRIMER	
PITTSBURGH, PA 15238	CHEMICAL FAMILY: EPOXY	
MSDS CONTACT: MANAGER, INDUSTRIAL HYGIENE	US-DOT: PAINT, FLAMMABLE LIQUID	
AND PRODUCT SAFETY	DATE OF PREPARATION: 11/10/87	
(412) 963-5822	CUSTOMER PART #:	
EMERGENCY TELEPHONE: (304) 843-1300		

SECTION II - INGREDIENTS

	APPROX. WGT.	CAS NO.	EXPOSURE LIMITS		
			ACGIH TLV	OSHA PEL	PPG IPEL
MAGNESIUM SILICATE	5	14807-96-6	10.00Mg/M3	NOT EST.	10.00Mg/M3
TITANIUM DIOXIDE #	10	13463-67-7	10.00Mg/M3	15.00Mg/M3	10.00Mg/M3
BARIUM SULFATE	10	7727-43-7	10.00Mg/M3	NOT EST.	10.00Mg/M3
STRONTIUM CHROMATE * **	5	7789-06-2	0.05Mg/M3	0.10Mg/M3	0.05Mg/M3
1-METHOXY-2-PROPANOL	5	107-98-2	100.00PPM	NOT EST.	100.00PPM
OXO-HEPTYL ACETATE	1	90438-79-2	NOT EST.	NOT EST.	NOT EST.
ISOBUTYL ACETATE	15	110-19-0	150.00PPM	150.00PPM	150.00PPM
ISOPROPYL ALCOHOL, ANHYDROUS	5	67-63-0	400.00PPM	400.00PPM	400.00PPM
METHYL ETHYL KETONE	15	78-93-3	200.00PPM	200.00PPM	200.00PPM
TOLUENE	5	108-88-3	100.00PPM	200.00PPM	100.00PPM
FILM FORMERS, RESINS, AND ADDITIVES	20	PROPRIETARY	NOT EST.	NOT EST.	NOT EST.

THE FOLLOWING HAZARDOUS MATERIALS ARE COMPONENTS OF ONE OR MORE OF THE ABOVE INGREDIENTS.

CHROMIUM COMPOUNDS (SLIGHTLY SOLUBLE, XNV)*	5	18540-29-9	.05Mg/M3	.50Mg/M3	.05Mg/M3
---	---	------------	----------	----------	----------

CARCINOGENIC ACCORDING TO CRITERIA ESTABLISHED BY: * = NTP ** = IARC @ = OSHA # = OTHER

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE : 78 - 200 DEG.C	SOLUBILITY IN WATER: 13.4 %
VAPOR PRESSURE: 37.9 mmHg	WT/GAL (LBS): 10.40 (U.S.)
VAPOR DENSITY : HEAVIER THAN AIR	pH: U/I
% VOL/VOLUME : 69.90	% SOLID BY WEIGHT: 52.79
EVAP RATE(S ₂₀ OAc=100): 348	SPECIFIC GRAVITY: 1.25

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

US-DOT CATEGORY: FLAMMABLE
FLASHPOINT: 30 DEG. F PHCC
FLAMMABLE LIMITS: LEL 1.6 UEL U/I

EXTINGUISHING MEDIA:

USE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL, OR UNIVERSAL AQUEOUS FILM FORMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS IB FLAMMABLE LIQUID FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES. TOXIC GASES MAY FORM WHEN PRODUCT IS CONTACTED BY FLAME OR HOT SURFACES.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. FIRE-FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
HAZARDOUS POLYMERIZATION: NOT EXPECTED TO OCCUR
INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID):

AVOID CONTACT WITH STRONG ALKALIES, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.
HAZARDOUS DECOMPOSITION PRODUCTS:

MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS WHEN HEATED. WELDING, BRAZING, OR FLAME-CUTTING ON SURFACES COATED WITH THIS PRODUCT MAY PRODUCE FUMES INCLUDING: Carbon Monoxide, Hydrogen Chloride, Chlorinated Products, chlorine, Oxides of Chromium

SECTION VI - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

PROVIDE MAXIMUM VENTILATION. ONLY PERSONNEL EQUIPPED WITH PROPER RESPIRATORY AND SKIN AND EYE PROTECTION SHOULD BE PERMITTED IN THE AREA. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD:

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED WASTE MANAGEMENT FACILITY.

SECTION VII - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: HARMFUL OR FATAL IF SWALLOWED.
EYE CONTACT:



SKIN CONTACT: CAUSES SEVERE EYE IRRITATION.
CAUSES PRIMARY SKIN IRRITATION.
INHALATION: PROLONGED OR REPEATED CONTACT MAY CAUSE AN ALLERGIC SKIN REACTION.

VAPOR AND SPRAY MIST MAY BE HARMFUL IF INHALED.
VAPOR IRRITATES EYES, NOSE, AND THROAT.
SANDING AND GRINDING DUSTS MAY BE HARMFUL IF INHALED.
REPEATED EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM AND PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.
INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

CHRONIC OVEREXPOSURE:
AVOID LONG-TERM AND REPEATED CONTACT.
THIS PRODUCT CONTAINS TITANIUM DIOXIDE. ANIMALS INHALING MASSIVE QUANTITIES OF TITANIUM DIOXIDE DUST IN A LONG-TERM STUDY DEVELOPED LUNG TUMORS. STUDIES WITH HUMANS INVOLVED IN MANUFACTURE OF THIS PIGMENT INDICATE NO INCREASED RISK OF CANCER FROM EXPOSURE. POTENTIAL FOR INHALATION OF TITANIUM DIOXIDE DUSTS FROM COATINGS IS VERY LIMITED AND OVEREXPOSURES ARE NOT EXPECTED.
THIS PRODUCT CONTAINS A SLIGHTLY SOLUBLE FORM OF A CHROMIUM (6+) COMPOUND. NTP AND IARC ASSOCIATE LONG-TERM EXPOSURE TO HIGH LEVELS OF THESE MATERIALS WITH AN INCREASED RISK OF CANCER.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:
EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, AND LOSS OF COORDINATION ARE INDICATIONS THAT SOLVENT LEVELS ARE TOO HIGH.
REDNESS, ITCHING, BURNING SENSATION AND VISUAL DISTURBANCES MAY INDICATE EXCESSIVE EYE CONTACT.
DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE CONDITIONS ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NOT APPLICABLE

SECTION VIII - FIRST AID PROCEDURES

INGESTION:

IF SWALLOWED, DO NOT INDUCE VOMITING.

EYE CONTACT:

IN CASE OF EYE CONTACT, FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT:

IN CASE OF SKIN CONTACT, REMOVE PROMPTLY BY WIPING, FOLLOWED BY WATERLESS HAND CLEANER AND SOAP AND WATER.

INHALATION:

IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION AND OTHER SUPPORTIVE MEASURES AS REQUIRED.

OTHER:

IF ANY OF THE FOLLOWING OCCUR DURING OR FOLLOWING USE OF THIS PRODUCT, CONTACT A POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY; HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE. *INGESTION *EXCESSIVE EXPOSURE TO A CORROSIVE MATERIAL.
* PERSISTENT SKIN/EYE IRRITATION OR BREATHING DIFFICULTIES.

SECTION IX - PROTECTION INFORMATION

PERSONAL PROTECTIVE EQUIPMENT FOR:

EYE PROTECTION:

WEAR CHEMICAL-TYPE SPLASH GOGGLES OR FULL FACE SHIELD.

SKIN PROTECTION:

WEAR PROTECTIVE CLOTHING, INCLUDING IMPERMEABLE APRON AND GLOVES CONSTRUCTED OF: POLYVINYL ALCOHOL, NEOPRENE RUBBER, OR LATEX RUBBER

RESPIRATORY PROTECTION:

OVEREXPOSURE TO VAPORS MAY BE PREVENTED BY ENSURING VENTILATION CONTROLS, VAPOR EXHAUST OR FRESH AIR ENTRY. NIOSH/MSHA-APPROVED (TC-23C-) PAINT SPRAY OR AIR SUPPLIED (TC-19C-) RESPIRATORS MAY ALSO REDUCE EXPOSURE. READ RESPIRATOR MANUFACTURER'S INSTRUCTIONS AND LITERATURE CAREFULLY TO DETERMINE THE TYPE OF AIRBORNE CONTAMINANTS AGAINST WHICH THE RESPIRATOR IS EFFECTIVE AND HOW IT IS TO BE PROPERLY FITTED.

OTHER EQUIPMENT:

CLEAN OR DISCARD CONTAMINATED CLOTHING AND SHOES.

VENTILATION REQUIREMENTS:

PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE CONCENTRATION OF INGREDIENTS LISTED IN SECTION II BELOW THE LOWEST SUGGESTED EXPOSURE LIMITS, THE LEL IN SECTION IV BELOW THE STATED LIMIT, AND TO REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR FLAME CUTTING ON SURFACES COATED WITH THIS PRODUCT.

SECTION X - SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS IB FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS:

IF THIS MATERIAL IS PART OF A MULTIPLE COMPONENT COATING SYSTEM, READ THE MATERIAL SAFETY DATA SHEET(S) FOR THE OTHER COMPONENT OR COMPONENTS BEFORE BLENDING AS THE RESULTING MIXTURE MAY HAVE THE HAZARDS OF ALL OF ITS PARTS.

CONTINUED ON PAGE 3



Continuation of Manufacturer's Code - DP40

DATE OF PREP: 11/10/87

CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A FEW INCHES.
ALL CHEMICAL SUBSTANCES IN THIS PRODUCT COMPLY WITH ALL APPLICABLE RULES OR ORDERS UNDER THE ENVIRONMENTAL PROTECTION AGENCY'S TOXIC SUBSTANCES CONTROL ACT.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

U/I = UNKNOWN INFORMATION

N/A = NOT APPLICABLE

NOT EST. = NOT ESTABLISHED

(CUSTOMER NO.) LOCATION : 87DP40/////1110



VAPOR AND SPRAY MIST MAY BE HARMFUL IF INHALED.
 VAPOR IRRITATES EYES, NOSE, AND THROAT.
 REPEATED EXPOSURE TO HIGH VAPOR CONCENTRATIONS MAY CAUSE IRRITATION OF THE RESPIRATORY SYSTEM AND PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.
 INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

CHRONIC OVEREXPOSURE:

AVOID LONG-TERM AND REPEATED CONTACT.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

EYE WATERING, HEADACHES, NAUSEA, DIZZINESS, AND LOSS OF COORDINATION ARE INDICATIONS THAT SOLVENT LEVELS ARE TOO HIGH.

REDNESS, ITCHING, BURNING SENSATION AND VISUAL DISTURBANCES MAY INDICATE EXCESSIVE EYE CONTACT.

DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE CONDITIONS ASSOCIATED WITH EXCESSIVE SKIN CONTACT.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NOT APPLICABLE**SECTION VIII - FIRST AID PROCEDURES****INGESTION:**

IF SWALLOWED, DO NOT INDUCE VOMITING.

EYE CONTACT:

IN CASE OF EYE CONTACT, FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT:

IN CASE OF SKIN CONTACT, REMOVE PROMPTLY BY WIPING, FOLLOWED BY WATERLESS HAND CLEANER AND SOAP AND WATER.

INHALATION:

IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION AND OTHER SUPPORTIVE MEASURES AS REQUIRED.

OTHER:

IF ANY OF THE FOLLOWING OCCUR DURING OR FOLLOWING USE OF THIS PRODUCT, CONTACT A POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY; HAVE MATERIAL SAFETY DATA SHEET INFORMATION AVAILABLE. *INGESTION *EXCESSIVE EXPOSURE TO A CORROSIVE MATERIAL.
 * PERSISTENT SKIN/EYE IRRITATION OR BREATHING DIFFICULTIES.

SECTION IX - PROTECTION INFORMATION**PERSONAL PROTECTIVE EQUIPMENT FOR:****EYE PROTECTION:**

WEAR CHEMICAL-TYPE SPLASH GOGGLES.

SKIN PROTECTION:

WEAR PROTECTIVE CLOTHING, INCLUDING IMPERMEABLE APRON AND GLOVES CONSTRUCTED OF: NITRILE RUBBER, NEOPRENE RUBBER OR POLYVINYL ALCOHOL

RESPIRATORY PROTECTION:

OVEREXPOSURE TO VAPORS MAY BE PREVENTED BY ENSURING VENTILATION CONTROLS, VAPOR EXHAUST OR FRESH AIR ENTRY. NIOSH/MSHA-APPROVED (TC-23C-) PAINT SPRAY OR AIR SUPPLIED (TC-19C-) RESPIRATORS MAY ALSO REDUCE EXPOSURE. READ RESPIRATOR MANUFACTURER'S INSTRUCTIONS AND LITERATURE CAREFULLY TO DETERMINE THE TYPE OF AIRBORNE CONTAMINANTS AGAINST WHICH THE RESPIRATOR IS EFFECTIVE AND HOW IT IS TO BE PROPERLY FITTED.

OTHER EQUIPMENT:

CLEAN OR DISCARD CONTAMINATED CLOTHING AND SHOES.

VENTILATION REQUIREMENTS:

PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE CONCENTRATION OF INGREDIENTS LISTED IN SECTION II BELOW THE LOWEST SUGGESTED EXPOSURE LIMITS, THE LEL IN SECTION IV BELOW THE STATED LIMIT, AND TO REMOVE DECOMPOSITION PRODUCTS DURING WELDING OR FLAME CUTTING ON SURFACES COATED WITH THIS PRODUCT.

SECTION X - SPECIAL PRECAUTIONS**HANDLING AND STORAGE PRECAUTIONS:**

DO NOT STORE ABOVE 120 DEGREES F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS IB FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS:

IF THIS MATERIAL IS PART OF A MULTIPLE COMPONENT COATING SYSTEM, READ THE MATERIAL SAFETY DATA SHEET(S) FOR THE OTHER COMPONENT OR COMPONENTS BEFORE BLENDING AS THE RESULTING MIXTURE MAY HAVE THE HAZARDS OF ALL OF ITS PARTS.
 CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUIDS IN EXCESS OF A FEW INCHES.

ALL CHEMICAL SUBSTANCES IN THIS PRODUCT COMPLY WITH ALL APPLICABLE RULES OR ORDERS UNDER THE ENVIRONMENTAL PROTECTION AGENCY'S TOXIC SUBSTANCES CONTROL ACT.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

U/I = UNKNOWN INFORMATION

N/A = NOT APPLICABLE

NOT EST. = NOT ESTABLISHED

(CUSTOMER NO.) LOCATION : 87DP401/////1110

MATERIAL SAFETY DATA SHEET
COATINGS AND RESINS GROUP



SECTION I - PRODUCT INFORMATION

MANUFACTURER'S NAME: PPG INDUSTRIES INC. CODE/IDENTITY : DP401 (0814860)
 PRODUCT SAFETY LOC.: 260 KAPPA DRIVE TRADE NAME: CATALYST FOR DP-40
 PITTSBURGH, PA 15238 CHEMICAL FAMILY: POLYAMIDE
 MSDS CONTACT: MANAGER, INDUSTRIAL HYGIENE AND PRODUCT SAFETY US-DOT: PAINT RELATED MATERIAL; FLAMMABLE LIQUID
 (412) 963-5822 DATE OF PREPARATION: 11/10/87
 EMERGENCY TELEPHONE: (304) 843-1300 CUSTOMER PART #:

SECTION II - INGREDIENTS

APPROX. WGT.	CAS NO.	EXPOSURE LIMITS			
		ACGIH TLV	OSHA PEL	PPG IPEL	
		TOLUENE	100.00PPM	200.00PPM	100.00PPM
		XYLENE	100.00PPM	100.00PPM	100.00PPM
		ISOPROPYL ALCOHOL, ANHYDROUS	400.00PPM	400.00PPM	400.00PPM
		1-METHOXY-2-PROPANOL	100.00PPM	NOT EST.	100.00PPM
		OXO-HEPTYL ACETATE	5	NOT EST.	NOT EST.
		2-BUTOXY ETHYL ACETATE	10	NOT EST.	NOT EST.
		FILM FORMERS, RESINS, AND ADDITIVES	15	NOT EST.	NOT EST.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE : 82 - 200 DEG.C SOLUBILITY IN WATER: 49.5 %
 VAPOR PRESSURE: 23.8 mmHg WT/GAL (LBS): 7.18 (U.S.)
 VAPOR DENSITY : HEAVIER THAN AIR pH: U/I
 % VOL/VOLUME : 84.50 % SOLID BY WEIGHT: 17.41
 EVAP RATE(BUOAC=100): 186 SPECIFIC GRAVITY: .86

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

US-DOT CATEGORY: FLAMMABLE
 FLASHPOINT: 40 DEG. F PMCC
 FLAMMABLE LIMITS: LEL 1.7 UEL U/I

EXTINGUISHING MEDIA:

USE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) CLASS B EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL, OR UNIVERSAL AQUEOUS FILM FORMING FOAM) DESIGNED TO EXTINGUISH NFPA CLASS B FLAMMABLE LIQUID FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES. TOXIC GASES MAY FORM WHEN PRODUCT IS CONTACTED BY FLAME OR HOT SURFACES.

SPECIAL FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE INEFFECTIVE. WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. FIRE-FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

SECTION V - REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION: NOT EXPECTED TO OCCUR
 INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID):
 AVOID CONTACT WITH STRONG ALKALIES, STRONG MINERAL ACIDS, OR STRONG OXIDIZING AGENTS.
 HAZARDOUS DECOMPOSITION PRODUCTS:

MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS WHEN HEATED. WELDING, BRAZING, OR FLAME-CUTTING ON SURFACES COATED WITH THIS PRODUCT MAY PRODUCE FUMES INCLUDING: Carbon Monoxide, Oxides of Nitrogen

SECTION VI - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

PROVIDE MAXIMUM VENTILATION. ONLY PERSONNEL EQUIPPED WITH PROPER RESPIRATORY AND SKIN AND EYE PROTECTION SHOULD BE PERMITTED IN THE AREA. REMOVE ALL SOURCES OF IGNITION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR DISPOSAL.

WASTE DISPOSAL METHOD:

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED WASTE MANAGEMENT FACILITY.

SECTION VII - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: HARMFUL OR FATAL IF SWALLOWED.
 EYE CONTACT: CAUSES SEVERE EYE IRRITATION.
 SKIN CONTACT: MAY CAUSE MODERATE SKIN IRRITATION.
 INHALATION: MAY BE ABSORBED THROUGH THE SKIN.

CONTINUED ON PAGE 2