
Deck & Shake #70 | MSDS

MSDS

Material Safety Data Sheet Deck & Shake #70 Clear





RECEIVED

MAY 24 2005

Facilities Management HEALTH AND SAFETY

Section I Identification

PSM (Pacific Sales & Manufacturing)

P.O. Box 7249

Berkeley, CA 94707

Phone: (800) 541-0128

(800) 541-0128

Emergency Numbers:

(510) 222-3850

(209) 763-5375

Manufacturing

Manufacturer:

531 16th St.

Location:

Richmond, CA 94801

Product Description:

Water repellent, penetrating wood sealer

Trade Name:

Deck & Shake #70 Clear

Chemical Family:

Lipids and petroleum distillate

Section II Hazardous Ingredients

Petroleum Distillate (mineral spirits)

CAS no. 64741-41-3

Amount:

PEL: 500 ppm TLV: 100 ppm (ACGIH)

STEL: 200 ppm (ACGIH)

39%

1-(1, 1-dimethylethoxy) -2- propanol

CAS no. 57018-52-7

2.0%

Chemist: P

Peter Chisa

Ph# (209) 763-5375

Section III Product Data

boiling point	300-380 F	solubility in water	negligible
vapor pressure (mm Hg)	3.0 @ 20 C	specific gravity (H2O=1)	0.82
vapor density (air=1)	4.8	percent volatility	64
evaporation rate (BUOAC=1)	0.13	рН	NA

NA= not applicable

Appearance and Odor: Light amber liquid with characteristic odor

Section IV Fire & Explosion Hazard Data

Flash point: 107 F	LEL: 1.0 % by vol.	UEL: 6.0% by vol.
(solvent component)	(approx.)	(approx.)

DOT Classification:

NA1993, Combustible Liquid N.O.S. P.G. III

(contains petroleum distillates)

Auto Ignition Temp:

400 F (approx.)

Extinguishing Media:

dry chemical, CO2, foam

Special fire fighting procedures:

Water may be useful for minimizing vapors and for cooling containers. Use of SCBA's for large fires is recommended.

Unusual Fire and explosion hazards:

Spontaneous combustion when in contact with rags or similar articles.

NFPA Rating:

Health: 2

Flammability: 2

Reactivity: 0

Section V Environmental Information

Recommended Disposal:

Generation of waste can be avoided by applying leftover material normally. Larger amounts can be shipped to a permitted recycler of solvents and paint related materials. Spills should be picked up using a suitable inert absorbent. DO NOT flush into the sewer. DO NOT dispose of as household waste.

Product mixed with absorbent to no greater than 20% by volume may be shipped to a permitted hazardous waste facility, by a permitted hauler as a 'Hazardous Waste Solid ORM E.'

Environmental Data:

COD=ND

BOD5 = ND

96-hr. LC50=>100mg/1*

fathead minnows

Volatile Organic Content = 350g/1

* estimated from solvent component information.

Section VI Health Hazard Data

Eye Contact:

This material may cause irritation from direct contact with the liquid or its vapors. Only transient irritation is expected. However, if it persists, seek medical attention. Safety glasses should be used to avoid eye contact with liquid

Skin Contact:

Prolonged and repeated liquid contact can defat and dry the skin which may result in skin irritation and dermatitis. LD50 rabbit > 4.0g/kg. (estimated) Use of rubber gloves is recommended.

Inh alitation:

Breathing high concentrations of vapors may cause irritation of the nose and throat. Prolonged overexposure may lead to CNS depression with symptoms of drowsiness, dizziness and loss of coordination. If material is used in confined spaces use a half mask respirator equipped with organic vapor cartridges.

Ing estion:

This material has a low order of toxicity (> 5.0g/kg. rat, calculated from solvent composition data.) Excessive amounts may cause CNS depression. There is an ASPIRATION HAZARD. Liquid entering the lungs can cause severe damage.

Sug gested First Aid:

Tar.

Flush with water for 15 minutes with eyelids open. Get

medical attention

skin:

eyes:

Wash with soap and water. Remove contaminated

clothing and shoes.

Inhalation:

Remove victim to fresh air. Oxygen can be administered

if breathing is difficult.

ingestion:

Do not induce vomiting. Get medical attention.

Section VII

Reactivity Data

Stability	STABLE Conditions to avoid: Oxidizing agents
Incompatibility	Materials to avoid: Avoid heat, sparks and open flame. Avoid leaving any contaminated rags, paper and other combustibles which may undergo spontaneous combustion.
Hazardous Polymerization	WILL NOT OCCUR
Hazardous Decomposition	Combustion can produce dangerous levels of carbon monoxide and carbon dioxide. Saturated towels or rags can lead to spontaneous combustion. They should be placed in an appropriate safety can.

Section VIII Protective Equipment

Eye Protection: Safety Glasses ----- Skin Protection: Rubber Gloves

Ventilation:

This product should be used in well ventilated areas. Confined spaces should be checked for excessive concentration of vapors.

Respiratory Protection:

When using indoors in poorly ventilated areas, use a half mask respirator equipped with organic vapor cartridges.

Section IX Precautionary Information

Avoid eye and skin contact. Avoid prolonged and repeated breathing of vapors. Use only in well ventilated areas. Keep away from heat and open flames. May undergo spontaneous combustion when in contact with rags and other combustibles.

Section X Regulatory Information

Super fund Reauthorization Act (SARA) Title III
Sect ion 311/312 Hazard Categories
Immediate (acute) Health Hazard / Fire Hazard

Sect ion 313

No chemicals in this product exceed the de minimus reporting level established by SARA Title II. Section 313 and 40 CFR 372.

Toxic SubstancesControl Act (TSCA)

All components of this product are listed on the TSCA inventory.

Comprenhensive Environmental Response, Compensation and Liability act (CERCLA)

No chemicals in this product are subject to the reporting requirements of CERCLA.

California Safe Water and Toxic Enforcement Act (Prop. 65)

Based on information currently available, this product is not known to contain any chemical listed as carcinogens or reproductive toxins under Proposition 65.

Revision: 4/20/99