

SYRACUSE CITY SCHOOL DISTRICT  
725 HARRISON STREET  
SYRACUSE, NEW YORK 13210

03/09/90

Plasti-Kote Company, Inc.  
1000 Lake Road  
Medina OH 44256

OSHA's Hazard Communication Standard requires that you supply Material Safety Data Sheets (MSDS) for all hazardous substances which you produce. Please send properly completed Material Safety Data Sheets for the following chemical(s) which we purchased from your firm.


Car Color 3<sup>d</sup>  
Fast Drying Super Enamel 84  
New Fast Dry Engine Enamel 7A#

Thank you for your assistance. If you have any questions, please contact me at (315) 425-4286.

Sincerely,

*Carole E. Wasko*

Carole E. Wasko  
Coor. for Envir. Safety





**SECTION I - MATERIAL SAFETY DATA SHEET**  
**PLASTI-KOTE CO., INC.**  
 1000 LAKE ROAD  
 MEDINA, OHIO 44256

Date Prepared: 5/2/89  
 Telephone No: (216) 725-4511  
 Product Class: Aerosol Spray Paint  
 Shipping Name: Consumer Commodity

NE = None Established  
 NA = None Available  
 Special Notice: NONE

**HAZARD RATING**  
 1 = Extreme  
 3 = High  
 2 = Moderate  
 1 = Slight  
 0 = None



**PLASTI-KOTE SUPER ENAMELS**

**SECTION II - HAZARDOUS INGREDIENTS**



Ingredient	CAS Number	ACGIH PPM	TLV mg/m <sup>3</sup>	OSHA PEL	Vapor Pressure mm Hg at 20°C	PRODUCT IDENTITY: Colors		Lacquers		Primers		Dull Alum.		Alum.	
						T-1 T-16 T-35	T-2 T-24 T-36	T-3 T-5	T-4 T-26 T-37	T-5 T-19	T-6 T-27 T-40	T-7 T-19	T-8 T-19	T-9 T-29 T-42	T-10 T-30 T-43
* Acetone	67-64-1	750	1780	1000	186	33-42	26-33	10-15	40-50	15-20					
Aliphatic Hydrocarbon	64742-89-8	500	350	200	38										
Aromatic Hydrocarbon	64742-95-6	100	NE	100	3										
* n-Butyl Alcohol	71-36-3	50	150	100	4.2										
* 2-Butoxy Ethanol	111-76-2	25	120	NE	1.0										
* Cyclohexane	110-82-7	300	1050	300	78										
Ethyl Acetate	141-78-6	400	1400	400	69	0-5	5-10	0-5	0-5						
Ethyl Alcohol	64-17-5	1000	1900	1000	40	5-10	0-5	0-5	0-5						
Diacetone Alcohol	123-42-2	50	240	50	0.8	5-10	0-5	0-5	0-5						
Di-isobutyl Ketone	108-83-8	25	250	50	1.7										
Isobutyl Acetate	110-19-0	150	700	150	12.8										
* Isopropyl Alcohol	67-63-0	400	400	400	33	0-5	0-5	0-5	0-5						
* Methyl Ethyl Ketone	78-93-3	200	590	200	70										
* Methyl Isobutyl Ketone	108-10-1	50	205	100	16	0-5	0-5	0-5	5-10						
Mineral Spirits	64742-88-7	500	350	500	2.0										
Oxo Alcohol Ester	88230-35-7	NE	NE	NE	1.4										
* Toluene	108-88-3	100	375	100	22										
* 1,1,1-Trichloroethane	71-55-6	350	1900	350	100										
V. M. and P Naphtha	80330-30-6	500	350	500	15										
* Xylene	1330-20-7	100	435	100	5.1	5-10	5-10	30-40	0-5	45-50					
Propylene Glycol Monomethyl Ether	107-98-2	100	360	100	8.0										
<b>PROPELLANT</b>															
Propane	74-98-6	NE	NE	1000											
Isobutane mixture	75-28-5	NE	NE	NE											
n-Butane	106-97-8	800	1900	NE											
<b>NON-HAZARDOUS INGREDIENTS</b>															
Not Reg'd	Not Reg'd	Not Reg'd	Not Reg'd	Not Reg'd	Not Reg'd	14-19	9-14	20-24	10-15	8-10					

\* These Compounds are subject to the reporting requirements of Section 313 of SARA Title III.

**SECTION I - MATERIAL SAFETY DATA SHEET**  
**PLASTI-KOTE CO., INC.**  
 1000 LAKE ROAD  
 MEDINA, OHIO 44256

Date Prepared: 4/7/89  
 Telephone No. (216) 725-4511  
 Product Class: Aerosol Spray Paint  
 Shipping Name: Consumer Commodity  
 ORN-D Paint

NE = None Established  
 NA = None Available  
 Special Notice: NONE  
 HAZARD RATING  
 4 = Extreme  
 3 = High  
 2 = Moderate  
 1 = Slight  
 0 = None



Protective Equipment

**SECTION II - HAZARDOUS INGREDIENTS**

Ingredient	CAS Number	ACGIH PPM	TLV mg/m <sup>3</sup>	OSHA PEL	Vapor Pressure mm Hg at 20°C	PRODUCT IDENTITY:		Health	Flammability	Reactivity	% (wt)	% (wt)	% (wt)	% (wt)	% (wt)
						PART NUMBERS	Percent (wt)								
* Acetone	67-64-1	750	1780	1000	186	30-40	201 211 231	200	207	227	228				
Aliphatic Hydrocarbon	64742-89-8	500	350	200	38		202 221 232	206	223		10-15				
Aromatic Hydrocarbon	64742-95-6	100	NE	100	3		203 222 233	209			5-10				
* n-Butyl Alcohol	71-36-3	50	150	100	4.2		204 224	226							
2-Butoxy Ethanol	111-76-2	25	120	NE	1.0		205 225								
* Cyclohexane	110-82-7	300	1050	300	78		208 229								
Ethyl Acetate	141-78-6	400	1400	400	69	5-10									
Ethyl Alcohol	64-17-5	1000	1900	1000	40										
Diacetone Alcohol	123-42-2	50	240	50	0.8	5-6									
D-Isobutyl Ketone	108-83-8	25	250	50	1.7										
Isobutyl Acetate	110-19-0	150	700	150	12.8										
* Isopropyl Alcohol	67-63-0	400	400	400	33	0-5									
* Methyl Ethyl Ketone	78-93-3	200	590	200	70										
* Methyl Isobutyl Ketone	108-10-1	50	205	100	16										
Mineral Spirits	64742-88-7	500	350	500	2.0										
Oxo Alcohol Ester	88230-35-7	NE	NE	NE	1.4										
* Toluene	108-88-3	100	375	100	22										
* 1,1,1-Trichloroethane	71-55-6	350	1900	350	100										
V.M. and P Naphtha	8030-30-6	500	350	500	15										
* Xylene	1330-20-7	100	435	100	5.1										
*Lead Chromate as Chromate	18454-12-1	NA	0.05	0.05	NA	5-10					30-35				
Propylene Glycol Monomethyl Ether PROPPELLANT	107-98-2	100	360	100	8.0										
Propane	74-98-6	NE	NE	1000											
Isobutane	75-28-5	NE	NE	NE											
n-Butane	106-97-8	800	1900	NE											
NON-HAZARDOUS INGREDIENTS	Not Req'd	Not Req'd	Not Req'd	Not Req'd	Not Req'd	15-20									



\*These compounds are subject to the reporting requirements of Section 313 of SARA Title III.

**SECTION I - MATERIAL SAFETY DATA SHEET**  
**PLASTI-KOTE CO., INC.**  
 1000 LAKE ROAD  
 MEDINA, OHIO 44256

Date Prepared: 5/15/89  
 Telephone No. (216) 725-4511  
 Product Class: Aerosol Spray Paint  
 Shipping Name: Consumer Commodity

NE = None Established  
 NA = None Available  
 Special Notice: NONE

**HAZARD RATING**  
 4 = Extreme  
 3 = High  
 2 = Moderate  
 1 = Slight  
 0 = None



**SECTION II - HAZARDOUS INGREDIENTS**

Ingredient	CAS Number	ACGIH PPM	TLV mg/m <sup>3</sup>	OSHA PEL	Vapor Pressure mm Hg at 20°C	Percent (wt)	% (wt)	% (wt)	% (wt)	% (wt)	% (wt)
* Acetone	67-64-1	750	1780	1000	186	40-50	30-35	45-50	25-30		
Aliphatic Hydrocarbon	64742-89-8	500	350	200	38						
Aromatic Hydrocarbon	64742-95-6	100	NE	100	3						
* n-Butyl Alcohol	71-36-3	50	150	100	4.2						
2-Butoxy Ethanol	111-76-2	25	120	NE	1.0						
* Cyclohexane	110-82-7	300	1050	300	78						
Ethyl Acetate	141-78-6	400	1400	400	69	0-5	5-10		0-5		
Ethyl Alcohol	64-17-5	1000	1900	1000	40						
Diacetone Alcohol	123-42-2	50	240	50	0.8	0-5	0-5	0-5	0-5		
Di-isobutyl Ketone	108-83-8	25	250	50	1.7						
Isobutyl Acetate	110-19-0	150	700	150	12.8						
* Isopropyl Alcohol	67-63-0	400	400	400	33	0-5	0-5	0-5	5-10		
* Methyl Ethyl Ketone	78-93-3	200	590	200	70	0-5	0-5	0-5	0-5		
* Methyl Isobutyl Ketone	108-10-1	50	205	100	16	5-10	5-10	0-5	0-5		
Mineral Spirits	64742-89-7	500	350	500	2.0						
Oxo Alcohol Ester	88230-35-7	NE	NE	NE	1.4						
* Toluene	108-88-3	100	375	100	22	5-10			0-5		
* 1,1,1-Trichloroethane	71-55-6	350	1900	350	100						
V.M. and P Naphtha	8030-30-6	500	350	500	15						
* Xylene	1330-20-7	100	435	100	5.1	0-5	5-10	5-10	0-5		
*Lead Chromate as Chromate	18454-12-1	na	0.05 as Cr	0.05 mg/m <sup>3</sup> as Pb.	na	0-5					
Exxate 600	88230-35-7	na	0.05 as Cr	0.05 mg/m <sup>3</sup> as Pb.	na	0-5					
Acetic Acid Ester	88230-35-7	na	0.05 as Cr	0.05 mg/m <sup>3</sup> as Pb.	na	0-5					
PROPELLANT											
Propane	74-98-6	NE	NE	1000							
Isobutane mixture	75-28-5	NE	NE	NE							
n-Butane	106-97-8	800	1900	NE		19	19	23	23		
NON-HAZARDOUS INGREDIENTS											
* These compounds are subject to the reporting requirements of Section 313 of SARA Title III.											