

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)

Form Approved  
OMB No. 1218-0072



IDENTITY (As Used on Label and List)  
Dick Blick Block Printing Ink

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

**Section I**

Manufacturer's Name  
Putnam Color & Dye  
Address (Number, Street, City, State, and ZIP Code)  
1558 S. Henderson St.  
Galesburg, IL 61401

Emergency Telephone Number  
(309) 342-0179  
Telephone Number for information  
(309) 342-0179  
Date Prepared  
June 3, 1991  
Signature of Preparer (optional)  
D. L. Wright

7961 - all codes  
7962 - all codes  
7963 - all codes  
64623 - all codes  
64624 - all codes  
64625 - all codes

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Contains no hazardous substance per OSHA 29 CFR 1940.1200				

Material is a water based product with the AP Seal. Products with the AP Approved Products Seal of the Art and Craft Materials Institute are certified in a program of toxicological evaluation by a medical expert to contain no material in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified by the Institute to be labeled in accordance with the voluntary chronic hazard Labeling Standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200 (c).

**Section III - Physical/Chemical Characteristics**

Boiling Point Range 215-225 °F	Specific Gravity (H <sub>2</sub> O = 1) Range 1.03-1.68
Vapor Pressure (mm Hg) Not Determined	Melting Point Not Determined
Vapor Density (AIR = 1) Lighter Than Air	Evaporation Rate (Butyl Acetate = 1) Slower Than Ether
Solubility in Water Completely Soluble In Water	
Appearance and Odor Various Colors & Odorless	

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used) Not Available	Flammable Limits Unknown	LEL	UEL
Extinguishing Media CO <sub>2</sub> , Foam or Water			
Special Fire Fighting Procedures None Known			
Unusual Fire and Explosion Hazards None			

V-1115

