

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

45199-02-
~~45131-00~~
~~45132-00~~
 45123-004
 3102-004



IDENTITY (As Used on Label and List)
 Dick Blick Premium Tempera

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Putnam Color & Dye	Emergency Telephone Number (309)342-0179	45145-all codes
Address (Number, Street, City, State, and ZIP Code) 1558 S. Henderson Street	Telephone Number for Information (309)342-0179	45035-all codes
Galesburg, IL 61401	Date Prepared June 3, 1991	45036-all codes
	Signature of Preparer (optional) D. L. Wright	45146-all codes
		45037-all codes

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Contains no hazardous substance per OSHA 29 CFR 1940.1200				

Material is a water based product with the CP Seal. Products with the CP Certified Products Seal of the Art and Craft Materials Institute are certified in a program of toxicological evaluation by a medical expert to contain no material in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified by the Institute to be labeled in accordance with the voluntary chronic hazard Labeling Standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200 (c).

Section III — Physical/Chemical Characteristics

Boiling Point Range 215-225°F	Specific Gravity (H ₂ O = 1) Range 1.03-1.68
Vapor Pressure (mm Hg.) Not Determined	Melting Point Not Determined
Vapor Density (AIR = 1) Lighter Than Air	Evaporation Rate (Butyl Acetate = 1) Slower Than Ether
Solubility in Water Completely Soluble In Water	
Appearance and Odor Various Colors & Odorless	

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Not Available	Flammable Limits Unknown	LEL	UEL
Extinguishing Media CO ₂ , Foam, Or Water			
Special Fire Fighting Procedures None Known			

Unusual Fire and Explosion Hazards
 None

V-1113

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

45199-02
45131-00
45132-00
45123-00
3102-00



IDENTITY (As Used on Label and List)
Dick Blick Premium Tempera

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name <u>Putnam Color & Dye</u>	Emergency Telephone Number (309) 342-0179	45145-all codes X 45035-all codes
Address (Number, Street, City, State, and ZIP Code) 1558 S. Henderson Street	Telephone Number for Information (309) 342-0179	X 45036-all codes
Galesburg, IL 61401	Date Prepared June 3, 1991	45146-all codes
	Signature of Preparer (optional) D. L. Wright	X 45037-all codes

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Contains no hazardous substance per OSHA 29 CFR 1940.1200				

Material is a water based product with the CP Seal. Products with the CP Certified Products Seal of the Art and Craft Materials Institute are certified in a program of toxicological evaluation by a medical expert to contain no material in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified by the Institute to be labeled in accordance with the voluntary chronic hazard Labeling Standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200 (c).

Section III — Physical/Chemical Characteristics

Boiling Point Range 215-225°F	Specific Gravity (H ₂ O = 1) Range 1.03-1.68
Vapor Pressure (mm Hg) Not Determined	Melting Point Not Determined
Vapor Density (AIR = 1) Lighter Than Air	Evaporation Rate (Butyl Acetate = 1) Slower Than Ether
Solubility in Water Completely Soluble In Water	
Appearance and Odor Various Colors & Odorless	

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Not Available	Flammable Limits Unknown	LEL	UEL
Extinguishing Media CO ₂ , Foam, Or Water			
Special Fire Fighting Procedures None Known			
Unusual Fire and Explosion Hazards None			

