

Section I. General Information

MSDS Identifier Code

Supplier ID: Ricoh Product Code: 4120-26

Identity: Savin Dispersant for Black Toner

Manufacturer's Name and Address:

 Ricoh Corporation
 5 Dedrick Place
 West Caldwell, NJ 07006

Distributor's Name and Address:

 Savin Corporation
 P.O. Box 10270
 Stamford, CT 06904

Emergency Telephone Number: (800) 336-6737

Telephone Number for Information: (201) 882-2000, (800) 336-6737

Synonyms & Common Names: Savin Product Code 7745, Savin T-D Pak 7720, Savin Dispersant for Black Toner

Uses: 7230/7300/7350/7450/V35

Chemical Formula: Hydrotreated heavy naphtha (ISOPAR)

Registry numbers

CAS Number: 64742-48-9

RTECS Number: N/A

Date Prepared: 02/08/90 Filed/Prepared By: Kristina Sage

Section II. Hazardous Ingredients/Identity Information

Composition

Component	%	CAS #	OSHA Pel	ACGIH TLV
Hydrotreated heavy naphtha (ISOPAR)	100%	64742-48-9	N/A	300 ppm

Exposure Limits (TLV/PEL)

OSHA: N/A

NIOSH: N/A

ACGIH: 300 ppm


State: N/A

Other: N/A

Section III. Physical/Chemical Characteristics

Boiling Point: 161-200C

Specific Gravity: 0.75 @ 15C



Vapor Pressure: <10mmHg @ 25C % Volatile by Volume: 100%
Melting Point: Less than -18C Vapor Density (Air=1): Greater than 5
Evaporation Rate (n-BuAc=1): Approx. 0.3

Solubility in Water: Negligible: Less than 0.1%

Appearance and Odor: Clear water white liquid, faint petroleum hydrocarbon odor.

Section IV. Fire and Explosion Hazard Data

Flash Point and Method: 43C (109.4F) T.C.C.

Explosive Limits: LEL 0.7 UEL 6.5

Comments: N/A

Extinguishing Media: Foam, dry chemicals, or carbon dioxide

Special Fire-Fighting Procedures: If a leak or spill has ignited, use standard fire-fighting procedures for petroleum based liquids. Minimize breathing gases, vapor, fumes or decomposition products. Fire-fighters should use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Unusual Fire and Explosion Hazards: Will not occur during normal use.

Section V. Reactivity Data

Stability: Stable

Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): Avoid contact with strong oxidizers such as Liquid Cl₂ or conc. O₂.

Hazardous Decomposition or Byproducts: Carbon monoxide and other decomposition products in the case of incomplete combustion.

Hazardous Polymerization: Will not Occur

Conditions to Avoid: N/A

Section VI. Health and Hazard Data

Routes of Entry: Eyes, inhalation, ingestion

Health Hazards of Short-Term exposure (Acute)

Eyes: Slight conjunctival irritation.

Skin: Mild irritation under conditions of excessive exposure. (Primary irritation index 1.75).

Inhalation: No untoward effects.

LD50 (rat): Greater than 12,400 mg/m³ (approximately 2000 ppm).

Ingestion: Practically non-toxic.

LD50 (rat): Greater than 10g/kg bodyweight.

Health Hazards of Long-Term exposure (Chronic): Health studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquid, vapor, mist or fumes should be minimized.

Carcinogenicity: N/A

NTP? No IARC Monographs? No OSHA Regulated? No

Signs and Symptoms of Exposure: High vapor concentrations (greater than approximately 1000 ppm) are irritative to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, and may have other central nervous system effects.

Medical Conditions Generally Aggravated by Exposure: N/A

Emergency and First Aid Procedures

First Aid

Eyes: If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides.

Skin: In the case of skin contact, remove any contaminated clothing and cleanse skin thoroughly with waterless hand cleaner followed by washing with soap and water.

Inhalation: If overcome by vapor, remove from exposure and call a physician immediately.

Ingestion: If ingestion occurs, do not induce vomiting; call a physician immediately.

Additional Information: N/A

Section VII. Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled: Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth, or other suitable absorbent to spill areas. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or

impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

Waste Disposal Method: Waste liquid should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Disposal regulations vary from locality to locality, therefore, consult your local office of the EPA to determine proper method of disposal.

Precautions to Be Taken in Handling and Storing:

CAUTION - COMBUSTIBLE LIQUID

Keep away from heat, open flame, and sparks. Keep out of reach of children.

Other Precautions: Empty containers retain residue (liquid and/or vapor) and can be dangerous. In order to avoid the risk of explosion, do not pressure or expose containers to heat, flame, sparks, or other sources of ignition.

Section VIII. Control Measures

Respiratory Protection: None needed under normal conditions of use.

Ventilation

Local Exhaust: None needed under normal conditions of use.

Special: None

Mechanical (general): Adequate ventilation.

Other: None

Protective Glove: None needed under normal conditions of use.

Eye Protection: None needed under normal conditions of use.

Other Protective Clothing or Equipment: None needed under normal conditions of use.

Work and Hygienic Practices: Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at the end of work periods. Product is readily removed from skin by waterless hand cleaners followed by washing with soap and water.